

Package ‘MDgof’

September 18, 2026

Title Various Methods for the Goodness-of-Fit Problem in D>1 Dimensions

Version 1.2.0

Description Provides multivariate goodness-of-fit testing with a common interface for several test statistics. Null models may be simple or include parameter estimation, with p-values obtained by parametric bootstrap simulation. The function `gof_test_adjusted_pvalue()` combines several tests and computes a p-value adjusted for simultaneous inference. The function `gof_power()` estimates test power. The functions `hybrid_test()` and `hybrid_power()` use Monte Carlo samples under the null together with two-sample procedures. The function `run.studies()` supports systematic power comparisons of user-supplied and included methods across case studies. See the included vignettes for method details and references.

License GPL (>= 2)

Encoding UTF-8

LinkingTo Rcpp

Imports Rcpp, parallel, stats, microbenchmark, spatstat.geom, spatstat.explore, FNN, copula, mvtnorm, ggplot2, MD2sample (>= 1.4.0)

Suggests rmarkdown, knitr, testthat (>= 3.0.0)

VignetteBuilder knitr

Depends R (>= 3.5)

LazyData true

Config/roxygen2/version 8.0.0

Config/testthat/edition 3

NeedsCompilation yes

Author Wolfgang Rolke [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-3514-726X>>)

Maintainer Wolfgang Rolke <wolfgang.rolke@upr.edu>

Repository CRAN

Date/Publication 2026-09-18 12:42:04 UTC

Contents

as.data.frame.MDgof_power	3
bakshaev_rudzkis	3
case.studies	4
case.studies.cont	5
case.studies.cont.D5	5
case.studies.disc	6
case.studies.est	6
chi_cont_test	7
chi_disc_test	8
chi_power	8
compute_M_for_dtaset	10
discretize	10
draw_case	11
estimateEV	12
examples.mdgof.vignette	12
gauss_kernel_matrix	13
gen.cop	13
gen_eval	14
gof_power	14
gof_test	17
gof_test_adjusted_pvalue	19
grad_mat	21
hybrid.mdgof.vignette	22
hybrid_power	22
hybrid_test	24
ksd	25
newTS	26
p2dC	26
power_studies_cont_D5_hybrid_results	27
power_studies_cont_D5_results	27
power_studies_cont_est_results	28
power_studies_cont_hybrid_results	28
power_studies_cont_nMC5_D5_hybrid_results	29
power_studies_cont_nMC5_hybrid_results	29
power_studies_cont_results	30
power_studies_disc_est_results	30
power_studies_disc_hybrid_results	31
power_studies_disc_nMC5_hybrid_results	31
power_studies_disc_results	32
print.MDgof_power	32
print.MDgof_test	33
RipleyK	34
run.studies	34
sq2rec	36
TS_cont	36
TS_disc	37

as.data.frame.MDgof_power	<i>Convert an MDgof power result to a data frame</i>
---------------------------	--

Description

Convert an MDgof power result to a data frame

Usage

```
## S3 method for class 'MDgof_power'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)
```

Arguments

x	An object of class "MDgof_power".
row.names	Ignored.
optional	Ignored.
...	Currently unused.

Value

A data frame with columns for the alternative parameter, method, power estimate, Monte Carlo standard error, and Wilson confidence limits.

bakshaev_rudzkis	<i>Run Bakshaev and Rudzkis Test</i>
------------------	--------------------------------------

Description

Run Bakshaev and Rudzkis Test

Usage

```
bakshaev_rudzkis(dta, rnull, p, m_eval = 100L, nsim = 200L, nsim_mc = 1000L)
```

Arguments

dta	data matrix.
rnull	generate new data.
p	, parameters for parametric bootstrap.
m_eval	=100, number of evaluation points of kde.
nsim	=200, number of simulation runs.
nsim_mc	=1000, number of simulation runs.

Value

a list

`case.studies`*Create various case studies*

Description

This function creates the functions needed to run the various case studies.

Usage

```
case.studies(  
  which,  
  Continuous = TRUE,  
  WithEstimation = FALSE,  
  Dim = 2,  
  nsample = 250,  
  nbins = c(5, 5),  
  ReturnCaseNames = FALSE  
)
```

Arguments

<code>which</code>	name or number of the case study.
<code>Continuous</code>	= TRUE for continuous data
<code>WithEstimation</code>	=FALSE, with parameter estimation
<code>Dim</code>	=2 dimension of data
<code>nsample</code>	=250, sample size.
<code>nbins</code>	=c(5,5) number of bins in x and y direction
<code>ReturnCaseNames</code>	=FALSE, just return names of case studies?

Value

a list of functions

case.studies.cont	<i>Create various case studies for continuous data without parameter estimation</i>
-------------------	---

Description

This function creates the functions needed to run the various case studies.

Usage

```
case.studies.cont(which, nsample = 250, ReturnCaseNames = FALSE)
```

Arguments

which	name of the case study.
nsample	=250, sample size.
ReturnCaseNames	=FALSE, just return names of case studies?

Value

a list of functions

case.studies.cont.D5	<i>Create various case studies for continuous data in 5 dimensions without parameter estimation</i>
----------------------	---

Description

This function creates the functions needed to run the various case studies.

Usage

```
case.studies.cont.D5(which, nsample = 250, ReturnCaseNames = FALSE)
```

Arguments

which	name of the case study.
nsample	=250, sample size.
ReturnCaseNames	=FALSE, just return names of case studies?

Value

a list of functions

case.studies.disc	<i>Discretize 2D data from case studies</i>
-------------------	---

Description

This function provides the info necessary to run the case studies for discrete data.

Usage

```
case.studies.disc(
  which,
  WithEstimation = FALSE,
  nbins = c(5, 5),
  nsample = 250
)
```

Arguments

which	name or number of desired case study.
WithEstimation	= FALSE, case study with or without parameter estimation.
nbins	=c(5, 5) number of bins to use in x and y direction
nsample	= 250, required sample size

Value

a list with needed stuff

case.studies.est	<i>Create various case studies with parameter estimation</i>
------------------	--

Description

This function creates the functions needed to run the various case studies that include parameter estimation.

Usage

```
case.studies.est(which, nsample = 250, ReturnCaseNames = FALSE)
```

Arguments

which	name of the case study.
nsample	=250, sample size.
ReturnCaseNames	=FALSE, just return names of case studies?

Value

a list of functions

chi_cont_test	<i>Chi-square test for 2D data</i>
---------------	------------------------------------

Description

This function does the chi square goodness-of-fit test for continuous data in two dimensions.

Usage

```
chi_cont_test(
  dta,
  pnull,
  phat = function(x) -99,
  Ranges = matrix(c(-Inf, Inf, -Inf, Inf), 2, 2),
  nbins = c(5, 5),
  minexpcount = 5,
  SuppressMessages = TRUE
)
```

Arguments

dta	a matrix of numbers.
pnull	function to calculate expected counts.
phat	=function(x) -99, function to estimate parameters of pnull.
Ranges	=matrix(c(-Inf, Inf, -Inf, Inf),2,2), a 2x2 matrix with lower and upper bounds
nbins	=c(5,5) number of bins in x and y direction
minexpcount	=5 minimum counts required per bin
SuppressMessages	=FALSE, should info be shown?

Value

a matrix with statistics, p values and degree of freedoms

chi_disc_test	<i>Chi-square test for discrete 2D data</i>
---------------	---

Description

This function does the chi square goodness-of-fit test for discrete data in two dimensions.

Usage

```
chi_disc_test(
  dta,
  pnull,
  dnull,
  phat = function(x) -99,
  minexpcount = 5,
  SuppressMessages = FALSE
)
```

Arguments

dta	a matrix of numbers.
pnull	distribution function to calculate expected counts.
dnull	density to calculate expected counts.
phat	=function(x) -99, function to estimate parameters of pnull.
minexpcount	=5 minimum counts required per bin
SuppressMessages	=TRUE, should info be shown?

Value

a vector with statistic, p value and degree of freedom

chi_power	<i>Power Estimation of Chi Square Tests</i>
-----------	---

Description

This function finds the power of various chi-square tests.

Usage

```
chi_power(
  pnull,
  ralt,
  param_alt,
  phat = function(x) -99,
  alpha = 0.05,
  Ranges = matrix(c(-Inf, Inf, -Inf, Inf), 2, 2),
  nbins = c(5, 5),
  rate = 0,
  minexpcount = 5,
  dnull = function(x) -99,
  Retry = TRUE,
  SuppressMessages = TRUE,
  B = 1000
)
```

Arguments

pnull	distribution function to find cdf under null hypothesis
ralt	function to generate data under alternative hypothesis
param_alt	vector of parameter values for distribution under alternative hypothesis
phat	=function(x) -99, function to estimate parameters
alpha	=0.05, the level of the hypothesis test
Ranges	=matrix(c(-Inf, Inf, -Inf, Inf),2,2), a 2x2 matrix with lower and upper bounds, if any
nbins	=c(5, 5), number of bins for chi square tests
rate	=0 rate of Poisson if sample size is random, 0 if sample size is fixed
minexpcount	=5 minimal expected bin count required
dnull	=function(x) -99, density function to find probabilities under null hypothesis, mostly used for discrete data, or -99 if missing.
Retry	=TRUE, retry if test fails?
SuppressMessages	=TRUE, should info be shown?
B	=1000 number of simulation runs to find power

Value

A numeric matrix of power values.

compute_M_for_dtaset	<i>Compute M statistic for one dtaset</i>
----------------------	---

Description

Compute M statistic for one dtaset

Usage

```
compute_M_for_dtaset(dta, Eval, hs, rnull, p, nsim_mc)
```

Arguments

dta	data matrix.
Eval	matrix of evaluations
hs	bandwidths
rnull	generate new data
p	values for parametric bootstrap
nsim_mc	number of simulation runs

Value

a double

discretize	<i>Bins continuous data</i>
------------	-----------------------------

Description

Bins continuous data

Usage

```
discretize(x, Range, nbins, ChangeVals = FALSE)
```

Arguments

x	A numeric matrix with two columns.
Range	range of variables
nbins	number of bins.
ChangeVals	=FALSE, should values of discrete rv's be adjusted to midpoints?

Value

A numeric matrix

draw_case	<i>Create plot for any case study</i>
-----------	---------------------------------------

Description

This function illustrates any of the case studies.

Usage

```
draw_case(  
  which,  
  Continuous = TRUE,  
  WithEstimation = FALSE,  
  Dim = 2,  
  palt,  
  nsample = 1000,  
  Dms = c(1, 2),  
  AltOnly = FALSE  
)
```

Arguments

which	name or number of the case study.
Continuous	= TRUE for continuous data
WithEstimation	=FALSE, with parameter estimation
Dim	=2 dimension of data
palt	parameter for alternative. If missing value in study is used.
nsample	=250, sample size.
Dms	=c(1,2), which dimensions are to be shown (for 5D data).
AltOnly	= FALSE show only graph for alternative?

Value

A ggplot2 plot object.

estimateEV

Estimate E and Var/n at Eval for given h, using MC from rnull

Description

Estimate E and Var/n at Eval for given h, using MC from rnull

Usage

```
estimateEV(rnull, p, Eval, h, nsim_mc, n)
```

Arguments

rnull	generate data under the null hypothesis.
p	values for rnull
Eval	matrix of evaluations
h	bandwith, a double
nsim_mc	number of simulation runs
n	sample size

Value

a matrix

examples.mdgof.vignette

examples.mdgof.vignette

Description

stuff needed to run vignette fast enough to pass CRAN

Usage

```
examples.mdgof.vignette
```

Format

'examples.mdgof.vignette':

A list

gauss_kernel_matrix	<i>Find gaussian kernel pdf</i>
---------------------	---------------------------------

Description

Find gaussian kernel pdf

Usage

```
gauss_kernel_matrix(Eval, S, h)
```

Arguments

Eval	a matrix.
S	a matrix
h	bandwidth, a double

Value

a matrix

gen.cop	<i>Create copula objects</i>
---------	------------------------------

Description

This function creates copula objects

Usage

```
gen.cop(family, p, d = 2)
```

Arguments

family	name of copula.
p	parameter of copula.
d	dimension

Value

a copula object

gen_eval	<i>Find evaluation points</i>
----------	-------------------------------

Description

Find evaluation points

Usage

```
gen_eval(rnull, p, m)
```

Arguments

rnull	a function that generate new data.
p	a vector of parameters for rnull.
m	size of matrix.

Value

a matrix

gof_power	<i>Power estimation of goodness-of-fit tests.</i>
-----------	---

Description

Find the power of various goodness-of-fit tests.

Usage

```
gof_power(
  pnull,
  rnull,
  ralt,
  param_alt,
  phat = function(x) -99,
  dnull = function(x) -99,
  TS,
  TSextra,
  With.p.value = FALSE,
  alpha = 0.05,
  Ranges = matrix(c(-Inf, Inf, -Inf, Inf), 2, 2),
  nbins = c(5, 5),
  minexpcount = 5,
  rate = 0,
```

```

    SuppressMessages = FALSE,
    maxProcessor,
    B = 1000,
    CI = FALSE,
    conf.level = 0.95,
    seed = NULL
)

```

Arguments

<code>pnull</code>	function to find cdf under null hypothesis
<code>rnull</code>	function to generate data under null hypothesis
<code>ralt</code>	function to generate data under alternative hypothesis
<code>param_alt</code>	vector of parameter values for distribution under alternative hypothesis
<code>phat</code>	=function(x) -99, function to estimate parameters from the data, or -99
<code>dnull</code>	=function(x) -99, density function under the null hypothesis, if available, or -99 if missing
<code>TS</code>	user supplied function to find test statistics. For discrete data it may have signature <code>TS(x)</code> or <code>TS(x, TSextra)</code> ; the legacy 3- or 4-argument form is also accepted.
<code>TSextra</code>	list provided to <code>TS</code> (optional)
<code>With.p.value</code>	=FALSE does user supplied routine return p values?
<code>alpha</code>	=0.05, the level of the hypothesis test
<code>Ranges</code>	=matrix(c(-Inf, Inf, -Inf, Inf),2,2), a 2x2 matrix with lower and upper bounds, if any, for chi-square tests
<code>nbins</code>	=c(5, 5), number of bins for chi square tests.
<code>minexpcount</code>	=5 minimal expected bin count required for chi square tests.
<code>rate</code>	=0 rate of Poisson if sample size is random, 0 if sample size is fixed
<code>SuppressMessages</code>	=FALSE, should informative messages be shown?
<code>maxProcessor</code>	maximum of number of processors to use, 1 if no parallel processing is needed or number of cores-1 if missing
<code>B</code>	=1000 number of simulation runs
<code>CI</code>	=FALSE if TRUE, return Monte Carlo standard errors and Wilson confidence intervals for the estimated power.
<code>conf.level</code>	=0.95 confidence level used when <code>CI=TRUE</code> .
<code>seed</code>	=NULL, optional seed for simulations

Details

For details on the usage of this routine consult the vignette with `vignette("MDgof", "MDgof")`

Value

By default, a numeric matrix (or vector for one alternative) of power values. If CI=TRUE, an object of class "MDgof_power" containing power estimates, Monte Carlo standard errors, and Wilson confidence limits.

Examples

```
# All examples are run with B=10 and maxProcessor=1 to pass CRAN checks.
# This is obviously MUCH TO SMALL for any real usage.
# Power of tests if null hypothesis specifies a bivariate standard normal
# distribution but data comes from a bivariate normal with different means,
# without parameter estimation.
rnull=function() mvtnorm::rmvnorm(100, c(0, 0))
ralt=function(p) mvtnorm::rmvnorm(100, c(p, p))
pnull=function(x) {
  if(!is.matrix(x)) return(mvtnorm::pmvnorm(rep(-Inf, 2), x))
  apply(x, 1, function(x) mvtnorm::pmvnorm(rep(-Inf, 2), x))
}
gof_power(pnull, rnull, ralt, c(0, 1), B=10, maxProcessor = 1)
# Same as above, but now with density included
dnull=function(x) {
  if(!is.matrix(x)) return(mvtnorm::dmvnorm(x))
  apply(x, 1, function(x) mvtnorm::dmvnorm(x))
}
gof_power(pnull, rnull, ralt, c(0, 1), dnull=dnull, B=10, maxProcessor = 1)
# Power of tests when null hypothesis specifies a bivariate normal distribution,
# with mean parameter estimated, whereas data comes from a t distribution
rnull=function(p) mvtnorm::rmvnorm(100, p)
ralt=function(df) mvtnorm::rmvt(100, sigma=diag(2), df=df)
pnull=function(x,p) {
  if(!is.matrix(x)) return(mvtnorm::pmvnorm(rep(-Inf, 2), x, mean=p))
  apply(x, 1, function(x) mvtnorm::pmvnorm(rep(-Inf, 2), x, mean=p))
}
dnull=function(x, p) {
  if(!is.matrix(x)) return(mvtnorm::dmvnorm(x, mean=p))
  apply(x, 1, function(x) mvtnorm::dmvnorm(x, mean=p))
}
phat=function(x) apply(x, 2, mean)
gof_power(pnull, rnull, ralt, c(50, 5), dnull=dnull, phat=phat, B=10, maxProcessor = 1)
# Example of a discrete model, with parameter estimation
# Under null hypothesis:  $X \sim \text{Bin}(10, p)$ ,  $Y|X \sim \text{Bin}(5, 0.5+x/100)$ 
# Under alternative hypothesis:  $X \sim \text{Bin}(10, p)$ ,  $Y|X \sim \text{Bin}(5, K+x/100)$ 
rnull=function(p=0.5) {
  x=stats::rbinom(1000, 10, p)
  y=stats::rbinom(1000, 5, 0.5+x/100)
  MDgof::sq2rec(table(x, y))
}
ralt=function(K=0.5) {
  x=stats::rbinom(1000, 10, 0.5)
  y=stats::rbinom(1000, 5, K+x/100)
  MDgof::sq2rec(table(x, y))
}
```

```

pnull=function(x, p) {
  f=function(x) sum(dbinom(0:x[1], 10, p[1])*pbinom(x[2], 5, 0.5+0:x[1]/100))
  if(!is.matrix(x)) x=rbind(x)
  apply(x, 1, f)
}
phat=function(x) {
  tx=tapply(x[,3], x[,1], sum)
  mean(rep(as.numeric(names(tx)), times=tx))/10
}
gof_power(pnull, rnull, ralt, c(0.5, 0.6), phat=phat, B=10, maxProcessor = 1)

```

gof_test

*Tests for the multivariate goodness-of-fit problem***Description**

This function runs a number of goodness-of-fit tests using Rcpp and parallel computing. The result is an object of class "MDgof_test". The object retains the traditional \$statistics and \$p.values components and also contains a data-frame representation and metadata about the test.

Usage

```

gof_test(
  x,
  pnull,
  rnull,
  phat = function(x) -99,
  dnull = function(x) -99,
  TS,
  TSextra,
  rate = 0,
  nbins = c(5, 5),
  Ranges = matrix(c(-Inf, Inf, -Inf, Inf), 2, 2),
  minexpcount = 5,
  maxProcessor,
  doMethods,
  B = 5000,
  seed = NULL,
  ReturnTSextra = FALSE
)

```

Arguments

x	a matrix with the data set
pnull	cdf under the null hypothesis
rnull	routine to generate data under the null hypothesis

phat	=function(x) -99, function to estimate parameters from the data, or -99 if no parameters are estimated
dnull	=function(x) -99, density function under the null hypothesis, if available, or -99 if missing
TS	user supplied function to find test statistics, if any. For discrete data it may have signature TS(x) or TS(x, TSextra); the legacy 3- or 4-argument form is also accepted.
TSextra	(optional) list passed to TS, if needed.
rate	=0 rate of Poisson if sample size is random, 0 if sample size is fixed
nbins	=c(5, 5) number of bins for chi-square tests
Ranges	=matrix(c(-Inf, Inf, -Inf, Inf), 2, 2), a 2x2 matrix with lower and upper bounds, if any, for chi-square tests
minexpcount	=5 minimal expected bin count required
maxProcessor	number of processors to use in parallel processing.
doMethods	a vector of codes for the methods to include. If ="all", it does all the included tests. #missing it runs a default selection. I
B	=5000 number of simulation runs. If B=0 the routine returns the test statistics.
seed	=NULL, optional seed for reproducibility
ReturnTSextra	=FALSE, should setup info be returned?

Details

For details on the usage of this routine consult the vignette with vignette("MDgof", "MDgof")

Value

An object of class "MDgof_test". Its main components are results, a data frame with method, statistic and p-value; statistics and p. values, retained for backward compatibility; parameters, the parameter estimates when present; and metadata, information about the calculation. If B=0, p-values are NA.

Examples

```
# All examples are run with B=10 and maxProcessor=1 to pass CRAN checks.
# This is obviously MUCH TO SMALL for any real usage.
# Tests to see whether data comes from a bivariate standard normal distribution,
# without parameter estimation.
rnull=function() mvtnorm::rmvnorm(100, c(0, 0))
x=rnull()
pnull=function(x) {
  if(!is.matrix(x)) return(mvtnorm::pmvnorm(rep(-Inf, 2), x))
  apply(x, 1, function(x) mvtnorm::pmvnorm(rep(-Inf, 2), x))
}
z <- gof_test(x, pnull, rnull, B=10, maxProcessor = 1)
z
z$results
summary(z)
```

```

as.data.frame(z)
# Same as above, but now with density included
dnull=function(x) {
  if(!is.matrix(x)) return(mvtnorm::dmvnorm(x))
  apply(x, 1, function(x) mvtnorm::dmvnorm(x))
}
gof_test(x, pnull, rnull, dnull=dnull, B=20, maxProcessor = 1)
# Tests to see whether data comes from a standard normal distribution,
# with mean parameter estimated.
rnull=function(p) mvtnorm::rmvnorm(100, p)
x=rnull(c(0,1))
pnull=function(x,p) {
  if(!is.matrix(x)) return(mvtnorm::pmvnorm(rep(-Inf, 2), x, mean=p))
  apply(x, 1, function(x) mvtnorm::pmvnorm(rep(-Inf, 2), x, mean=p))
}
dnull=function(x, p) {
  if(!is.matrix(x)) return(mvtnorm::dmvnorm(x, mean=p))
  apply(x, 1, function(x) mvtnorm::dmvnorm(x, mean=p))
}
phat=function(x) apply(x, 2, mean)
gof_test(x, pnull, rnull, dnull=dnull, phat=phat,B=20, maxProcessor = 1)
# Example of a discrete model, with parameter estimation
#  $X \sim \text{Bin}(10, p1)$ ,  $Y|X=x \sim \text{Bin}(5, p2+x/100)$ 
rnull=function(p) {
  x=rbinom(1000, 10, p[1])
  y=rbinom(1000, 5, p[2]+x/100)
  MDgof::sq2rec(table(x, y))
}
pnull=function(x, p) {
  f=function(x) sum(dbinom(0:x[1], 10, p[1])*pbinom(x[2], 5, p[2]+0:x[1]/100))
  if(!is.matrix(x)) x=rbind(x)
  apply(x, 1, f)
}
phat=function(x) {
  tx=tapply(x[,3], x[,1], sum)
  p1=mean(rep(as.numeric(names(tx)), times=tx))/10
  ty=tapply(x[,3], x[,2], sum)
  p2=mean(rep(as.numeric(names(ty)), times=ty))/5-p1/10
  c(p1, p2)
}
x=rnull(c(0.5, 0.5))
gof_test(x, pnull, rnull, phat=phat,B=10, maxProcessor = 1)

```

gof_test_adjusted_pvalue

Adjusted p values

Description

This function runs a number of goodness-of-fit tests using Rcpp and parallel computing and then finds the correct p value for the combined tests.

Usage

```

gof_test_adjusted_pvalue(
  x,
  pnull,
  rnull,
  phat = function(x) -99,
  dnull = function(x) -99,
  B = c(5000, 1000),
  seed = NULL,
  nbins = c(5, 5),
  minexpcount = 5,
  Ranges = matrix(c(-Inf, Inf, -Inf, Inf), 2, 2),
  SuppressMessages = FALSE,
  maxProcessor,
  doMethods
)

```

Arguments

x	matrix with data
pnull	cdf under the null hypothesis
rnull	routine to generate data under the null hypothesis
phat	=function(x) -99, function to estimate parameters from the data, or -99 if no parameters are estimated
dnull	=function(x) -99, density function under the null hypothesis, if available, or -99 if missing
B	=c(5000, 1000), number of simulation runs for permutation test and for estimation of the empirical distribution function.
seed	=NULL
nbins	=c(5, 5), number of bins for chi square tests (2D only).
minexpcount	= 5, minimum required expected counts for chi-square tests.
Ranges	=matrix(c(-Inf, Inf, -Inf, Inf),2,2) a 2x2 matrix with lower and upper bounds.
SuppressMessages	= FALSE, show informative messages?
maxProcessor	number of cores for parallel processing.
doMethods	Which methods should be included? If missing a small number of methods that generally have good power are used.

Details

For details consult the vignette("MDgof","MDgof")

Value

A named numeric vector containing the individual p-values and the adjusted minimum-p value in the final element, named Min p.

Examples

```
# All examples are run with B=10 and maxProcessor=1 to pass CRAN checks.
# This is obviously MUCH TO SMALL for any real usage.
# Tests to see whether data comes from a bivariate standard normal distribution,
# without parameter estimation.
rnull=function() mvtnorm::rmvnorm(100, c(0, 0))
x=rnull()
pnull=function(x) {
  if(!is.matrix(x)) return(mvtnorm::pmvnorm(rep(-Inf, 2), x))
  apply(x, 1, function(x) mvtnorm::pmvnorm(rep(-Inf, 2), x))
}
dnull=function(x) {
  if(!is.matrix(x)) return(mvtnorm::dmvnorm(x))
  apply(x, 1, function(x) mvtnorm::dmvnorm(x))
}
gof_test_adjusted_pvalue(x, pnull, rnull, dnull=dnull, B=10, maxProcessor = 1)
```

grad_mat

*Find gradient of log(f) for a matrix of points***Description**

Find gradient of log(f) for a matrix of points

Usage

```
grad_mat(x, f)
```

Arguments

x	point of evaluation
f	function

Value

a matrix of gradient vectors

```
hybrid.mdgof.vignette  hybrid.mdgof.vignette
```

Description

stuff needed to run vignette MDgof::hybrid fast enough to pass CRAN

Usage

```
hybrid.mdgof.vignette
```

Format

'hybrid.mdgof.vignette':

A list

hybrid_power	<i>Power Estimation for the multivariate goodness-of-fit problem via twosample tests</i>
--------------	--

Description

This function estimates the power of goodness-of-fit/two-sample hybrid tests using Rcpp and parallel computing by generating a Monte Carlo data set and then running a twosample test.

Usage

```
hybrid_power(
  rnull,
  ralt,
  param_alt,
  phat = function(x) -99,
  nMC = 1,
  TS,
  TSextra,
  With.p.value = FALSE,
  alpha = 0.05,
  B = 1000,
  seed = NULL,
  maxProcessor,
  doMethods = "all"
)
```

Arguments

<code>rnull</code>	routine to generate data under the null hypothesis.
<code>ralt</code>	routine to generate data under the alternative hypothesis.
<code>param_alt</code>	values passed to <code>ralt</code> .
<code>phat</code>	<code>=function(x)</code> -99 parameter estimation, if needed.
<code>nMC</code>	<code>=1</code> sample size of Monte Carlo data set, if it is a number <code>nMC</code> ≤ 10 sample size used will be <code>nMC</code> *sample size of <code>x</code> .
<code>TS</code>	user supplied function to find test statistics, if any.
<code>TSextra</code>	(optional) list passed to <code>TS</code> , if needed.
<code>With.p.value</code>	<code>=FALSE</code> , does user supplied method find its own p-values?
<code>alpha</code>	<code>=0.05</code> type I error rate used in tests.
<code>B</code>	<code>=5000</code> number of simulation runs. If <code>B=0</code> the routine returns the test statistics.
<code>seed</code>	<code>=NULL</code> (optional) seed for simulations, to aid reproducibility
<code>maxProcessor</code>	number of processors to use in parallel processing.
<code>doMethods</code>	<code>"all"</code> , a vector of codes for the methods to include or all of them.

Details

For details on the usage of this routine consult the vignette with `vignette("MDgof-hybrid", "MDgof-hybrid")`

Value

A list with vectors of test statistics and p.values

Examples

```
# All examples are run with B=20 and maxProcessor=1 to pass CRAN checks.
# Power of tests see whether data comes from a bivariate standard normal distribution,
# without parameter estimation. True Distribution is bivariate normal with
# correlation r.
rnull=function() mvtnorm::rmvnorm(100, c(0, 0))
ralt=function(r) mvtnorm::rmvnorm(100, sigma=matrix(c(1,r,r,1),2,2))
hybrid_power(rnull, ralt, 0.3, B=20, maxProcessor = 1)
# Power of tests to see whether data comes from a standard normal distribution,
# with mean parameter estimated. True data comes from t distribution.
rnull=function(p) mvtnorm::rmvnorm(100, p)
ralt=function(df) mvtnorm::rmvt(100, df=df)
phat=function(x) apply(x, 2, mean)
hybrid_power(rnull, ralt, 5, phat, B=20, maxProcessor = 1)
```

hybrid_test

*Tests for the multivariate goodness-of-fit problem via twosample tests***Description**

This function runs a number of goodness-of-fit tests using Rcpp and parallel computing by generating a Monte Carlo data set and then running a twosample test.

Usage

```
hybrid_test(
  x,
  rnull,
  phat = function(x) -99,
  nMC = 1,
  TS,
  TSextra,
  B = 1000,
  seed = NULL,
  maxProcessor,
  doMethods = "all"
)
```

Arguments

x	a matrix with the data set
rnull	routine to generate data under the null hypothesis.
phat	=function(x) -99 parameter estimation, if needed.
nMC	=1 sample size of Monte Carlo data set, if it is a number nMC<=10 sample size used will be nMC*sample size of x.
TS	user supplied function to find test statistics, if any.
TSextra	(optional) list passed to TS, if needed.
B	=5000 number of simulation runs. If B=0 the routine returns the test statistics.
seed	=NULL (optional) seed for simulations, to aid reproducibility
maxProcessor	number of processors to use in parallel processing.
doMethods	="all", a vector of codes for the methods to include or all of them.

Details

For details on the usage of this routine consult the vignette with vignette("MDgof-hybrid", "MDgof-hybrid")

Value

A list with vectors of test statistics and p.values

Examples

```
# All examples are run with B=20 and maxProcessor=1 to pass CRAN checks.
# Tests to see whether data comes from a bivariate standard normal distribution,
# without parameter estimation.
rnull=function() mvtnorm::rmvnorm(100, c(0, 0))
x=rnull()
hybrid_test(x, rnull, B=20, maxProcessor = 1)
# Tests to see whether data comes from a standard normal distribution,
# with mean parameter estimated.
rnull=function(p) mvtnorm::rmvnorm(100, p)
phat=function(x) apply(x, 2, mean)
x=rnull(c(0,1))
hybrid_test(x, rnull, phat, B=20, maxProcessor = 1)
# Example of a discrete model, without parameter estimation
#  $X \sim \text{Bin}(5, 0.5)$ ,  $Y|X=x \sim \text{Bin}(4, 0.5+x/100)$ 
rnull=function() {
  x=rbinom(1000, 5, 0.5)
  y=rbinom(1000, 4, 0.5)
  MDgof::sq2rec(table(x, y))
}
x=rnull()
hybrid_test(x, rnull, B=50, maxProcessor = 1)
# Example of a discrete model, with parameter estimation
#  $X \sim \text{Bin}(5, p)$ ,  $Y|X=x \sim \text{Bin}(4, 0.5+x/100)$ 
rnull=function(p) {
  x=rbinom(1000, 5, p)
  y=rbinom(1000, 4, 0.5+x/100)
  MDgof::sq2rec(table(x, y))
}
phat=function(x) {
  tx=tapply(x[,3], x[,1], sum)
  p1=mean(rep(as.numeric(names(tx)), times=tx))/5
  p1
}
x=rnull(0.5)
hybrid_test(x, rnull, phat, B=20, maxProcessor = 1)
```

ksd

Find test statistic for Kernel Stein Discrepancy test

Description

Find test statistic for Kernel Stein Discrepancy test

Usage

```
ksd(X, scf, p)
```

Arguments

x	data set.
scf	function to find scores
p	(possible) parameters

Value

a double (test statistic)

newTS	<i>Example for a new test</i>
-------	-------------------------------

Description

This shows how a new test routine can be used with Mgof, based on chi square tests

Usage

```
newTS(x, pnull, p, TSextra)
```

Arguments

x	a data set.
pnull	function to calculate expected counts.
p	parameter for pnull, if needed
TSextra	a list with setup info

Value

a vector with either values of the test statistic, or p values

p2dC	<i>Find probabilities from cdf for discrete data</i>
------	--

Description

Find probabilities from cdf for discrete data

Usage

```
p2dC(x, cdf, p, Fx = as.numeric(c(-1)))
```

Arguments

x	matrix with data
cdf	function to find distribution function
p	(possible) arguments for cdf
Fx	(if available) already calculated values of cdf

Value

a matrix with probabilities added

```
power_studies_cont_D5_hybrid_results
      power_studies_cont_D5_hybrid_results
```

Description

the results of the included power studies for continuous data without estimation using two-sample methods in 5 dimensions

Usage

```
power_studies_cont_D5_hybrid_results
```

Format

'power_studies_cont_D5_hybrid_results':
A list of matrices with powers

```
power_studies_cont_D5_results
      power_studies_cont_D5_results
```

Description

the results of the included power studies for continuous data without estimation in 5 dimensions

Usage

```
power_studies_cont_D5_results
```

Format

'power_studies_cont_D5_results':
A list of matrices with powers

```
power_studies_cont_est_results  
    power_studies_cont_est_results
```

Description

the results of the included power studies for continuous data with estimation

Usage

```
power_studies_cont_est_results
```

Format

'power_studies_cont_est_results':

A list of matrices with powers

```
power_studies_cont_hybrid_results  
    power_studies_cont_hybrid_results
```

Description

the results of the included power studies for continuous data without estimation using two-sample methods

Usage

```
power_studies_cont_hybrid_results
```

Format

'power_studies_cont_hybrid_results':

A list of matrices with powers

```
power_studies_cont_nMC5_D5_hybrid_results  
    power_studies_cont_nMC5_D5_hybrid_results
```

Description

the results of the included power studies for continuous data without estimation using two-sample methods in 5 dimensions and five times sample size using two-sample methods and nMC=5

Usage

```
power_studies_cont_nMC5_D5_hybrid_results
```

Format

'power_studies_cont_nMC5_D5_hybrid_results':
A list of matrices with powers

```
power_studies_cont_nMC5_hybrid_results  
    power_studies_cont_nMC5_hybrid_results
```

Description

the results of the included power studies for continuous data without estimation using two-sample methods and nMC=5

Usage

```
power_studies_cont_nMC5_hybrid_results
```

Format

'power_studies_cont_nMC5_hybrid_results':
A list of matrices with powers

```
power_studies_cont_results  
    power_studies_cont_results
```

Description

the results of the included power studies for continuous data without estimation

Usage

```
power_studies_cont_results
```

Format

'power_studies_cont_results':
A list of matrices with powers

```
power_studies_disc_est_results  
    power_studies_disc_est_results
```

Description

the results of the included power studies for discrete data with estimation

Usage

```
power_studies_disc_est_results
```

Format

'power_studies_disc_est_results':
A list of matrices with powers

```
power_studies_disc_hybrid_results  
    power_studies_disc_hybrid_results
```

Description

the results of the included power studies for discrete data without estimation using two-sample methods

Usage

```
power_studies_disc_hybrid_results
```

Format

'power_studies_disc_hybrid_results':
A list of matrices with powers

```
power_studies_disc_nMC5_hybrid_results  
    power_studies_disc_nMC5_hybrid_results
```

Description

the results of the included power studies for discrete data without estimation using two-sample methods and nMC=5

Usage

```
power_studies_disc_nMC5_hybrid_results
```

Format

'power_studies_disc_nMC5_hybrid_results':
A list of matrices with powers

```
power_studies_disc_results
      power_studies_disc_results
```

Description

the results of the included power studies for discrete data without estimation

Usage

```
power_studies_disc_results
```

Format

'power_studies_disc_results':
A list of matrices with powers

```
print.MDgof_power      Print an MDgof power result with Monte Carlo uncertainty
```

Description

Print an MDgof power result with Monte Carlo uncertainty

Usage

```
## S3 method for class 'MDgof_power'
print(x, ...)
```

Arguments

x An object of class "MDgof_power".
... Further arguments passed to print.data.frame.

Value

x, invisibly.

print.MDgof_test	<i>Methods for MDgof goodness-of-fit test results</i>
------------------	---

Description

Printing, summarizing, and data-frame conversion methods for objects returned by `gof_test()`.

Usage

```
## S3 method for class 'MDgof_test'
print(x, ...)

## S3 method for class 'MDgof_test'
summary(object, ...)

## S3 method for class 'summary.MDgof_test'
print(x, ...)

## S3 method for class 'MDgof_test'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)
```

Arguments

<code>x</code>	An object of class "MDgof_test".
<code>...</code>	Further arguments passed to <code>print.data.frame</code> where applicable.
<code>object</code>	An object of class "MDgof_test".
<code>row.names</code>	Ignored.
<code>optional</code>	Ignored.

Value

`print.MDgof_test` returns `x` invisibly.

`summary.MDgof_test` returns an object of class "summary.MDgof_test".

`print.summary.MDgof_test` returns `x` invisibly.

`as.data.frame.MDgof_test` returns a data frame with columns `method`, `statistic`, and `p.value`.

RipleyK	<i>Ripley's K function test</i>
---------	---------------------------------

Description

this function calculates the test statistic of Ripley's K function test

Usage

```
RipleyK(x)
```

Arguments

x matrix with data

Value

a number (test statistic)

run.studies	<i>Benchmarking for Multivariate Goodness-of-fit Tests</i>
-------------	--

Description

This function runs the case studies included in the package.

Usage

```
run.studies(
  study,
  Continuous = TRUE,
  WithEstimation = FALSE,
  Hybrid = FALSE,
  nMC5 = FALSE,
  Dim = 2,
  TS,
  TSextra,
  With.p.value = FALSE,
  nsample = 250,
  nbins = c(5, 5),
  alpha = 0.05,
  param_alt,
  SuppressMessages = FALSE,
  ShowResult = TRUE,
  B = 1000,
  seed = NULL,
  maxProcessor
)
```

Arguments

study	either the name of the study, or its number in the list. If missing all the studies are run.
Continuous	=TRUE, run cases for continuous data.
WithEstimation	=FALSE, run case studies with or without parameter estimation?
Hybrid	=FALSE run hybrid tests?
nMC5	=FALSE, sample size of hybrid test.
Dim	=2 two or five-dimensional continuous data sets?
TS	routine to calculate new test statistics.
TSextra	list passed to TS (optional).
With.p.value	=FALSE, does user supplied routine return p values?
nsample	= 250, desired sample size. 250 is used in included case studies.
nbins	=c(5,5) number of bins for discretized data.
alpha	=0.05, type I error probability of tests. 0.05 is used in included case studies.
param_alt	vector or matrix of values of parameters under the alternative hypothesis. If missing included values are used.
SuppressMessages	=FALSE, should informative messages be shown?
ShowResult	=TRUE should result be shown in console?
B	= 1000, number of simulation runs.
seed	=NULL (optional) seed for simulations, to aid reproducibility
maxProcessor	number of cores to use. If missing the number of physical cores-1 is used. If set to 1 no parallel processing is done.

Details

For details consult vignette(package="MDgof")

Value

A (list of) matrices of p.values.

Examples

```
#Examples are run with a super small B=25 simulation runs to satisfy CRAN submission rules.
#Run a new test for studies 1-3 for continuous data and without estimation.
#The new test is an (included) chi square test that finds it's own p value.
TSextra=list(Continuous=TRUE, WithEstimation=FALSE, Withpvalue=TRUE)
MDgof::run.studies(study=1:3, Continuous=TRUE, WithEstimation=FALSE,
  TS=MDgof::newTS, TSextra=TSextra,
  With.p.value = TRUE, B=25, maxProcessor = 1)
#Run included tests for studies 1-3 for discrete data and without estimation,
#but with type I error alpha=0.1
p=MDgof::power_studies_disc_results[[3]][1:3,,drop=FALSE]
MDgof::run.studies(study=1:3, Continuous=FALSE, WithEstimation=FALSE,
  param_alt=p,alpha=0.1, B=25, maxProcessor = 1)
```

sq2rec	<i>Rearrange 2D discrete data</i>
--------	-----------------------------------

Description

This function changes a discrete data set given as a $n \times m$ counting matrix to a $nm \times 3$ matrix

Usage

```
sq2rec(x)
```

Arguments

`x` a matrix of discrete data.

Value

a rearranged matrix

TS_cont	<i>Find test statistics for continuous data</i>
---------	---

Description

Find test statistics for continuous data

Usage

```
TS_cont(x, pnull, param, TSextra)
```

Arguments

<code>x</code>	A numeric matrix.
<code>pnull</code>	cdf.
<code>param</code>	parameters for pnull in case of parameter estimation.
<code>TSextra</code>	list with additional info

Value

A numeric vector with test statistics

TS_disc

*Find test statistics for discrete data***Description**

Find test statistics for discrete data

Usage

```
TS_disc(x, pnull, param, TSextra)
```

Arguments

x	A numeric matrix.
pnull	cdf.
param	parameters for pnull in case of parameter estimation.
TSextra	list with additional info

Value

A numeric vector with test statistics

Index

* datasets

examples.mdgof.vignette, [12](#)
hybrid.mdgof.vignette, [22](#)
power_studies_cont_D5_hybrid_results,
[27](#)
power_studies_cont_D5_results, [27](#)
power_studies_cont_est_results, [28](#)
power_studies_cont_hybrid_results,
[28](#)
power_studies_cont_nMC5_D5_hybrid_results,
[29](#)
power_studies_cont_nMC5_hybrid_results,
[29](#)
power_studies_cont_results, [30](#)
power_studies_disc_est_results, [30](#)
power_studies_disc_hybrid_results,
[31](#)
power_studies_disc_nMC5_hybrid_results,
[31](#)
power_studies_disc_results, [32](#)

as.data.frame.MDgof_power, [3](#)
as.data.frame.MDgof_test
(print.MDgof_test), [33](#)

bakshaev_rudzkis, [3](#)

case.studies, [4](#)
case.studies.cont, [5](#)
case.studies.cont.D5, [5](#)
case.studies.disc, [6](#)
case.studies.est, [6](#)
chi_cont_test, [7](#)
chi_disc_test, [8](#)
chi_power, [8](#)
compute_M_for_dtaset, [10](#)

discretize, [10](#)
draw_case, [11](#)

estimateEV, [12](#)

examples.mdgof.vignette, [12](#)
gauss_kernel_matrix, [13](#)
gen.cop, [13](#)
gen_eval, [14](#)
gof_power, [14](#)
gof_test, [17](#)
gof_test_adjusted_pvalue, [19](#)
grad_mat, [21](#)
hybrid.mdgof.vignette, [22](#)
hybrid_power, [22](#)
hybrid_test, [24](#)

ksd, [25](#)

newTS, [26](#)

p2dC, [26](#)
power_studies_cont_D5_hybrid_results,
[27](#)
power_studies_cont_D5_results, [27](#)
power_studies_cont_est_results, [28](#)
power_studies_cont_hybrid_results, [28](#)
power_studies_cont_nMC5_D5_hybrid_results,
[29](#)
power_studies_cont_nMC5_hybrid_results,
[29](#)
power_studies_cont_results, [30](#)
power_studies_disc_est_results, [30](#)
power_studies_disc_hybrid_results, [31](#)
power_studies_disc_nMC5_hybrid_results,
[31](#)
power_studies_disc_results, [32](#)
print.MDgof_power, [32](#)
print.MDgof_test, [33](#)
print.summary.MDgof_test
(print.MDgof_test), [33](#)

RipleyK, [34](#)
run.studies, [34](#)

sq2rec, [36](#)

summary.MDgof_test (print.MDgof_test),
[33](#)

TS_cont, [36](#)

TS_disc, [37](#)