

Package ‘StreamCatTools’

October 2, 2026

Type Package

Title Tools for Working with 'StreamCat' and 'LakeCat' Data

Version 0.12.0

Date 2026-09-23

Author Marc Weber [aut, cre],
Ryan Hill [aut],
Selia Markley [aut],
Travis Hudson [aut],
Allen Brookes [aut],
David Rebhuhn [ctb],
Michael Dumelle [ctb],
Justin Bousquin [ctb],
Zachary Smith [ctb]

Maintainer Marc Weber <weber.marc@epa.gov>

Description Tools for using the 'StreamCat' and 'LakeCat' API and
interacting with the 'StreamCat' and 'LakeCat' database.
Convenience functions in the package wrap the API for 'StreamCat'
on <<https://api.epa.gov/StreamCat/streams/metrics>>.

Depends R (>= 4.1.0)

Imports sf, hydrogeofetch, jsonlite, httr2, curl (>= 6.0.0),
ggpattern, patchwork, cowplot, tigris, ggplot2, dplyr, tidyr,
stringr, tibble,

Suggests mapview, testthat, knitr, rmarkdown, devtools, xml2,
magrittr, readr, purrr, lifecycle, tidyselect, DBI, duckdb,
tictoc, stats, wk

Encoding UTF-8

URL <https://usepa.github.io/StreamCatTools/>,
<https://github.com/USEPA/StreamCatTools>

BugReports <https://github.com/USEPA/StreamCatTools/issues>

VignetteBuilder knitr

License MIT + file LICENSE

NeedsCompilation no
Config/roxygen2/version 8.1.0
Repository CRAN
Date/Publication 2026-10-02 19:50:09 UTC

Contents

lc_fullname	2
lc_get_comid	3
lc_get_data	4
lc_get_metric_names	6
lc_get_nlcd	7
lc_get_nni	8
lc_get_params	10
lc_get_watershed	11
lc_plotnni	12
sc_fullname	13
sc_get_comid	14
sc_get_data	15
sc_get_metric_names	17
sc_get_nni	18
sc_get_params	19
sc_plotnni	20
Index	22

lc_fullname	<i>Lookup Full Metric Name</i>
-------------	--------------------------------

Description

Function to retrieve a full metric name based on the short name using the LakeCat API.

Usage

lc_fullname(metric = NULL)

Arguments

metric Short metric name Syntax: metric=value1 Values: metric

Value

A lookup of the full name for a given LakeCat metric

Author(s)

Marc Weber

Examples

```
## Not run:
fullname <- lc_fullname(metric='clay')
## End(Not run)
```

lc_get_comid

*Get Lake COMIDs***Description**

Function to return NHDPlusV2 Waterbody COMIDS using either a dataframe with coordinates and a specified CRS or an sf object. The function generates a vector of NHDPlus Waterbody COMID values a user can then pass to lc_get_data function

Usage

```
lc_get_comid(
  dd = NULL,
  xcoord = NULL,
  ycoord = NULL,
  crsys = NULL,
  buffer = NULL
)
```

Arguments

dd	Name of data frame object. Can be a simple data frame with coordinate columns in a known CRS or an sf points data frame
xcoord	The x coordinate column if using a raw data frame
ycoord	The y coordinate column if using a raw data frame
crsys	The epsg code if using a raw data frame
buffer	The amount of buffer to use to extend search for a waterbody (simply passed to hydrogeofetch::get_waterbodies)

Value

A new sf data frame with a populated 'COMID' column

Author(s)

Marc Weber

Examples

```
## Not run:

dd <- data.frame(x = c(-89.198,-114.125,-122.044),
y = c(45.502,47.877,43.730))

comids <- lc_get_comid(dd, xcoord='x',
                      ycoord='y', crsys=4269)

dd <- data.frame(x = c(-89.198,-114.125,-122.044),
y = c(45.502,47.877,43.730)) |>
  sf::st_as_sf(coords = c('x', 'y'), crs = 4326)

comids <- lc_get_comid(dd)

## End(Not run)
```

 lc_get_data

Get LakeCat data

Description

Function to return LakeCat metrics using the StreamCat API. The function allows a user to get specific metric data aggregated by area of interest, returned by comid(s), hydroregion(s), state(s), or county(ies).

Usage

```
lc_get_data(
  comid = NULL,
  metric = NULL,
  aoi = NULL,
  showAreaSqKm = NULL,
  showPctFull = NULL,
  state = NULL,
  county = NULL,
  region = NULL,
  conus = NULL,
  countOnly = NULL
)
```

Arguments

comid	Return metric information for specific COMIDs. Can be a comma-delimited list, a character vector, or any object that can be coerced to a comma-delimited list with paste . One of comid, county, state, or region is required unless conus='true'. Syntax: comid=<comid1>,<comid2>
-------	--

metric	Name(s) of metrics to query. Must be character string with comma-delimited list of metrics. Not case-sensitive . Syntax: name=<name1>,<name2>
aoi	Specify the area of interest described by a metric. By default, all available areas of interest for a given metric are returned. <i>Case-sensitive</i> . Syntax: areaOfInterest=<value1>,<value2> Values: catchment watershed
showAreaSqKm	Return the area in square kilometers of a given area of interest. The default value is false. Values: true false
showPctFull	Return the pctfull for each dataset. The default value is false. Values: true false
state	Return metric information for COMIDs within a specific state. Use a state's abbreviation to query for a given state. One of comid, county, state, or region is required unless conus='true'. If specified <i>and valid</i> , comid and county are ignored. <i>Case-sensitive</i> . Syntax: state=<state1>,<state2>
county	Return metric information for COMIDs within a specific county. Users must use the FIPS code, not county name, as a way to disambiguate counties. One of comid, county, state, or region is required unless conus='true'. If specified <i>and valid</i> , comid is ignored. Syntax: county=<county1>,<county1>
region	Return metric information for COMIDs within a specified hydroregion. Hydroregions are specified using full name i.e. 'Region01', 'Region03N', 'Region10L'. One of comid, county, state, or region is required unless conus='true'. If specified <i>and valid</i> , comid, county, and state are ignored. <i>Case-sensitive</i> . Syntax: region=<regionid1>,<regionid2>
conus	Return all COMIDs in the conterminous United States. Character string (Not case-sensitive) or logical. The default value is false. If true, comid, county, state, and region are ignored. Values: true false
countOnly	Return a CSV containing only the row count (ROWCOUNT) and the column count (COLUMNCOUNT) that the server expects to return in a request. The default value is false. Values: true false

Value

A tibble of desired StreamCat metrics. If data are missing for all rows of a given metric, then the column for that metric will not exist. If data are missing for only some rows, then they will be specified with NA.

Author(s)

Marc Weber

Examples

```
## Not run:
df <- lc_get_data(comid='23794487', aoi='cat', metric='fert')

df <- lc_get_data(metric='pcturbmd2006', aoi='ws',
comid='24083377')

df <- lc_get_data(metric='pctgrs2006', aoi='ws', region='Region01')
```

```

df <- lc_get_data(metric='pctwdwet2006', aoi='ws', county='41003')

df <- lc_get_data(metric='pcturbmd2006', aoi='ws',
comid='24083377', showAreaSqKm=FALSE, showPctFull=TRUE)

df <- lc_get_data(metric='pcturbmd2006,damdens',
aoi='cat,ws', comid='23783629,23794487,23812618')

df <- lc_get_data(metric='pcturbmd2006,damdens',
aoi='cat,ws', comid=c('23783629','23794487','23812618'))

df <- lc_get_data(metric='pcturbmd2006,damdens',
aoi='cat,ws', comid='23783629,23794487,23812618',
countOnly=TRUE)

## End(Not run)

```

lc_get_metric_names	<i>Get LakeCat Metric Names</i>
---------------------	---------------------------------

Description

Function to filter LakeCat metrics metrics by category, area of interest, dataset or year. Use 'lc_get_params(categories)' or 'lc_get_params(datasets)' to see all the valid category or dataset options

Usage

```
lc_get_metric_names(category = NULL, aoi = NULL, year = NULL, dataset = NULL)
```

Arguments

category	Filter LakeCat metrics based on the metric category
aoi	Filter LakeCat metrics based on the area of interest
year	Filter LakeCat metrics based on a particular year or years
dataset	Filter LakeCat metrics based on the dataset name

Value

A dataframe of metrics and description that match filter criteria

Author(s)

Marc Weber

Examples

```
## Not run:
metrics <- lc_get_metric_names(category='Natural')
metrics <- lc_get_metric_names(category = c('Anthropogenic','Natural'),
aoi=c('Cat','Ws'))
## End(Not run)
```

lc_get_nlcd

Get NLCD Data

Description

‘r lifecycle::badge("deprecated")’ ‘lc_nlcd()’ was renamed to ‘lc_get_nlcd()’ to create a more consistent API. Function to specifically retrieve all NLCD metrics for a given year using the StreamCat API.

Usage

```
lc_get_nlcd(
  year = "2019",
  comid = NULL,
  aoi = NULL,
  showAreaSqKm = NULL,
  showPctFull = NULL,
  state = NULL,
  county = NULL,
  region = NULL,
  conus = NULL,
  countOnly = NULL
)
```

Arguments

year	Years(s) of NLCD metrics to query. Only valid NLCD years are accepted (i.e. 2001, 2004, 2006, 2008, 2011, 2013, 2016, 2019) Syntax: year=<year1>,<year2>
comid	Return metric information for specific COMIDs Syntax: comid=<comid1>,<comid2>
aoi	Specify the area of interest described by a metric. By default, all available areas of interest for a given metric are returned. Syntax: areaOfInterest=<value1>,<value2> Values: catchment watershed riparian_catchment riparian_watershed other
showAreaSqKm	Return the area in square kilometers of a given area of interest. The default value is false. Values: true false
showPctFull	Return the pctfull for each dataset. The default value is false. Values: true false
state	Return metric information for COMIDs within a specific state. Use a state’s abbreviation to query for a given state. Syntax: state=<state1>,<state2>

county	Return metric information for COMIDs within a specific county. Users must use the FIPS code, not county name, as a way to disambiguate counties. Syntax: county=<county1>,<county1>
region	Return metric information for COMIDs within a specified hydroregion. Syntax: region=<regionid1>,<regionid2>
conus	Return all COMIDs in the conterminous United States. The default value is false. Values: true/false
countOnly	Return a CSV containing only the row count (ROWCOUNT) and the column count (COLUMNCOUNT) that the server expects to return in a request. The default value is false. Values: true/false

Value

A tibble of desired StreamCat metrics

Author(s)

Marc Weber

Examples

```
## Not run:

df <- lc_get_nlcd(comid='23783629', year='2019', aoi='ws') # Will show a deprecation warning

df <- lc_get_nlcd(comid='23783629', year='2019', aoi='ws')

df <- lc_get_nlcd(year='2016', aoi='cat',
  comid='23783629,23794487,23812618', showAreaSqKm=FALSE, showPctFull=TRUE)

df <- lc_get_nlcd(year='2016', aoi='cat',
  comid='23783629,23794487,23812618', countOnly=TRUE)

df <- lc_get_nlcd(year='2016, 2019', aoi='cat,ws',
  comid='23783629,23794487,23812618')

## End(Not run)
```

lc_get_nni

Get NNI

Description

Function to get all NNI data available for a given year.

Usage

```
lc_get_nni(
  year,
  aoi = NULL,
  comid = NULL,
  showAreaSqKm = TRUE,
  showPctFull = NULL,
  countOnly = NULL
)
```

Arguments

year	Years(s) of NNI metrics to query. Only valid NNI years are accepted (1987:2017) Syntax: year=<year1>,<year2>
aoi	Specify the area of interest described by a metric. By default, all available areas of interest for a given metric are returned. Syntax: areaOfInterest=<value1>,<value2> Values: catchment watershed
comid	Return metric information for specific COMIDs Syntax: comid=<comid1>,<comid2>
showAreaSqKm	Return the area in square kilometers of a given area of interest. The default value is true. Values: true false
showPctFull	Return the pctfull for each dataset. The default value is false. Values: true false
countOnly	Return a CSV containing only the row count (ROWCOUNT) and the column count (COLUMNCOUNT) that the server expects to return in a request. The default value is false. Values: true false

Value

A tibble of desired StreamCat metrics

Author(s)

Selia Markley

Examples

```
df <- lc_get_nni(year='1987, 1990, 2005, 2017', aoi='cat,ws',
  comid='23783629,23794487,23812618')

df <- lc_get_nni(year='2015', aoi='cat',
  comid='23783629', countOnly=TRUE)

df <- lc_get_nni(comid='23783629', year='2011, 2012', aoi='ws')
```

lc_get_params	<i>Get LakeCat Parameters</i>
---------------	-------------------------------

Description

Function to return available LakeCat parameters using the StreamCat API.

Usage

```
lc_get_params(param = NULL)
```

Arguments

param	List of available parameters in the API for the following options: name, areaofInterest, region, state, county. State and county return a data frame that includes FIPS codes, names and state abbreviations Syntax: param=<value1>,<value2> Values: name area
-------	--

Value

A list of all the current LakeCat values for a given parameter

Author(s)

Marc Weber

Examples

```
## Not run:
params <- lc_get_params(param='variable_info')
params <- lc_get_params(param='metric_names')
params <- sc_get_params(param='categories')
params <- lc_get_params(param='aoi')
params <- lc_get_params(param='state')
params <- lc_get_params(param='county')
params <- sc_get_params(param='datasets')

## End(Not run)
```

lc_get_watershed

*Get LakeCat Lake Watershed***Description**

Lookup function for a single COMID from S3 GeoParquet (optionally restricted to one HUC2). Queries one COMID from an S3-hosted, HUC2-partitioned GeoParquet dataset and returns an sf object. If 'huc2' is provided, only that partition is scanned (fastest). If not, the function tries a glob over all HUC2 partitions and falls back to a shallower pattern if needed. The function: - loads DuckDB httpfs (S3) extension, - pushes an equality filter on 'COMID' for row-group/file pruning, - converts WKB geometry to sf with the CRS you provide (default EPSG:4326).

Usage

```
lc_get_watershed(
  comid,
  huc2 = NA_character_,
  huc2_filter = NULL,
  bucket = "dmap-data-commons-ow",
  prefix = "data/streamcat/LakeCatWatersheds/",
  region = "us-east-1",
  install_missing = FALSE,
  keep_open = FALSE,
  verbose = TRUE,
  progress = TRUE,
  threads = 4,
  enable_object_cache = TRUE,
  skip_describe = FALSE,
  skip_counts = TRUE,
  sf_crs = 4326,
  retries = 5,
  retry_base_delay = 0.5,
  retry_max_delay = 8,
  url_style = c("path", "virtual_hosted"),
  s3_endpoint = NULL
)
```

Arguments

comid	Scalar COMID to query (numeric or character, required).
huc2	Optional two-digit HUC2 string (e.g., "01") to restrict search to one partition.
huc2_filter	Optional character vector of HUC2s to read (e.g., c("01", "05")) for multi-partition pruning.
bucket	Character(1). S3 bucket (default "dmap-data-commons-ow").
prefix	Character(1). S3 prefix under the bucket (default "data/streamcat/LakeCatWatersheds/").

region	Character(1). S3 region (default "us-east-1").
install_missing	Logical. Install missing packages (duckdb, DBI, sf, wk) if needed (default FALSE).
keep_open	Logical. Keep the DuckDB connection open (default FALSE). Note: the connection is not returned.
verbose	Logical. Print progress messages (default TRUE).
progress	Logical. Show a simple progress bar (default TRUE).
threads	Integer or NULL. If set, 'PRAGMA threads' for DuckDB (parallelism).
enable_object_cache	Logical. Enable DuckDB object cache to speed repeated queries (default TRUE).
skip_describe	Logical. Skip DESCRIBE step (default FALSE).
skip_counts	Logical. Skip HUC2 counts step (default TRUE; no longer returned).
sf_crs	Integer or character. CRS for the output sf object (default 4326).
retries	Integer. Number of retries for transient S3/HTTP errors (default 5).
retry_base_delay	Numeric. Initial exponential backoff delay in seconds (default 0.5).
retry_max_delay	Numeric. Maximum backoff delay per attempt in seconds (default 8).
url_style	Character. S3 URL style used by DuckDB httpfs, one of "path" or "virtual_hosted". Passed to 'match.arg()', default "path".
s3_endpoint	Optional character(1). Custom S3 endpoint hostname (e.g., "s3.amazonaws.com"). NULL uses the default for the selected region.

Value

An sf object with zero or one+ rows (if multiple features share the same COMID).

lc_plotnni	<i>Plot National Nutrient Inventory data for lakes</i>
------------	--

Description

Function to plot time series of nitrogen and phosphorus budgets for a given lake COMID. This function allows a user to return a time series of major inputs, outputs, and derived metrics of nitrogen and phosphorus. Plot is returned as an object

Usage

```
lc_plotnni(comid, include.nue = FALSE)
```

Arguments

comid	Identifier of lake COMID user wants to plot NNI data for. Must be a character string with the COMID digit. Syntax: com=<COMID>
include.nue	Include time series of nitrogen use efficiency in the returned plot. The default value is false. Values: truelfalse

Value

Return plot as an object.

Author(s)

Selia Markley

Examples

```
## Not run:
p <- lc_plotnni(comid='23794487')
p <- lc_plotnni(comid='23794487', include.nue=TRUE)

## End(Not run)
```

sc_fullname	<i>Lookup Full Metric Name</i>
-------------	--------------------------------

Description

Function to retrieve a full metric name based on the short name using the StreamCat API.

Usage

```
sc_fullname(metric = NULL)
```

Arguments

metric	Short metric name Syntax: metric=value1 Values: metric
--------	--

Value

A lookup of the full name for a given StreamCat metric

Author(s)

Marc Weber

Examples

```
fullname <- sc_fullname(metric='clay')
```

sc_get_comid

*Get COMIDs via ArcGIS batch query***Description**

Retrieve NHDPlus catchment FEATUREID (COMID) for a set of point locations by batching points to an ArcGIS Feature Service /query endpoint and mapping the returned catchment geometries back to the input points via a local spatial intersection. This avoids per-point HTTP requests and is faster for moderate-to-large point sets.

Usage

```
sc_get_comid(
  points_sf,
  service_layer_url = paste0("https://watersgeo.epa.gov/arcgis/rest/services/",
    "NHDPlus_NP21/Catchments_NP21_Simplified/MapServer/0"),
  layer_id = NULL,
  chunk_size = 1000,
  feature_id_field = "FEATUREID",
  verbose = TRUE,
  crs = NULL,
  coords = NULL
)
```

Arguments

points_sf	An 'sf' POINT object containing the input locations. If you supply a plain 'data.frame', convert it to an 'sf' object first.
service_layer_url	URL to the ArcGIS service layer. Defaults to the EPA NHDPlus catchments endpoint.
layer_id	Deprecated. This argument is kept only for backward compatibility. If supplied, it is appended to 'service_layer_url' after trimming any trailing slash.
chunk_size	Number of points to send per batch request. Default is 1000.
feature_id_field	Name of the feature attribute to return as the COMID. Default is "FEATUREID".
verbose	Logical; print progress messages for each chunk. Default is 'TRUE'.
crs	Optional CRS for the input points when a 'data.frame' is supplied or when an 'sf' object has no attached CRS. Use an EPSG code such as 4326.
coords	Optional character vector of length 2 giving x/y coordinate column names when 'points_sf' is a data frame. Example: 'c("lon", "lat")'.

Value

An integer vector of FEATUREID (COMID) values in the same order as the input points. Missing values are returned as 'NA'.

Examples

```
## Not run:
pts <- sf::st_as_sf(
  data.frame(
    id = 1:3,
    x = c(-90, -90.1, -90.2),
    y = c(40, 40.1, 40.2)
  ),
  coords = c("x", "y"),
  crs = 4326
)

comids <- sc_get_comid(points_sf = pts, chunk_size = 500)

## End(Not run)
```

sc_get_data

Get StreamCat data

Description

Function to return StreamCat catchment and watershed metrics using the StreamCat API. The function allows a user to get specific metric data aggregated by area of interest, returned by comid(s), hydroregion(s), state(s), or county(ies).

Usage

```
sc_get_data(
  comid = NULL,
  metric = NULL,
  aoi = NULL,
  showAreaSqKm = NULL,
  showPctFull = NULL,
  state = NULL,
  county = NULL,
  region = NULL,
  conus = NULL,
  countOnly = NULL
)
```

Arguments

comid	Return metric information for specific COMIDs. Can be a comma-delimited list, a character vector, or any object that can be coerced to a comma-delimited list with paste . One of comid, county, state, or region is required unless conus='true'. Syntax: comid=<comid1>,<comid2>
-------	--

metric	Name(s) of metrics to query. Must be character string with comma-delimited list of metrics, or, if metric='all' then all metrics will be queried. Not case-sensitive . Syntax: name=<name1>,<name2>
aoi	Name(s) of areas of interest to query. If a metric does not have data for a given AOI, no data is returned for that AOI. Certain metrics that have no AOI specified for StreamCat need the AOI to be specified as 'other'. These metrics include: BankfullDepth, BankfullWidth, ThalwagDepth (sic), CHEM_V2_1, CONN, HABT, HYD, ICI, IWI, TEMP, WettedWidth, prg_bmml, and all the mast, msst, mwst metrics. <i>Case-sensitive</i> . Syntax: areaOfInterest=<value1>,<value2> Values: cat wslcatrp100 wsrp100 other
showAreaSqKm	Return the area in square kilometers of a given area of interest. The default value is false. Values: true false
showPctFull	Return the pctfull for each dataset. The default value is false. Values: true false
state	Return metric information for COMIDs within a specific state. Use a state's abbreviation to query for a given state. One of comid, county, state, or region is required unless conus='true'. If specified <i>and valid</i> , comid and county are ignored. <i>Case-sensitive</i> . Syntax: state=<state1>,<state2>
county	Return metric information for COMIDs within a specific county. Users must use the FIPS code, not county name, as a way to disambiguate counties. One of comid, county, state, or region is required unless conus='true'. If specified <i>and valid</i> , comid is ignored. Syntax: county=<county1>,<county1>
region	Return metric information for COMIDs within a specified hydroregion. Hydroregions are specified using full name i.e. 'Region01', 'Region03N', 'Region10L'. One of comid, county, state, or region is required unless conus='true'. If specified <i>and valid</i> , comid, county, and state are ignored. <i>Case-sensitive</i> . Syntax: region=<regionid1>,<regionid2>
conus	Return all COMIDs in the conterminous United States. Character string (Not case-sensitive) or logical. The default value is false. If true, comid, county, state, and region are ignored. Values: true false
countOnly	Return a CSV containing only the row count (ROWCOUNT) and the column count (COLUMNCOUNT) that the server expects to return in a request. The default value is false. Values: true false

Value

A data frame of StreamCat metrics. If data are missing for all rows of a given metric, then the column for that metric will not exist. If data are missing for only some rows, then they will be specified with NA.

Author(s)

Marc Weber

Examples

```
## Not run:
df <- sc_get_data(comid='179', aoi='cat', metric='fert')
```

```

df <- sc_get_data(metric='pctgrs2006', aoi='ws', region='Region01')

df <- sc_get_data(metric='pctwdwet2006', aoi='ws', county='41003')

df <- sc_get_data(metric='pcturbmd2006', aoi='ws,rp100',
comid='1337420')

df <- sc_get_data(metric='pcturbmd2006,damdens',
aoi='cat,ws', comid='179,1337,1337420')

df <- sc_get_data(metric='pcturbmd2006,damdens',
aoi='cat,ws', comid='179,1337,1337420',
showAreaSqKm='true', showPctFull='true')

df <- sc_get_data(metric='pcturbmd2006,damdens',
aoi='cat,ws', comid='179,1337,1337420', countOnly='true')

df <- sc_get_data(metric='thalwagdepth', comid='179,1337,1337420', aoi='other')

df <- sc_get_data(metric='thalwagdepth', comid=c('179','1337','1337420'), aoi='other')

df <- sc_get_data(comid='179', aoi='ws', metric='all')

## End(Not run)

```

sc_get_metric_names	<i>Get StreamCat Metric Names</i>
---------------------	-----------------------------------

Description

Function to filter StreamCat metrics metrics by category, area of interest, dataset or year. Use 'sc_get_params(categories)' or 'sc_get_params(datasets)' to see all the valid category or dataset options

Usage

```
sc_get_metric_names(category = NULL, aoi = NULL, year = NULL, dataset = NULL)
```

Arguments

category	Filter StreamCat metrics based on the metric category
aoi	Filter StreamCat metrics based on the area of interest
year	Filter StreamCat metrics based on a particular year or years
dataset	Filter StreamCat metrics based on the dataset name

Value

A dataframe of metrics and description that match filter criteria

Author(s)

Marc Weber

Examples

```
## Not run:
metrics <- sc_get_metric_names(category='Wildfire')
metrics <- sc_get_metric_names(category = c('Deposition','Climate'),
aoi=c('Cat','Ws'))
metrics <- sc_get_metric_names(aoi='Other',
dataset=c('Canal Density','Predicted Channel Widths Depths'))

## End(Not run)
```

sc_get_nni

Get NNI

Description

Function to get all NNI data available for a given year.

Usage

```
sc_get_nni(
  year,
  aoi = NULL,
  comid = NULL,
  showAreaSqKm = TRUE,
  state = NULL,
  county = NULL,
  region = NULL,
  conus = NULL,
  showPctFull = NULL,
  countOnly = NULL
)
```

Arguments

year	Years(s) of NNI metrics to query. Only valid NNI years are accepted (1987:2017) Syntax: year=<year1>,<year2>
aoi	Specify the area of interest described by a metric. By default, all available areas of interest for a given metric are returned. Syntax: areaOfInterest=<value1>,<value2> Values: catchment watershed
comid	Return metric information for specific COMIDs Syntax: comid=<comid1>,<comid2>
showAreaSqKm	Return the area in square kilometers of a given area of interest. The default value is true. Values: true false

state	Return metric information for COMIDs within a specific state. Use a state's abbreviation to query for a given state. Syntax: state=<state1>,<state2>
county	Return metric information for COMIDs within a specific county. Users must use the FIPS code, not county name, as a way to disambiguate counties. Syntax: county=<county1>,<county1>
region	Return metric information for COMIDs within a specified hydroregion. Syntax: region=<regionid1>,<regionid2>
conus	Return all COMIDs in the conterminous United States. The default value is false. Values: true/false
showPctFull	Return the pctfull for each dataset. The default value is false. Values: true/false
countOnly	Return a CSV containing only the row count (ROWCOUNT) and the column count (COLUMNCOUNT) that the server expects to return in a request. The default value is false. Values: true/false

Value

A tibble of desired StreamCat metrics

Author(s)

Selia Markley

Examples

```
## Not run:

df <- sc_get_nni(year='1987, 1990, 2005, 2017', aoi='cat,ws',
comid='179,1337,1337420')

df <- sc_get_nni(year='2015', aoi='cat',
comid='179', countOnly=TRUE)

df <- sc_get_nni(comid='179', year='2011, 2012', aoi='ws')

df <- sc_get_nni(year='2015, 2016, 2017', county='41003', aoi='ws')

## End(Not run)
```

sc_get_params

Get StreamCat Parameters

Description

Function to return available StreamCat parameters using the StreamCat API.

Usage

```
sc_get_params(param = NULL)
```

Arguments

`param` List of available parameters in the API for the following options: name, areaofInterest, region, state, county. State and county return a data frame that includes FIPS codes, names and state abbreviations Syntax: `param=<value1>,<value2>`
Values: name|area

Value

A list of all the current StreamCat values for a given parameter

Author(s)

Marc Weber

Examples

```
## Not run:
params <- sc_get_params(param='variable_info')
params <- sc_get_params(param='metric_names')
params <- sc_get_params(param='categories')
params <- sc_get_params(param='aoi')
params <- sc_get_params(param='state')
params <- sc_get_params(param='county')
params <- sc_get_params(param='datasets')
## End(Not run)
```

sc_plotnni

Plot National Nutrient Inventory data for streams

Description

Function to plot time series of nitrogen and phosphorus budgets for a given stream COMID. This function allows a user to return a time series of major inputs, outputs, and derived metrics of nitrogen and phosphorus. Plot is returned as an object

Usage

```
sc_plotnni(comid, include.nue = FALSE, include.inset = TRUE)
```

Arguments

`comid` Identifier of stream COMID user wants to plot NNI data for. Must be a character string with the COMID digit. Syntax: `com=<COMID>`

`include.nue` Include time series of nitrogen use efficiency in the returned plot. The default value is false. Values: true|false

`include.inset` Include inset map that shows the location of the COMID and its basin. The default value is true. Values: true|false

Value

Return plot as an object.

Author(s)

Selia Markley

Examples

```
## Not run:  
p <- sc_plotnni(comid='1337420')  
p <- sc_plotnni(comid='1337420', include.nue=TRUE)  
p <- sc_plotnni(comid='1337420', include.inset=FALSE)  
  
## End(Not run)
```

Index

lc_fullname, [2](#)
lc_get_comid, [3](#)
lc_get_data, [4](#)
lc_get_metric_names, [6](#)
lc_get_nlcd, [7](#)
lc_get_nni, [8](#)
lc_get_params, [10](#)
lc_get_watershed, [11](#)
lc_plotnni, [12](#)

paste, [4](#), [15](#)

sc_fullname, [13](#)
sc_get_comid, [14](#)
sc_get_data, [15](#)
sc_get_metric_names, [17](#)
sc_get_nni, [18](#)
sc_get_params, [19](#)
sc_plotnni, [20](#)