

Package ‘causalfrag’

October 1, 2026

Type Package

Title Cross-Framework Sensitivity Analysis with an OLS Crosswalk

Version 0.2.0

Date 2026-10-01

Description Runs, classifies, interprets and reports sensitivity analyses for unmeasured confounding across the partial R-squared robustness value approach (Cinelli and Hazlett, 2020, <[doi:10.1111/rssb.12348](https://doi.org/10.1111/rssb.12348)>), E-values (VanderWeele and Ding, 2017, <[doi:10.7326/M16-2607](https://doi.org/10.7326/M16-2607)>), and the impact threshold for a confounding variable and robustness of inference to replacement (Frank, 2000, <[doi:10.1177/0049124100029002001](https://doi.org/10.1177/0049124100029002001)>; Frank, Maroulis, Duong and Kelcey, 2013, <[doi:10.3102/0162373713493129](https://doi.org/10.3102/0162373713493129)>). An ordinary least squares crosswalk reports the robustness values, impact threshold and replacement percentage computed from the focal t statistic and residual degrees of freedom, makes explicit that their agreement is largely fixed by that shared input, and flags the boundary band in which they disagree. Template-based plain-language reports are included, with optional integration with the 'confoundvis' package for plots.

License MIT + file LICENSE

URL <https://github.com/subirhait/causalfrag>

BugReports <https://github.com/subirhait/causalfrag/issues>

Encoding UTF-8

Depends R (>= 4.1.0)

Imports cli (>= 3.4.0), rlang (>= 1.0.0), jsonlite (>= 1.8.0), glue (>= 1.6.0)

Suggests httr2 (>= 1.0.0), confoundvis (>= 0.1.0), sensemakr (>= 0.1.4), EValue (>= 4.1.3), konfound (>= 0.4.0), rbounds (>= 2.1), rmarkdown (>= 2.14), knitr (>= 1.39), testthat (>= 3.0.0), withr (>= 2.5.0)

VignetteBuilder knitr

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

NeedsCompilation no
Author Subir Hait [aut, cre] (ORCID: <<https://orcid.org/0009-0004-9871-9677>>)
Maintainer Subir Hait <haitsubi@msu.edu>
Repository CRAN
Date/Publication 2026-10-01 21:40:16 UTC

Contents

causalfrag-package	2
compare_cfi	4
compute_cfi	5
compute_cfi_benchmarked	6
compute_cfi_weighted	7
crosswalk	9
detect_design	10
extract_sensemakr	11
flag_fragility	12
fragility_report	13
generate_report	15
interpret_sensitivity	16
is_sens_results	17
new_sens_results	17
plot.sens_results	18
print.sens_results	19
print_cfi	19
run_sensitivity	20
summary.sens_results	21
use_llm_provider	22
visualize_sensitivity	23
Index	24

causalfrag-package	<i>causalfrag: Cross-Framework Sensitivity Analysis with an OLS Cross-walk</i>
--------------------	--

Description

causalfrag runs, classifies, interprets and reports sensitivity analyses for unmeasured confounding across several frameworks.

Its central reporting tool is [crosswalk()]. Under ordinary least squares with model-based standard errors, the point and inference Robustness Values, the conditional ITCV and RIR are all functions of the focal $|t|$ and residual degrees of freedom, so their agreement is largely fixed by construction. ‘crosswalk()’ reports them together with that dependence made explicit, and flags the narrow boundary band in which ITCV and RIR are positive while the inference Robustness Value is still zero.

Main workflow

```
““r fit <- lm(outcome ~ treatment + covariates, data = mydata) crosswalk(fit, treatment = "treatment") # shared-information audit res <- run_sensitivity(fit, treatment = "treatment", data = mydata) res <- flag_fragility(res) # per-framework classification print(res) generate_report(res)““
```

Deprecated

The Causal Fragility Index (`[compute_cfi()]`) and related functions) is deprecated as of version 0.2.0. It averaged statistics that, under OLS, share the same test information. `'sens_report()'` was renamed `[fragility_report()]` to avoid masking `'confoundvis::sens_report()'`.

Supported sensitivity frameworks

- **sensemakr**: Cinelli & Hazlett (2020) partial R-squared approach
- **EValue**: VanderWeele & Ding (2017) E-value metrics
- **konfound**: Frank (2000) Impact Threshold (ITCV)
- **rbounds**: Rosenbaum (2002) bounds for matched designs

Relationship to confoundvis

confoundvis provides visualization tools for sensitivity analysis. **causalfrag** provides the multi-framework runner, the crosswalk, per-framework classification and reporting, and can use **confoundvis** graphics.

Author(s)

Subir Hait <haitsubi@msu.edu>

References

- Frank, K. A. (2000). Impact of a confounding variable on the inference of a regression coefficient. *Sociological Methods & Research*, 29(2), 147–194. doi:10.1177/0049124100029002001
- Cinelli, C., & Hazlett, C. (2020). Making sense of sensitivity: Extending omitted variable bias. *Journal of the Royal Statistical Society: Series B*, 82(1), 39–67. doi:10.1111/rssb.12348
- VanderWeele, T. J., & Ding, P. (2017). Sensitivity analysis in observational research: Introducing the E-value. *Annals of Internal Medicine*, 167(4), 268–274. doi:10.7326/M162607

See Also

Useful links:

- <https://github.com/subirhait/causalfrag>
- Report bugs at <https://github.com/subirhait/causalfrag/issues>

compare_cfi

Compare CFI across multiple treatment effects

Description

Produces a side-by-side comparison table of CFI scores and fragility classifications across two or more `sens_results` objects. Useful for comparing policy interventions or treatment arms.

Usage

```
compare_cfi(...)
```

Arguments

... Two or more named `sens_results` objects. Names become the row labels in the output table.

Value

A data frame with one row per treatment and columns: `treatment`, `outcome`, `cfi`, `label`, `point_fragility`, `significance_fragility`, `rv_q`, `evaluate`, `pct_bias`.

Deprecated

Deprecated in `causalfrag` 0.2.0; see `[crosswalk()]`.

Examples

```
if (requireNamespace("sensemakr", quietly = TRUE)) {
  data("darfur", package = "sensemakr")

  fit_a <- lm(peacefactor ~ directlyharmed + age + female, data = darfur)
  fit_b <- lm(peacefactor ~ herder_dar + age + female, data = darfur)

  res_a <- run_sensitivity(fit_a, "directlyharmed", darfur, verbose = FALSE)
  res_b <- run_sensitivity(fit_b, "herder_dar", darfur, verbose = FALSE)

  res_a <- flag_fragility(res_a)
  res_b <- flag_fragility(res_b)

  compare_cfi(
    "Directly harmed" = res_a,
    "Herder"          = res_b
  )
}
```

compute_cfi	<i>Compute the Causal Fragility Index (CFI)</i>
-------------	---

Description

The Causal Fragility Index (CFI) is a single 0–100 composite score that integrates sensitivity evidence across multiple causal frameworks into one interpretable measure of robustness.

Each framework contributes one or more component scores, which are averaged into the final CFI. Higher scores indicate greater robustness to unmeasured confounding.

Usage

```
compute_cfi(x, weights = NULL)
```

Arguments

- x A sens_results object from run_sensitivity().
- weights Optional named numeric vector to weight components. Names must match: "rv", "rv_alpha", "evaluate", "pct_bias". Default: equal weights.

Value

The input sens_results object with \$cfi populated as a named list with elements:

- score** Numeric 0–100. The overall CFI.
- label** Character. CFI classification label.
- components** Named numeric vector of component scores.
- interpretation** Character. One-sentence plain-language summary.

Scoring rules

Component	Rule	Full score at
RV (point)	$rv / 0.20 * 100$	$RV \geq 0.20$
RV (significance)	$rv_alpha / 0.10 * 100$	$RV \geq 0.10$
E-value	$(evaluate - 1) / 2.0 * 100$	$E\text{-value} \geq 3$
Percent bias	pct_bias (direct)	$pct \geq 100$

CFI classification

CFI range	Label
0 – 24	Fragile
25 – 49	Moderately fragile
50 – 74	Moderately robust
75 – 100	Robust

Deprecated

Deprecated in causalfrag 0.2.0; see [crosswalk()].

Examples

```
res <- new_sens_results(
  design = "regression", treatment = "directlyharmed",
  outcome = "peacefactor", frameworks = c("sensemakr", "evaluate", "itcv"),
  results = list(
    sensemakr = list(rv_q = 0.139, rv_qa = 0.076,
                     r2yd_x = 0.022, estimate = 0.097),
    evaluate   = list(evaluate = 1.90, evaluate_lower = 1.55,
                     estimate = 0.097),
    itcv       = list(itcv = 0.065, rir = 678, pct_bias = 53.1)
  )
)
res <- compute_cfi(res)
print_cfi(res)
```

compute_cfi_benchmarked

Compute benchmark-adjusted CFI

Description

Extends the CFI with benchmark-relative interpretation. Rather than assessing fragility against absolute thresholds, the benchmark-adjusted CFI compares the required confounding strength to the observed association of a named covariate with treatment and outcome.

This answers: "Would an omitted confounder need to be stronger than benchmark_covariate to overturn the conclusion?"

Usage

```
compute_cfi_benchmarked(x, benchmark_covariate, kd = 1)
```

Arguments

x	A sens_results object with sensemakr results.
benchmark_covariate	Character. Name of the covariate to benchmark against. Must be a covariate in the original model.
kd	Numeric. Multiplier for treatment partial R-squared in benchmark. Default 1 (benchmark at 1x covariate strength).

Value

The input sens_results object with \$cfi_benchmarked populated as a named list with elements:

rv_q_benchmark Ratio: RV / benchmark partial R-squared (treat).

rv_qa_benchmark Same for significance threshold.

benchmark_label Plain-language benchmark statement.

exceeds_benchmark Logical. Does required confounding exceed the benchmark covariate's strength?

Deprecated

Deprecated in causalfrag 0.2.0; see [crosswalk()].

Examples

```
if (requireNamespace("sensemakr", quietly = TRUE)) {
  data("darfur", package = "sensemakr")
  fit <- lm(peacefactor ~ directlyharmed + age + female + village,
    data = darfur)
  res <- run_sensitivity(fit, treatment = "directlyharmed", data = darfur,
    benchmark_covariates = "female")
  res <- compute_cfi_benchmarked(res, benchmark_covariate = "female")
  cat(res$cfi_benchmarked$benchmark_label)
}
```

compute_cfi_weighted *Compute CFI with user-defined or preset weights*

Description

Extends compute_cfi() with named weight presets and user-defined weights. Different sensitivity frameworks carry different evidential weight depending on the study design and analyst priorities.

Usage

```
compute_cfi_weighted(x, weights = "balanced")
```

Arguments

<code>x</code>	A <code>sens_results</code> object from <code>run_sensitivity()</code> .
<code>weights</code>	Character preset or named numeric vector. Character: one of "balanced", "rv_priority", "evaluate_priority", "itcv_priority". Numeric: named vector with any subset of <code>c("rv", "rv_alpha", "evaluate", "pct_bias")</code> .

Value

The input `sens_results` object with `$cfi` updated.

Weight presets

- balanced** Equal weight to all available components (default).
- rv_priority** Double weight on both Robustness Value components. Use when the partial R-squared framework is most relevant.
- evaluate_priority** Double weight on E-value. Use when risk-ratio framing is most natural (e.g. binary outcomes, relative risks).
- itcv_priority** Double weight on percent bias (ITCV/konfound). Use when case-replacement interpretability is prioritised.

Deprecated

Deprecated in `causalfrag` 0.2.0; see `[crosswalk()]`.

Note

Presets are transparent defaults, not discipline-specific claims. Present chosen weights explicitly when reporting results.

Examples

```
if (requireNamespace("sensemakr", quietly = TRUE)) {
  data("darfur", package = "sensemakr")
  fit <- lm(peacefactor ~ directlyharmed + age + female, data = darfur)
  res <- run_sensitivity(fit, treatment = "directlyharmed", data = darfur)
  res <- compute_cfi_weighted(res, weights = "rv_priority")
  print_cfi(res)
}
```

crosswalk

*OLS crosswalk of shared-information sensitivity statistics***Description**

Under ordinary least squares with model-based standard errors, a fixed significance level and $q = 1$, the point and inference Robustness Values (Cinelli and Hazlett, 2020), the conditional impact threshold for a confounding variable (ITCV; Frank, 2000) and the robustness of inference to replacement (RIR; Frank et al., 2013) are all functions of the focal $|t|$ and the residual degrees of freedom ν . ‘crosswalk()’ computes all of them from that shared input, so that they can be reported together with an explicit statement that their agreement is largely fixed by construction and is not independent corroboration.

Usage

```
crosswalk(x, ...)

## Default S3 method:
crosswalk(x, ..., df, n = NULL, alpha = 0.05)

## S3 method for class 'lm'
crosswalk(x, treatment, ..., alpha = 0.05)

## S3 method for class 'sens_results'
crosswalk(x, ..., alpha = 0.05)
```

Arguments

x	A fitted ‘lm’ object, a ‘sens_results’ object created from one, or a numeric t statistic (in which case ‘df’ is required).
...	Further arguments passed to methods.
df	Residual degrees of freedom (numeric method).
n	Optional number of observations, used to express RIR as a count of cases (numeric method). Defaults to ‘df + 2’.
alpha	Two-sided significance level. Default 0.05.
treatment	Character. Name of the treatment coefficient (‘lm’ and ‘sens_results’ methods).

Details

With $f = |t|/\sqrt{\nu}$, the point Robustness Value is $RV = \{\sqrt{f^4 + 4f^2} - f^2\}/2$. The inference Robustness Value replaces f by $f - t_{\nu-1}^*/\sqrt{\nu-1}$ (zero when that is not positive), following the **sensemakr** convention. The partial correlation is $r = t/\sqrt{t^2 + \nu}$, the critical correlation is $r^\# = c/\sqrt{c^2 + \nu}$ with $c = t_\nu^*$, the conditional ITCV is $(|r| - r^\#)/(1 - r^\#)$, and the RIR percentage is $100(1 - c/|t|)$, following the **konfound** convention.

Because the two conventions use slightly different degrees of freedom in their critical terms, there is a narrow *boundary band*, $c < |t| \leq t_{\nu-1}^* \sqrt{\nu/(\nu-1)}$, in which ITCV and RIR are already

positive while the inference Robustness Value is still zero. The returned object flags whether the estimate lies in that band.

The crosswalk applies to OLS with model-based standard errors. It should not be carried over to heteroskedasticity-robust or cluster-robust standard errors. E-values, Oster's delta and benchmark-based bounds use information beyond $|t|$ and ν and are outside the crosswalk.

Value

An object of class 'cf_crosswalk': a list with the inputs ('t', 'df', 'n', 'alpha'), the partial correlation 'r', the critical values, 'rv', 'rv_alpha', 'itcv', 'rir_pct', 'rir_n', the logical flag 'boundary_band', and a data frame 'table' summarising each statistic and the information it uses.

References

- Cinelli, C., & Hazlett, C. (2020). Making sense of sensitivity: Extending omitted variable bias. **Journal of the Royal Statistical Society: Series B**, 82(1), 39–67. doi:[10.1111/rssb.12348](https://doi.org/10.1111/rssb.12348)
- Frank, K. A. (2000). Impact of a confounding variable on a regression coefficient. **Sociological Methods & Research**, 29(2), 147–194. doi:[10.1177/0049124100029002001](https://doi.org/10.1177/0049124100029002001)
- Frank, K. A., Maroulis, S. J., Duong, M. Q., & Kelcey, B. M. (2013). What would it take to change an inference? **Educational Evaluation and Policy Analysis**, 35(4), 437–460. doi:[10.3102/0162373713493129](https://doi.org/10.3102/0162373713493129)

Examples

```
# From a t statistic and residual degrees of freedom
crosswalk(4.2228, df = 5668)

# From a fitted model
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
crosswalk(fit, treatment = "am")

# Just above the conventional threshold: the boundary band
crosswalk(1.972, df = 244)
```

detect_design

Detect the study design from a model object

Description

Inspects a fitted model object and returns the most appropriate sensitivity analysis design type. The detected design determines which sensitivity frameworks are run by 'run_sensitivity()'.

Users can always override the detected design manually via the 'design' argument in 'fragility_report()' or 'run_sensitivity()'.

Usage

```
detect_design(model, verbose = TRUE)
```

Arguments

- | | |
|---------|--|
| model | A fitted model object. Supported classes: <ul style="list-style-type: none"> • 'lm', 'glm' → "regression" • 'lmerMod', 'glmerMod' (lme4) → "regression" • Objects with class "Match" (Matching package) → "matched" • 'coxph', 'survreg' (survival) → "survival" • 'ivreg' (ivreg/AER) → "iv" |
| verbose | Logical. If 'TRUE', prints the detected design. Default 'TRUE'. |

Value

A character string: one of "regression", "matched", "survival", "iv", or "unknown".

Examples

```
fit <- lm(mpg ~ am + wt + hp, data = mtcars)
detect_design(fit)
```

extract_sensemakr	<i>Extract and standardise results from a sensemakr object</i>
-------------------	--

Description

Inspects a fitted sensemakr object and returns a clean named list with correctly mapped field names, ready to pass to new_sens_results().

This function exists because sensemakr internal field names (rv_q, rv_qa) are not immediately obvious from the printed output, and differ across versions. Always use this extractor rather than accessing sm\$sensitivity_stats directly.

Usage

```
extract_sensemakr(sm)
```

Arguments

- | | |
|----|--|
| sm | A sensemakr object returned by sensemakr::sensemakr(). |
|----|--|

Value

A named list with elements:

- estimate** Point estimate of the treatment effect.
- se** Standard error.
- t_stat** t-statistic.

r2yd_x Partial R-squared of treatment with outcome.
r2dz_x Partial R-squared of treatment with treatment (benchmark).
rv_q Robustness Value for q=1 (point-estimate nullification).
rv_qa Robustness Value for q=1, alpha=.05 (significance).
raw_object The original sensemakr object.

Examples

```
if (requireNamespace("sensemakr", quietly = TRUE)) {
  data("darfur", package = "sensemakr")
  fit <- lm(peacefactor ~ directlyharmed + age + female + village,
            data = darfur)
  sm <- sensemakr::sensemakr(fit, treatment = "directlyharmed")
  extract_sensemakr(sm)
}
```

flag_fragility

Flag the fragility of a sensitivity analysis conclusion

Description

Classifies the robustness of a causal conclusion using a five-level scale separately for (1) point-estimate nullification and (2) statistical significance, where supported by the framework.

Usage

```
flag_fragility(x, thresholds = NULL)
```

Arguments

x A sens_results object from run_sensitivity().
thresholds Optional named list to override default thresholds.

Value

The input sens_results object with \$fragility populated as a named list with elements point, alpha, point_label, alpha_label.

Classification scale

Level	RV threshold	Meaning
Highly stable	≥ 0.20	Very strong confounding needed
Stable	$0.10 - 0.20$	Moderate confounding needed
Moderately fragile	$0.05 - 0.10$	Plausible confounding could matter
Fragile	$0.01 - 0.05$	Weak confounding could overturn result
Highly fragile	< 0.01	Minimal confounding overturns result

Interpreting the labels

The labels are descriptive conventions, not judgments that a result is or is not credible. There is no universal threshold for robustness; compare the required confounding with substantive knowledge and observed benchmarks for the application at hand.

Examples

```
res <- new_sens_results(
  design = "regression", treatment = "t", outcome = "y",
  frameworks = "sensemakr",
  results = list(sensemakr = list(rv_q = 0.14, rv_qa = 0.08,
                                r2yd_x = 0.02, estimate = 0.10))
)
res <- flag_fragility(res)
res$fragility
```

fragility_report

Run the full sensitivity analysis pipeline

Description

Renamed from ‘sens_report()’ in causalfrag 0.2.0 to avoid masking ‘confoundvis::sens_report()’ when both packages are attached.

The main user-facing function. It runs the available sensitivity-analysis frameworks, classifies fragility, creates a narrative interpretation, and optionally draws a sensitivity plot when a supported plotting object is available.

Usage

```
fragility_report(
  model,
  treatment,
  data,
  design = NULL,
  narrative = "standard",
  plot = TRUE,
  ...
)
```

Arguments

<code>model</code>	A fitted model object (for example, from <code>lm()</code> or <code>glm()</code>).
<code>treatment</code>	Character. Name of the treatment variable in the model.
<code>data</code>	A data frame containing the variables in <code>'model'</code> .
<code>design</code>	Character. Optional study-design override. One of <code>"regression"</code> , <code>"matched"</code> , <code>"iv"</code> , or <code>"survival"</code> . The default, <code>'NULL'</code> , detects the design automatically.
<code>narrative</code>	Character. Narrative detail: <code>"brief"</code> , <code>"standard"</code> , or <code>"reviewer-ready"</code> . The default is <code>"standard"</code> .
<code>plot</code>	Logical. If <code>'TRUE'</code> , draw a sensitivity plot when the required plotting object and package are available. The default is <code>'TRUE'</code> .
<code>...</code>	Additional arguments passed to <code>'run_sensitivity()'</code> .

Value

A `'sens_results'` object containing the framework-specific numeric results, fragility classifications, the OLS crosswalk when available, and narrative interpretation. When `'plot = TRUE'`, a plot may also be produced as a side effect.

Examples

```
if (requireNamespace("sensemakr", quietly = TRUE)) {
  data("darfur", package = "sensemakr")
  fit <- lm(peacefactor ~ directlyharmed + age + female + village,
           data = darfur)
  result <- fragility_report(
    fit,
    treatment = "directlyharmed",
    data = darfur,
    frameworks = "sensemakr",
    plot = FALSE
  )
  print(result)
}
```

generate_report	<i>Generate a structured sensitivity analysis report</i>
-----------------	--

Description

Produces a complete, structured report from a `sens_results` object. The report includes study design, numeric results, fragility classification, narrative interpretation, and suggested reporting language for academic papers.

Works fully offline without an API key. If `interpret_sensitivity()` has not been run, the function runs it automatically using template-based narratives.

Usage

```
generate_report(
  x,
  format = c("markdown", "text"),
  include_citation = TRUE,
  verbosity = "standard",
  file = NULL
)
```

Arguments

<code>x</code>	A <code>sens_results</code> object, ideally with fragility assessed.
<code>format</code>	Character. Output format. One of "markdown", "text". Default "markdown".
<code>include_citation</code>	Logical. Append reference list. Default TRUE.
<code>verbosity</code>	Character. Narrative verbosity passed to <code>interpret_sensitivity()</code> if narrative not yet generated. Default "standard".
<code>file</code>	Character. Optional file path to write the report. If NULL (default), returns the report as a character string and prints it.

Value

Invisibly returns the report as a character string. If `file` is specified, also writes to disk.

Examples

```
res <- new_sens_results(
  design = "regression", treatment = "directlyharmed",
  outcome = "peacefactor", frameworks = c("sensemakr", "evaluate"),
  results = list(
    sensemakr = list(estimate = 0.097, r2yd_x = 0.022,
                     rv_q = 0.139, rv_qa = 0.076),
    evaluate = list(estimate = 0.097, evaluate = 1.90,
                    evaluate_lower = 1.55)
  ),
)
```

```

    fragility = list(point = "Stable", alpha = "Moderately fragile",
                     point_label = "RV = 13.9%", alpha_label = "RV = 7.6%")
  )
  report <- generate_report(res)
  cat(report)

```

`interpret_sensitivity` *Interpret sensitivity results using an LLM or concise templates*

Description

Generates a concise plain-language interpretation (2-3 sentences per framework) of sensitivity analysis findings. Uses an LLM if configured via `use_llm_provider()`; falls back to pre-written concise templates when no LLM is available.

The LLM assists only in phrasing. All statistical values come from the `sens_results` object computed by transparent R functions.

Usage

```
interpret_sensitivity(x, verbosity = "standard", cache = TRUE, ...)
```

Arguments

<code>x</code>	A <code>sens_results</code> object with fragility assessed.
<code>verbosity</code>	Character. Controls output length. "brief" = one sentence per framework. "standard" = 2-3 sentences per framework (default). "reviewer-ready" = full methods paragraph with citations.
<code>cache</code>	Logical. Cache the LLM response to avoid repeat API calls. Default TRUE.
<code>...</code>	Reserved for future use.

Value

The input `sens_results` object with `$narrative` populated.

Examples

```

res <- new_sens_results(
  design = "regression", treatment = "directlyharmed",
  outcome = "peacefactor", frameworks = "sensemakr",
  results = list(sensemakr = list(
    rv_q = 0.139, rv_qa = 0.076, r2yd_x = 0.022, estimate = 0.097
  )),
  fragility = list(point = "Stable", alpha = "Moderately fragile",
                   point_label = "", alpha_label = "")
)
res <- interpret_sensitivity(res)

```

```
cat(res$narrative)
```

is_sens_results	<i>Check if object is a sens_results</i>
-----------------	--

Description

Check if object is a sens_results

Usage

```
is_sens_results(x)
```

Arguments

x Any R object.

Value

Logical.

new_sens_results	<i>Create a sens_results object</i>
------------------	-------------------------------------

Description

Constructor for the unified sens_results S3 class. This is the central data structure that all causalfrag functions produce and consume.

Usage

```
new_sens_results(
  design,
  treatment,
  outcome,
  frameworks,
  results,
  fragility = NULL,
  narrative = NULL,
  llm_used = FALSE,
  call = NULL,
  crosswalk = NULL
)
```

Arguments

design	Character. Detected study design. One of "regression", "matched", "iv", "survival".
treatment	Character. Name of the treatment variable.
outcome	Character. Name of the outcome variable.
frameworks	Character vector. Which sensitivity frameworks were run.
results	Named list. Raw numeric results from each framework.
fragility	Named list with elements point and alpha.
narrative	Character. Plain-language interpretation.
llm_used	Logical. Whether an LLM was used for narrative generation.
call	The matched call.
crosswalk	Optional 'cf_crosswalk' object from [crosswalk()].

Value

An object of class sens_results.

Examples

```
res <- new_sens_results(
  design    = "regression",
  treatment = "treat",
  outcome   = "outcome",
  frameworks = "sensemakr",
  results   = list(sensemakr = list(rv_q = 0.14, rv_qa = 0.08,
                                     r2yd_x = 0.02, estimate = 0.10))
)
print(res)
```

plot.sens_results	<i>Plot method for sens_results</i>
-------------------	-------------------------------------

Description

Plot method for sens_results

Usage

```
## S3 method for class 'sens_results'
plot(x, ...)
```

Arguments

x A sens_results object.
 ... Passed to visualize_sensitivity().

Value

Invisibly returns x, the unchanged sens_results object. The method is called for its side effect of drawing a sensitivity plot.

print.sens_results *Print method for sens_results*

Description

Print method for sens_results

Usage

```
## S3 method for class 'sens_results'
print(x, ...)
```

Arguments

x A sens_results object.
 ... Further arguments (unused).

Value

Invisibly returns x, the unchanged sens_results object. The method is called for its side effect of printing a formatted summary.

print_cfi *Print the Causal Fragility Index*

Description

Displays a formatted summary of the CFI score, component breakdown, and interpretation. Call after compute_cfi().

Usage

```
print_cfi(x, ...)
```

Arguments

`x` A `sens_results` object with `$cfi` populated.
`...` Further arguments (unused).

Value

Invisibly returns `x`.

Deprecated

Deprecated in `causalfrag` 0.2.0; see `[crosswalk()]`.

<code>run_sensitivity</code>	<i>Run sensitivity analysis across frameworks</i>
------------------------------	---

Description

Dispatches to the appropriate sensitivity analysis packages based on the detected or user-specified study design. Returns a unified ‘`sens_results`’ object containing numeric results from all frameworks run.

Each framework is called only if the required package is installed. Missing packages produce a warning, not an error, so the function always returns whatever results it can compute.

Usage

```
run_sensitivity(
  model,
  treatment,
  data,
  design = NULL,
  frameworks = NULL,
  benchmark_covariates = NULL,
  verbose = TRUE,
  ...
)
```

Arguments

`model` A fitted model object (e.g. from `lm()`, `glm()`).
`treatment` Character. Name of the treatment variable.
`data` A data frame containing the model variables.
`design` Character. Study design. If `NULL`, calls `detect_design()` automatically. One of "regression", "matched", "iv", "survival".
`frameworks` Character vector. Which frameworks to run. If `NULL`, selects automatically based on design. Subset of `c("sensemakr", "evaluate", "itcv", "rosenbaum")`.

benchmark_covariates	Character vector. Covariate names to use as benchmarks in sensemakr. Default NULL.
verbose	Logical. Print progress messages. Default TRUE.
...	Additional arguments (reserved for future use).

Value

A sens_results object with \$results populated for each framework successfully run.

Examples

```
if (requireNamespace("sensemakr", quietly = TRUE)) {
  data("darfur", package = "sensemakr")
  fit <- lm(peacefactor ~ directlyharmed + age + female + village,
           data = darfur)
  res <- run_sensitivity(fit, treatment = "directlyharmed", data = darfur)
  print(res)
}
```

summary.sens_results	<i>Summary method for sens_results</i>
----------------------	--

Description

Summary method for sens_results

Usage

```
## S3 method for class 'sens_results'
summary(object, ...)
```

Arguments

object	A sens_results object.
...	Further arguments (unused).

Value

Invisibly returns object, the unchanged sens_results object. The method is called for its side effect of printing a concise summary of the study, frameworks, fragility assessment, and narrative status.

use_llm_provider	<i>Configure the LLM provider for causalfrag</i>
------------------	--

Description

Sets up the LLM provider used by ‘interpret_sensitivity()’ and ‘generate_report()’. Configuration is stored in the R session environment.

****The package works fully without calling this function.**** When no LLM is configured, narrative output falls back to pre-written templates based on the numeric results.

Usage

```
use_llm_provider(
  provider = c("openai", "anthropic", "none"),
  api_key = NULL,
  model = NULL,
  max_tokens = 512L
)
```

Arguments

provider	Character. One of “openai”, “anthropic”, “none”. Use “none” to explicitly disable LLM and use templates only.
api_key	Character. Your API key. If ‘NULL’, the function looks for environment variables ‘OPENAI_API_KEY’ or ‘ANTHROPIC_API_KEY’.
model	Character. Model name to use. • OpenAI default: “gpt-4o” • Anthropic default: “claude-3-5-haiku-latest”
max_tokens	Integer. Maximum tokens for LLM response. Default 512.

Value

Invisibly returns a list of the current LLM configuration.

Examples

```
# Use Anthropic (key from environment variable)
use_llm_provider("anthropic")

# Use OpenAI with explicit key
use_llm_provider("openai", api_key = "sk-...")

# Disable LLM explicitly (template mode)
use_llm_provider("none")
```

`visualize_sensitivity` *Plot sensitivity contours from a `sens_results` object*

Description

Produces sensitivity analysis figures using **sensemakr**'s built-in plotting functions, or **confoundvis** if installed and engine is set accordingly. Plots are generated for each framework in the `sens_results` object that supports visualisation.

Usage

```
visualize_sensitivity(x, engine = "sensemakr", type = "contour", ...)
```

Arguments

<code>x</code>	A <code>sens_results</code> object.
<code>engine</code>	Character. One of "sensemakr", "confoundvis". Default "sensemakr" (uses the raw <code>sensemakr</code> object stored in <code>x\$results\$sensemakr\$raw_object</code>).
<code>type</code>	Character. Plot type for <code>sensemakr</code> engine. One of "contour", "extreme". Default "contour".
<code>...</code>	Additional arguments passed to the plotting function.

Value

Invisibly returns `x`. Called for side effects (plots).

Examples

```
if (requireNamespace("sensemakr", quietly = TRUE)) {  
  data("darfur", package = "sensemakr")  
  fit <- lm(peacefactor ~ directlyharmed + age + female + village,  
           data = darfur)  
  res <- run_sensitivity(fit, treatment = "directlyharmed", data = darfur,  
                       benchmark_covariates = "female")  
  visualize_sensitivity(res)  
  visualize_sensitivity(res, type = "extreme")  
}
```

Index

causalfrag (causalfrag-package), [2](#)
causalfrag-package, [2](#)
compare_cfi, [4](#)
compute_cfi, [5](#)
compute_cfi_benchmarked, [6](#)
compute_cfi_weighted, [7](#)
crosswalk, [9](#)

detect_design, [10](#)

extract_sensemakr, [11](#)

flag_fragility, [12](#)
fragility_report, [13](#)

generate_report, [15](#)

interpret_sensitivity, [16](#)
is_sens_results, [17](#)

new_sens_results, [17](#)

plot.sens_results, [18](#)
print.sens_results, [19](#)
print_cfi, [19](#)

run_sensitivity, [20](#)

summary.sens_results, [21](#)

use_llm_provider, [22](#)

visualize_sensitivity, [23](#)