

Package ‘immunaut’

September 10, 2026

Version 1.0.3

Date 2026-09-10

Title Machine Learning Immunogenicity and Vaccine Response Analysis

Author Ivan Tomic [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0003-3596-681X>>),
Adriana Tomic [aut, ctb, cph, fnd] (ORCID:
<<https://orcid.org/0000-0001-9885-3535>>),
Stephanie Hao [aut] (ORCID: <<https://orcid.org/0000-0002-3760-8234>>)

Description Used for analyzing immune responses and predicting vaccine efficacy using machine learning and advanced data processing techniques. 'Immunaut' integrates both unsupervised and supervised learning methods, managing outliers and capturing immune response variability. It performs multiple rounds of predictive model testing to identify robust immunogenicity signatures that can predict vaccine responsiveness. The platform is designed to handle high-dimensional immune data, enabling researchers to uncover immune predictors and refine personalized vaccination strategies across diverse populations.

Maintainer Ivan Tomic <info@ivantomic.com>

Imports cluster, plyr, dplyr, caret, pROC, PRROC, stats, rlang, Rtsne,
dbscan, FNN, igraph, fpc, mclust, ggplot2, grDevices,
RColorBrewer, R.utils, clusterSim, parallel, doParallel,
MLmetrics

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Depends R (>= 3.4.0)

URL <https://github.com/atomiclaboratory/immunaut>,
<<https://atomic-lab.org>>

BugReports <https://github.com/atomiclaboratory/immunaut/issues>

License GPL-3

Encoding UTF-8

LazyLoad yes

LazyData yes

Config/roxygen2/version 8.0.0
NeedsCompilation no
Repository CRAN
Date/Publication 2026-09-10 13:10:02 UTC

Contents

auto_simon_ml	2
generate_demo_data	4
generate_file_header	5
immunaut	6
immunautDemo	9
immunautLAIV	9
plot_clustered_tsne	10
Index	12

auto_simon_ml	<i>Automated Machine Learning Model Building</i>
---------------	--

Description

This function automates the process of building machine learning models using the caret package. It supports both binary and multi-class classification and allows users to specify a list of machine learning algorithms to be trained on the dataset.

Usage

```
auto_simon_ml(dataset_ml, settings)
```

Arguments

- | | |
|------------|---|
| dataset_ml | A data frame containing the dataset for training. All columns except the outcome column (and any specified in settings\$excludedColumns) should contain the features. |
| settings | A list containing the following parameters: <ul style="list-style-type: none">• outcome: A string specifying the name of the outcome column in dataset_ml. Defaults to "immunaut".• models or selectedPackages: A character vector specifying the machine learning algorithms to train (e.g., "rpart", "rf"). Defaults to c("nb", "rpart").• trainTestRatio or selectedPartitionSplit: A numeric value specifying the proportion of data for training (between 0 and 1). Defaults to 0.7.• excludedColumns: A character vector of column names to be excluded from feature predictors. Defaults to NULL. |

- `preProcessDataset`: A character vector of preprocessing transformations (e.g., `c("medianImpute", "center", "scale", "zv")`). Defaults to `NULL`.
- `num_cores`: Integer. The number of CPU cores to use for parallel training. Defaults to 2 (or 1 during CRAN check environments).
- `kFold`: Integer. The number of cross-validation folds. Defaults to 5.
- `kFoldRepeat`: Integer. The number of cross-validation repeats. Defaults to 1.
- `trainingTimeout`: Numeric. Timeout in seconds for training each individual model. Defaults to 180.

Details

To prevent data leakage, the dataset is partitioned into training and testing sets *before* any pre-processing is performed. Transformation parameters (imputation, centering, scaling, filtering) are learned exclusively from the training partition and applied without leakage to the test set.

The function partitions the data into training and testing sets prior to applying preprocessing, guaranteeing strict isolation between train and test distributions. Models are trained using repeated cross-validation via `caret::train()`.

For binary classification, AUROC and PR-AUC are calculated. For multi-class classification, macro-averaged AUROC, weighted AUROC, and macro-averaged F1 scores are computed from the test partition.

Value

A list containing:

- `models`: A list where each element corresponds to a trained model. Contains info, training, and predictions.
- `dataset`: The combined preprocessed dataset.
- `trainData`: The preprocessed training dataset.
- `testData`: The preprocessed test dataset.
- `is_binary_classification`: Logical indicating whether the problem is binary classification.
- `preProcessParams`: The preprocessing parameter object(s) fitted on the training dataset.

Examples

```
# Generate demo dataset and run clustering pipeline
demo_data <- generate_demo_data(n_subjects = 80, n_features = 8, desired_number_clusters = 3)
settings <- list(preProcessDataset = c("medianImpute", "center", "scale"))
result <- immunaut(demo_data, settings)
```

```
# Train automated machine learning model on clustered cohort
ml_settings <- list(
  outcome = "immunaut",
  models = c("rpart"),
  excludedColumns = c("outcome", "age", "gender"),
  preProcessDataset = c("medianImpute", "center", "scale"),
```

```

    trainTestRatio = 0.7,
    num_cores = 1
)
ml_results <- auto_simon_ml(result$dataset$dataset_ml, ml_settings)
print(names(ml_results$models))

```

generate_demo_data	<i>Generate a Demo Dataset with Specified Number of Clusters and Overlap</i>
--------------------	--

Description

This function generates a demo dataset with a specified number of subjects, features, and desired number of clusters, ensuring that the generated clusters are not too far apart and have some degree of overlap to simulate real-world data. The generated dataset includes demographic information (outcome, age, and gender), as well as numeric features with a specified probability of missing values.

Usage

```

generate_demo_data(
  n_subjects = 1000,
  n_features = 200,
  missing_prob = 0.1,
  desired_number_clusters = 3,
  cluster_overlap_sd = 15
)

```

Arguments

n_subjects	Integer. The number of subjects (rows) to generate. Defaults to 1000.
n_features	Integer. The number of features (columns) to generate. Defaults to 200.
missing_prob	Numeric. The probability of introducing missing values (NA) in the feature columns. Defaults to 0.1.
desired_number_clusters	Integer. The approximate number of clusters to generate in the feature space. Defaults to 3.
cluster_overlap_sd	Numeric. The standard deviation to control cluster overlap. Defaults to 15 for more overlap.

Details

The function generates n_features numeric columns based on Gaussian clusters with some overlap between clusters to simulate more realistic data. Missing values are introduced in each feature column based on the missing_prob.

Value

A data frame containing the generated demo dataset, with columns:

- outcome: A categorical variable with values "low" or "high".
- age: A numeric variable representing the age of the subject (range 18-90).
- gender: A categorical variable with values "male" or "female".
- Feature X: Numeric feature columns with random values and some missing data.

Examples

```
# Generate a demo dataset with 1000 subjects, 200 features, and 3 clusters
demo_data <- generate_demo_data(n_subjects = 1000, n_features = 200,
                                desired_number_clusters = 3,
                                cluster_overlap_sd = 15, missing_prob = 0.1)

# View the first few rows of the dataset
head(demo_data)
```

generate_file_header	<i>Generate a File Header</i>
----------------------	-------------------------------

Description

This function generates a fileHeader object from a given data frame which includes original names and remapped names of the data frame columns.

Usage

```
generate_file_header(dataset)
```

Arguments

dataset	The input data frame.
---------	-----------------------

Value

A data frame containing original and remapped column names.

immunaut

*Main function to carry out Immunaut Analysis***Description**

This function performs clustering and dimensionality reduction analysis on a dataset using user-defined settings. It handles various preprocessing steps, dimensionality reduction via t-SNE, multiple clustering methods, and generates associated plots based on user-defined or default settings.

Usage

```
immunaut(dataset, settings = list())
```

Arguments

- | | |
|----------|--|
| dataset | A data frame representing the dataset on which the analysis will be performed. The dataset must contain numeric columns for dimensionality reduction and clustering. |
| settings | <p>A named list containing settings for the analysis. If NULL, defaults will be used. The settings list may contain:</p> <p>fileHeader A data frame mapping the original column names to remapped column names. Used for t-SNE input preparation.</p> <p>selectedColumns Character vector of columns to be used for the analysis. Defaults to NULL.</p> <p>cutOffColumnSize Numeric. The maximum size of the dataset in terms of columns. Defaults to 50,000.</p> <p>excludedColumns Character vector of columns to exclude from the analysis. Defaults to NULL.</p> <p>groupingVariables Character vector of columns to use for grouping the data during analysis. Defaults to NULL.</p> <p>colorVariables Character vector of columns to use for coloring in the plots. Defaults to NULL.</p> <p>preProcessDataset Character vector of preprocessing methods to apply (e.g., scaling, normalization). Defaults to NULL.</p> <p>fontSize Numeric. Font size for plots. Defaults to 12.</p> <p>pointSize Numeric. Size of points in plots. Defaults to 1.5.</p> <p>theme Character. The ggplot2 theme to use (e.g., "theme_gray"). Defaults to "theme_gray".</p> <p>colorPalette Character. Color palette for plots (e.g., "RdPu"). Defaults to "RdPu".</p> <p>aspect_ratio Numeric. The aspect ratio of plots. Defaults to 1.</p> <p>clusterType Character. The clustering method to use. Options are "Louvain", "Hierarchical", "Mclust", "Density". Defaults to "Louvain".</p> <p>removeNA Logical. Whether to remove rows with NA values. Defaults to FALSE.</p> |

datasetAnalysisGrouped Logical. Whether to perform grouped dataset analysis. Defaults to FALSE.

plot_size Numeric. The size of the plot. Defaults to 12.

knn_clusters Numeric. The number of clusters for KNN-based clustering. Defaults to 250.

perplexity Numeric. The perplexity parameter for t-SNE. Defaults to NULL (automatically determined).

exaggeration_factor Numeric. The exaggeration factor for t-SNE. Defaults to NULL.

max_iter Numeric. The maximum number of iterations for t-SNE. Defaults to NULL.

theta Numeric. The Barnes-Hut approximation parameter for t-SNE. Defaults to NULL.

eta Numeric. The learning rate for t-SNE. Defaults to NULL.

clustLinkage Character. Linkage method for hierarchical clustering. Defaults to "ward.D2".

clustGroups Numeric. The number of groups for hierarchical clustering. Defaults to 9.

distMethod Character. Distance metric for clustering. Defaults to "euclidean".

minPtsAdjustmentFactor Numeric. Adjustment factor for the minimum points in DBSCAN clustering. Defaults to 1.

epsQuantile Numeric. Quantile to compute the epsilon parameter for DBSCAN clustering. Defaults to 0.9.

assignOutliers Logical. Whether to assign outliers in the clustering step. Defaults to TRUE.

excludeOutliers Logical. Whether to exclude outliers from clustering. Defaults to TRUE.

legendPosition Character. Position of the legend in plots (e.g., "right", "bottom"). Defaults to "right".

datasetAnalysisClustLinkage Character. Linkage method for dataset-level analysis. Defaults to "ward.D2".

datasetAnalysisType Character. Type of dataset analysis (e.g., "heatmap"). Defaults to "heatmap".

datasetAnalysisRemoveOutliersDownstream Logical. Whether to remove outliers during downstream dataset analysis (e.g., machine learning). Defaults to FALSE.

datasetAnalysisSortColumn Character. The column used to sort dataset analysis results. Defaults to "cluster".

datasetAnalysisClustOrdering Numeric. The order of clusters for analysis. Defaults to 1.

anyNAValues Logical. Whether the dataset contains NA values. Defaults to FALSE.

categoricalVariables Logical. Whether the dataset contains categorical variables. Defaults to FALSE.

- resolution_increments** Numeric vector. The resolution increments to be used for Louvain clustering. Defaults to `c(0.01, 0.05, 0.1, 0.2, 0.3, 0.4, 0.5)`.
- min_modularities** Numeric vector. The minimum modularities to test for clustering. Defaults to `c(0.4, 0.5, 0.6, 0.7, 0.8, 0.85, 0.9)`.
- target_clusters_range** Numeric vector. The range of acceptable clusters to identify. Defaults to `c(3, 6)`.
- pickBestClusterMethod** Character. The method to use for picking the best clustering result: "Overall" (multi-metric composite score of normalized modularity, silhouette, Davies-Bouldin, and Calinski-Harabasz indices), "Modularity", "Silhouette", or "SIMON". Defaults to "Modularity".
- weights** List. Weights for evaluating clusters based on AUROC, modularity, and silhouette. Defaults to `list(AUROC = 0.5, modularity = 0.3, silhouette = 0.2)`. These weights are applied to help choose the most relevant clusters based on user goals:
- AUROC** Weight for predictive performance (area under the receiver operating characteristic curve). Prioritize this when predictive accuracy is the main goal. For predictive analysis, a recommended configuration could be `list(AUROC = 0.8, modularity = 0.1, silhouette = 0.1)`.
 - modularity** Weight for modularity score, which indicates the strength of clustering. Higher modularity suggests that clusters are well-separated. To prioritize well-separated clusters, use a configuration like `list(AUROC = 0.4, modularity = 0.4, silhouette = 0.2)`.
 - silhouette** Weight for silhouette score, a measure of cohesion within clusters. Useful when cluster cohesion and interpretability are desired. For balanced clusters, a suggested configuration is `list(AUROC = 0.4, modularity = 0.3, silhouette = 0.3)`.

Value

A list containing the following:

- **tsne_calc**: The t-SNE results object (coordinates, PCA variances, perplexity).
- **tsne_clust**: The clustering results (centroids, cluster sizes, silhouette scores, modularity).
- **dataset**: A list containing the original dataset (`original`), the preprocessed dataset (`preprocessed`), and the machine learning-ready dataset (`dataset_ml`) with the `immunaut` outcome column attached.
- **clusters**: The final cluster assignments.
- **settings**: The list of settings used for the analysis.

Examples

```
data <- matrix(runif(2000), ncol=20)
settings <- list(clusterType = "Louvain",
  resolution_increments = c(0.05, 0.1),
  min_modularities = c(0.3, 0.5))
result <- immunaut(data.frame(data), settings)
print(result$clusters)
```

immunautDemo	<i>Demo data set from immunaut package. This data is used in this package examples. It consist of 4x4 feature matrix + additional dummy columns that can be used for testing.</i>
--------------	---

Description

Demo data set from immunaut package. This data is used in this package examples. It consist of 4x4 feature matrix + additional dummy columns that can be used for testing.

Usage

```
data(immunautDemo)
```

Format

An object of class data.frame with 4 rows and 7 columns.

Examples

```
## Not run:
data(immunautDemo)
## define settings variable
settings <- list()
settings$fileHeader <- generate_file_header(immunautDemo)
# ... and other settings
results <- immunaut(immunautDemo, settings)

## End(Not run)
```

immunautLAIV	<i>Demo data set from immunaut package. This data is used in this package examples.</i>
--------------	---

Description

Demo data set from immunaut package. This data is used in this package examples.

Usage

```
data(immunautLAIV)
```

Format

An object of class `data.frame` with 244 rows and 32 columns.

Examples

```
## Not run:
data(immunautLAIV)
## define settings variable
settings <- list()
settings$fileHeader <- generate_file_header(immunautLAIV)
# ... and other settings
results <- immunaut(immunautLAIV, settings)

## End(Not run)
```

`plot_clustered_tsne` *Plot Clustered t-SNE Results*

Description

This function generates a t-SNE plot with cluster assignments using consistent color mappings. It includes options for plotting points based on their t-SNE coordinates and adding cluster labels at the cluster centroids.

Usage

```
plot_clustered_tsne(info.norm, cluster_data, settings)
```

Arguments

- | | |
|---------------------------|--|
| <code>info.norm</code> | A data frame containing t-SNE coordinates (<code>tsne1</code> , <code>tsne2</code>) and cluster assignments (<code>pandora_cluster</code>) for each point. |
| <code>cluster_data</code> | A data frame containing the cluster centroids and labels, with columns <code>tsne1</code> , <code>tsne2</code> , <code>label</code> , and <code>pandora_cluster</code> . |
| <code>settings</code> | A list of settings for the plot, including: <ul style="list-style-type: none"> • <code>theme</code>: The ggplot2 theme to use (e.g., <code>"theme_classic"</code>). • <code>colorPalette</code>: The color palette to use for clusters (e.g., <code>"RdPu"</code>). • <code>pointSize</code>: The size of points in the plot. • <code>fontSize</code>: The font size used in the plot. • <code>legendPosition</code>: The position of the legend (e.g., <code>"right"</code>). • <code>plot_size</code>: The size of the plot. • <code>aspect_ratio</code>: The aspect ratio of the plot. |

Value

ggplot2 object representing the clustered t-SNE plot.

Examples

```
## Not run:  
# Example usage  
plot <- plot_clustered_tsne(info.norm, cluster_data, settings)  
print(plot)  
  
## End(Not run)
```

Index

* **datasets**

immunautDemo, [9](#)

immunautLAIV, [9](#)

auto_simon_ml, [2](#)

generate_demo_data, [4](#)

generate_file_header, [5](#)

immunaut, [6](#)

immunautDemo, [9](#)

immunautLAIV, [9](#)

plot_clustered_tsne, [10](#)