

Package ‘medicalcoder’

October 3, 2026

Title A Unified and Longitudinally Aware Framework for ICD-Based Comorbidity Assessment

Version 0.10.0

Description Provides comorbidity classification algorithms such as the Pediatric Complex Chronic Conditions (PCCC), Charlson, and Elixhauser indices, supports longitudinal comorbidity flagging across encounters, and includes utilities for working with medical coding schemas such as the International Classification of Diseases (ICD).

Depends R (>= 3.5.0)

License BSD_3_clause + file LICENSE

Language en-US

Encoding UTF-8

URL <http://www.peteredewitt.com/medicalcoder/>,
<https://github.com/dewittpe/medicalcoder/>

BugReports <https://github.com/dewittpe/medicalcoder/issues>

LazyData true

Suggests data.table, dplyr, kableExtra, knitr, R.utils, rmarkdown, tibble, tidyr

VignetteBuilder knitr, rmarkdown

Config/Needs/website pkgdown, comorbidity, multimorbidity, dplyr, tidyr, tibble, DBI, RSQLite, pccc

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Peter DeWitt [aut, cre, cov] (ORCID:
<<https://orcid.org/0000-0002-6391-0795>>),
Tell Bennett [ctb] (ORCID: <<https://orcid.org/0000-0003-1483-4236>>),
Seth Russell [ctb] (ORCID: <<https://orcid.org/0000-0002-2436-1367>>),
Meg Rebull [ctb] (ORCID: <<https://orcid.org/0000-0003-0334-4223>>),
Vincent Rubinetti [cov] (ORCID:
<<https://orcid.org/0000-0002-4655-3773>>)

Maintainer Peter DeWitt <peter.dewitt@cuanschutz.edu>
Repository CRAN
Date/Publication 2026-10-03 19:20:02 UTC

Contents

comorbidities	2
get_charlson_codes	8
get_charlson_index_scores	9
get_elixhauser_codes	10
get_elixhauser_index_scores	11
get_elixhauser_poa	12
get_icd_codes	13
get_pccc_codes	15
get_pccc_conditions	16
icd_compact_to_full	17
is_icd	18
lookup_icd_codes	20
mdcr	22
mdcr_longitudinal	23
summary.medicalcoder_comorbidities	23
summary.medicalcoder_comorbidities_with_subconditions	24

Index	26
--------------	-----------

comorbidities	<i>Comorbidities</i>
---------------	----------------------

Description

Apply established comorbidity algorithms to ICD-coded data. Supported methods include several variants of the Charlson comorbidity system, Elixhauser, and the Pediatric Complex Chronic Conditions (PCCC).

Usage

```
comorbidities(  
  data,  
  icd.codes,  
  method,  
  id.vars = NULL,  
  icdv.var = NULL,  
  icdv = NULL,  
  dx.var = NULL,  
  dx = NULL,  
  poa.var = NULL,  
  poa = NULL,
```

```

age.var = NULL,
primarydx.var = NULL,
primarydx = NULL,
flag.method = c("current", "cumulative"),
full.codes = TRUE,
compact.codes = TRUE,
subconditions = FALSE,
mapping = c("precomputed", "regex")
)

```

Arguments

<code>data</code>	A data.frame in a "long" format. The input data.frame is expected to have one column of ICD codes (one code per row) with additional (optional) columns for patient/encounter ids, ICD version, diagnostic/procedure status, present-on-admission flags, primary diagnostic flags, or age.
<code>icd.codes</code>	Character scalar naming the column in data that contains ICD codes (character strings). Codes may be provided in full form (with decimal points, e.g., C84.2), compact form (dots omitted, e.g., C842), or any mix of the two. Matching against lookup tables is governed by <code>icdv.var/icdv</code> , <code>dx.var/dx</code> , and the <code>full.codes / compact.codes</code> flags.
<code>method</code>	Character string indicating the comorbidity algorithm to apply to data.
<code>id.vars</code>	Optional character vector of column names. When missing, the entire input data is treated as a single encounter from a single patient. If you want to set <code>flag.method = "cumulative"</code> then <code>length(id.vars) >= 2</code> is expected. The last element should be the encounter order. It must not contain missing values, must not be a factor, and must be numeric, character, Date, or POSIXt. Character encounter order columns are allowed with a warning because they are sorted lexicographically.
<code>icdv.var</code>	Character scalar naming the column in data that indicates the ICD version. If present it must be numeric. Rows with values other than 9L or 10L will not be used to map ICD codes to comorbidities. <code>icdv.var</code> takes precedence over <code>icdv</code> if both are provided.
<code>icdv</code>	An integer value of 9L or 10L indicating that all <code>data[[icd.codes]]</code> are ICD version 9 or 10, respectively. Ignored (with a warning) if <code>icdv.var</code> is provided.
<code>dx.var</code>	Character scalar naming the column in data that indicates diagnostic (1L) vs procedural (0L) codes. If present it must be numeric. Rows with values other than 0L or 1L will not be used to map ICD codes to comorbidities. <code>dx.var</code> takes precedence over <code>dx</code> if both are provided.
<code>dx</code>	An integer indicating that all <code>data[[icd.codes]]</code> are diagnostic (1L) or procedure (0L) codes. Ignored (with a warning) if <code>dx.var</code> is provided.
<code>poa.var</code>	Character scalar naming the column with present-on-admission flags: integer 1L (present), 0L (not present), or NA. For AHRQ SAS-compatible present-on-admission indicators, convert "Y" and "W" to 1L, convert "N" and "U" to 0L, and convert blank or missing values to NA_integer_ before calling <code>comorbidities()</code> .

	PCCC and Charlson will only flag conditions when the code is present-on-admission. Elixhauser has a mix of conditions; some require present-on-admission while others do not. <code>poa.var</code> takes precedence over <code>poa</code> if both are provided.
<code>poa</code>	Integer scalar 0L or 1L. Use when all <code>icd.codes</code> share the same present-on-admission status. Ignored with a warning if <code>poa</code> and <code>poa.var</code> are both provided.
<code>age.var</code>	Character scalar naming the column in data that contains patient age in years. Only applicable to Charlson comorbidities.
<code>primarydx.var</code>	Character scalar naming the column in data that indicates whether <code>data[[icd.codes]]</code> are primary diagnostic codes (1L) or not (0L). Primary diagnosis is used only for Elixhauser and Charlson comorbidities and is ignored when the method is a PCCC variant. <code>primarydx.var</code> takes precedence over <code>primarydx</code> if both are provided.
<code>primarydx</code>	An integer value of 0L or 1L. If 0L, treat all codes as non-primary diagnoses; if 1L, treat all codes as primary diagnoses. Ignored, with a warning, if <code>primarydx.var</code> is provided.
<code>flag.method</code>	When <code>flag.method = "current"</code> (default) only codes associated with the current <code>id.vars</code> are considered when flagging comorbidities. The <code>flag.method = "cumulative"</code> option also considers prior encounters when flagging comorbidities. See Details .
<code>full.codes, compact.codes</code>	Logical; when TRUE compare <code>data[[icd.codes]]</code> against full and/or compact ICD codes in the method's lookup tables. Full ICD codes include a decimal point (when applicable) and compact codes omit the decimal point. For example: B95.0 is the full ICD-10-CM diagnostic code for "Streptococcus, group A, as the cause of disease classified elsewhere," whereas B950 is the associated compact code.
<code>subconditions</code>	Logical scalar; when TRUE, report both conditions and subconditions (PCCC only).
<code>mapping</code>	Character string specifying how <code>data[[icd.codes]]</code> should be mapped to comorbidity conditions. <code>mapping = "precomputed"</code> uses the precomputed ICD code-condition links included with <code>medicalcoder</code> and is the default. <code>mapping = "regex"</code> applies the method's regular expressions directly to the input ICD codes. See Details .

Details

When `flag.method = "current"`, only codes from the index encounter contribute to flags. The `flag.method = "cumulative"` option lets prior encounters for the same `id.vars` combination contribute to condition flags. For the cumulative method to work, `id.vars` needs to be a character vector of length 2 or more. The last element is treated as the encounter identifier and must be sortable. For example, say you have data with a hospital, patient, and encounter id. The `id.vars` could be one of two entries: `c("hospital", "patient", "encounter")` or `c("patient", "hospital", "encounter")`. In both cases the return will be the same because the encounter identifier is unchanged regardless of whether hospital or patient is listed first.

It is critically important that the `data[[tail(id.vars, 1)]]` variable can be sorted. Just because your data is sorted in temporal order does not mean that the results will be correct if the `tail(id.vars, 1)` is not in the same order as the data. For example, say you had the following:

patid	enc_id	date
P1	10823090	Aug 2023
P1	10725138	Jul 2025

`id.vars = c("patid", "enc_id")` will give the wrong result as `enc_id 10725138` would be sorted to come before `enc_id 10823090`. `id.vars = c("patid", "date")` would be sufficient input, assuming that date has been correctly stored. Adding a column `enc_seq`, e.g.,

patid	enc_id	date	enc_seq
P1	10823090	Aug 2023	1
P1	10725138	Jul 2025	2

and calling `comorbidities()` with `id.vars = c("patid", "enc_seq")` will have better performance than using the date and will clear up any possible issues with non-sequential encounter ids from the source data.

For `flag.method = "cumulative"`, the encounter order column must not contain missing values, must not be a factor, and must be numeric, character, Date, or POSIXt. Character encounter order columns are allowed, but they are sorted lexicographically; use an integer sequence, Date, or POSIXt column when possible.

Cumulative flagging + POA defaults:

When `flag.method = "cumulative"` and neither `poa` nor `poa.var` is supplied, the first encounter for a condition is treated as `poa = 0L`. Subsequent encounters for that condition are flagged as `poa = 1L`.

When `flag.method = "current"` and neither `poa` nor `poa.var` is supplied, then all codes will be considered present-on-admission. If `poa` was assumed to be 0, then in this case the only conditions that could be flagged are the Elixhauser conditions which are `poa-exempt`.

The mapping option controls how ICD codes are mapped to conditions. The default, `mapping = "precomputed"`, uses a precomputed table that links valid ICD codes to comorbidity conditions. Those links are built from the ICD code sources included with `medicalcoder`: the United States Centers for Disease Control and Prevention (CDC), the Centers for Medicare and Medicaid Services (CMS), the World Health Organization (WHO), the Independent Health and Aged Care Pricing Authority (IHACPA) ICD-10 Australian Modification (ICD-10-AM) data, and Socialstyrelsen ICD-10-SE data.

`mapping = "precomputed"` is generally fastest and is the behavior used by `medicalcoder` before the mapping argument was added. `mapping = "regex"` applies the method's regular expressions directly to the input ICD codes. Regex mapping is currently implemented for Charlson methods and is useful when codes come from an ICD modification that may not be completely covered by the precomputed code-condition links, or when auditing a method.

Value

The return object will be slightly different depending on the value of `method` and `subconditions`.

- When `subconditions = FALSE`, a `medicalcoder_comorbidities` object (a `data.frame` with attributes) is returned. Column(s) for `id.vars`, if defined in the function call. For all methods there will be the following columns:

- num_cmrb a count of comorbidities/conditions flagged
- cmrb_flag a 0L/1L integer indicator for at least one comorbidity/condition.

Additional columns:

- PCCC methods:
 - * For method = "pccc_v2.0" and method = "pccc_v2.1", there is one indicator column per condition.
 - * For method = "pccc_v3.0" and method = "pccc_v3.1", there are four columns per condition:
 - <condition>_dxpr_or_tech: the condition was flagged due to the presence of either a diagnostic or procedure code, or was flagged due to the presence of a technology dependence code along with at least one comorbidity being flagged by a diagnostic or procedure code.
 - <condition>_dxpr_only: the condition was flagged due to the presence of a non-technology-dependent diagnostic or procedure code only.
 - <condition>_tech_only: the condition was flagged due to the presence of a technology-dependent code only and at least one other comorbidity was flagged by a non-technology-dependent code.
 - <condition>_dxpr_and_tech: The patient had both diagnostic or procedure codes and a technology dependence code for the condition.
- For Charlson variants, indicator columns are returned for the relevant conditions, cci (Charlson Comorbidity Index), and age_score.
- For Elixhauser variants, indicator columns are returned for all relevant comorbidities, mortality, and readmission indices.
- When subconditions = TRUE and the method is a PCCC variant, a list of length two is returned: the first element contains condition indicators; the second element is a named list of data.frames with indicators for subconditions within each condition.

References

- Pediatric Complex Chronic Conditions:
 - Feudtner, C., Feinstein, J.A., Zhong, W. et al. Pediatric complex chronic conditions classification system version 2: updated for ICD-10 and complex medical technology dependence and transplantation. BMC Pediatr 14, 199 (2014). <https://doi.org/10.1186/1471-2431-14-199>
 - Feinstein JA, Hall M, Davidson A, Feudtner C. Pediatric Complex Chronic Condition System Version 3. JAMA Netw Open. 2024;7(7):e2420579. <https://doi.org/10.1001/jamanetworkopen.2024.20579>
- Charlson Comorbidities:
 - Mary E. Charlson, Peter Pompei, Kathy L. Ales, C.Ronald MacKenzie, A new method of classifying prognostic comorbidity in longitudinal studies: Development and validation, Journal of Chronic Diseases, Volume 40, Issue 5, 1987, Pages 373-383, ISSN 0021-9681, [https://doi.org/10.1016/0021-9681\(87\)90171-8](https://doi.org/10.1016/0021-9681(87)90171-8).
 - Deyo RA, Cherkin DC, Ciol MA. Adapting a clinical comorbidity index for use with ICD-9-CM administrative databases. J Clin Epidemiol. 1992 Jun;45(6):613-9. [https://doi.org/10.1016/0895-4356\(92\)90133-8](https://doi.org/10.1016/0895-4356(92)90133-8). PMID: 1607900.

- Sundararajan V, Henderson T, Perry C, Muggivan A, Quan H, Ghali WA. New ICD-10 version of the Charlson comorbidity index predicted in-hospital mortality. *J Clin Epidemiol.* 2004 Dec;57(12):1288-94. <https://doi.org/10.1016/j.jclinepi.2004.03.012>. PMID: 15617955.
- Quan H, Sundararajan V, Halfon P, Fong A, Burnand B, Luthi JC, Saunders LD, Beck CA, Feasby TE, Ghali WA. Coding algorithms for defining comorbidities in ICD-9-CM and ICD-10 administrative data. *Med Care.* 2005 Nov;43(11):1130-9. <https://doi.org/10.1097/01.mlr.0000182534.1983.1b>. PMID: 16224307.
- Quan H, Li B, Couris CM, Fushimi K, Graham P, Hider P, Januel JM, Sundararajan V. Updating and validating the Charlson comorbidity index and score for risk adjustment in hospital discharge abstracts using data from 6 countries. *Am J Epidemiol.* 2011 Mar 15;173(6):676-82. <https://doi.org/10.1093/aje/kwq433>. Epub 2011 Feb 17. PMID: 21330339.
- Glasheen WP, Cordier T, Gumpina R, Haugh G, Davis J, Renda A. Charlson Comorbidity Index: ICD-9 Update and ICD-10 Translation. *Am Health Drug Benefits.* 2019 Jun-Jul;12(4):188-197. PMID: 31428236; PMCID: PMC6684052.
- Ludvigsson JF, Appelros P, Askling J, et al. Adaptation of the Charlson Comorbidity Index for Register-Based Research in Sweden. *Clin Epidemiol.* 2021;13:21-41. <https://doi.org/10.2147/CLEP.S282475>.
- Ludvigsson JF, Appelros P, Askling J, et al. Adaptation of the Charlson Comorbidity Index for Register-Based Research in Sweden [Corrigendum]. *Clin Epidemiol.* 2023;15:753-754. <https://doi.org/10.2147/CLEP.S420607>.
- Elixhauser Comorbidities:
 - Agency for Healthcare Research and Quality (AHRQ). Elixhauser Comorbidity Software Refined for ICD-10-CM Diagnoses, v2026.1 [Internet]. 2026. Available from: https://www.hcup-us.ahrq.gov/toolssoftware/comorbidityicd10/comorbidity_icd10.jsp

See Also

- `vignettes(topic = "comorbidities", package = "medicalcoder")`
- `vignettes(topic = "pccc", package = "medicalcoder")`
- `vignettes(topic = "charlson", package = "medicalcoder")`
- `vignettes(topic = "elixhauser", package = "medicalcoder")`

Examples

```
pccc_v3.1_results <-
  comorbidities(data = mdcr,
    icd.codes = "code",
    id.vars = "patid",
    dx.var = "dx",
    method = "pccc_v3.1",
    flag.method = 'current',
    poa = 1L)
summary(pccc_v3.1_results)

pccc_v3.1_subcondition_results <-
  comorbidities(data = mdcr,
```

```

        icd.codes = "code",
        id.vars = "patid",
        dx.var = "dx",
        method = "pccc_v3.1",
        flag.method = 'current',
        poa = 1L,
        subconditions = TRUE)
summary(pccc_v3.1_subcondition_results)

charlson_results <-
  comorbidities(data = mdcr,
    icd.codes = "code",
    id.vars = "patid",
    dx.var = "dx",
    method = "charlson_quan2011",
    flag.method = 'current',
    poa = 1L)
summary(charlson_results)

elixhauser_results <-
  comorbidities(data = mdcr,
    icd.codes = "code",
    id.vars = "patid",
    dx.var = "dx",
    method = "elixhauser_ahrq2025",
    primarydx = 1L,
    flag.method = 'current',
    poa = 1L)
summary(elixhauser_results)

```

get_charlson_codes	<i>Get Charlson Codes</i>
--------------------	---------------------------

Description

Retrieve a copy of internal lookup tables for the ICD codes used in assessing Charlson comorbidities. The lookup includes indicator columns for each implemented Charlson variant.

Usage

```
get_charlson_codes()
```

Value

A data.frame with the following columns:

- `icdv`: Integer vector indicating if the code is from ICD-9 or ICD-10.
- `dx`: Integer vector. 1L if the code is diagnostic (ICD-9-CM, ICD-10-CM, ICD-10-AM, ICD-10-SE, WHO, CDC Mortality), or 0L if the code is procedural (ICD-9-PCS, ICD-10-PCS).

- `full_code`: Character vector with the ICD code and any relevant decimal point
- `code`: Character vector with the compact ICD code
- `condition`: Character vector of the conditions
- `charlson_<variant>`: Integer vector indicating if the code is part of the `<variant>` of the Charlson comorbidities.

See Also

- [get_charlson_index_scores\(\)](#) for a lookup table of comorbidity index scores.
- [get_icd_codes\(\)](#) for the lookup table of all ICD codes.
- [get_pccc_codes\(\)](#) for the lookup table of ICD codes used for the PCCC.
- [get_elixhauser_codes\(\)](#) for the lookup table of ICD codes used for the Elixhauser comorbidities.
- [comorbidities\(\)](#) for applying comorbidity algorithms to a dataset.

Examples

```
head(get_charlson_codes())
str(get_charlson_codes())
```

```
get_charlson_index_scores
```

Get Charlson Index Scores

Description

Retrieve a copy of internal lookup tables of index scores used in assessing Charlson comorbidities. The lookup includes score columns for each implemented Charlson variant.

Usage

```
get_charlson_index_scores()
```

Value

A data.frame with the following columns:

- `condition`: Character vector of the conditions
- `index`: Character vector indicating whether the score is for the mortality or readmission index.
- `charlson_<variant>`: The index scores for the variant.

See Also

- [get_charlson_codes\(\)](#) for a lookup table of the ICD codes mapping to the Charlson comorbidities.
- [comorbidities\(\)](#) for applying comorbidity algorithms to a dataset.

Examples

```
head(get_charlson_index_scores())
str(get_charlson_index_scores())
```

get_elixhauser_codes *Get Elixhauser Codes*

Description

Retrieve a copy of internal lookup tables for the ICD codes used in assessing Elixhauser comorbidities.

Usage

```
get_elixhauser_codes()
```

Details

The method previously named `elixhauser_elixhauser1988` is named `elixhauser_elixhauser1998` as of v0.10.0, correcting the publication year. Accordingly, the returned method indicator column is now `elixhauser_elixhauser1998`. Code that refers to the old column name must be updated; the old column is not included as an alias. Calls to `comorbidities(method = "elixhauser_elixhauser1988")` remain temporarily supported with a deprecation warning.

Value

A data.frame with the following columns:

- `icdv`: Integer vector indicating if the code is from ICD-9 or ICD-10.
- `dx`: Integer vector. 1L if the code is diagnostic (ICD-9-CM, ICD-10-CM, ICD-10-AM, ICD-10-SE, WHO, CDC Mortality), or 0L if the code is procedural (ICD-9-PCS, ICD-10-PCS).
- `full_code`: Character vector with the ICD code and any relevant decimal point
- `code`: Character vector with the compact ICD code omitting any relevant decimal point
- `condition`: Character vector of the conditions
- `elixhauser_<variant>`: Integer vector indicating if the code is part of the <variant> of the Elixhauser comorbidities.

See Also

- [get_elixhauser_index_scores\(\)](#) for the lookup table of the condition by condition scores for mortality and readmission indices.
- [get_elixhauser_poa\(\)](#) for the lookup table of the conditions which do and do not require associated ICD codes to be present-on-admission to flag the comorbidity.
- [get_icd_codes\(\)](#) for the lookup table of all ICD codes.

- [get_pccc_codes\(\)](#) for the lookup table of ICD codes used for the PCCC.
- [get_charlson_codes\(\)](#) for the lookup table of ICD codes used for the Charlson comorbidities.
- [comorbidities\(\)](#) for applying comorbidity algorithms to a dataset.

Examples

```
head(get_elixhauser_codes())  
str(get_elixhauser_codes())
```

```
get_elixhauser_index_scores  
      Get Elixhauser Index Scores
```

Description

Functions to get a copy of internal lookup tables for the ICD codes and index scores used in assessing Elixhauser comorbidities.

Usage

```
get_elixhauser_index_scores()
```

Value

A data.frame with the following columns:

- condition: Character vector of the conditions
- index: Character vector indicating whether the score is for the mortality or readmission index.
- elixhauser_<variant>: Integer vector of the scores.

See Also

- [get_elixhauser_codes\(\)](#) for the lookup table of ICD codes mapping to the Elixhauser comorbidities.
- [get_elixhauser_poa\(\)](#) for the lookup table of the conditions which do and do not require associated ICD codes to be present-on-admission to flag the comorbidity.
- [comorbidities\(\)](#) for applying comorbidity algorithms to a dataset.

Examples

```
head(get_elixhauser_index_scores())  
str(get_elixhauser_index_scores())
```

get_elixhauser_poa	<i>Get Elixhauser Present-on-Admission Requirements</i>
--------------------	---

Description

Retrieve a copy of internal lookup table with details on which Elixhauser comorbidities do and do not require the associated ICD codes to be present-on-admission to be flagged. This is a condition-level rule table; code-level POA exemptions are a separate part of the Elixhauser mapping.

Usage

```
get_elixhauser_poa()
```

Details

For the AHRQ ICD-10-CM methods, `poa_required = 1L` means a condition is flagged when a mapped diagnosis is POA or its code is POA exempt. `poa_required = 0L` means the condition is flagged regardless of the diagnosis POA value. The `elixhauser_ahrqYYYY` columns identify which annual AHRQ release uses each condition/rule row. The combined `elixhauser_ahrq_icd10` column marks rows used by any included annual release; it is a union, not a separate annual AHRQ release.

Value

A data.frame with the following columns:

- `condition`: Character vector naming the comorbidity condition. A condition can have more than one row if its POA requirement changes by method or release.
- `poa_required`: Integer rule flag: 1L means POA is required, subject to code-level exemptions; 0L means the condition is POA neutral.
- `elixhauser_<variant>`: Integer membership flag indicating whether the row's condition and POA rule apply to that variant.

See Also

- [get_elixhauser_index_scores\(\)](#) for the lookup table of the condition by condition scores for mortality and readmission indices.
- [get_elixhauser_codes\(\)](#) for the lookup table of ICD codes mapping to the Elixhauser comorbidities.
- [comorbidities\(\)](#) for applying comorbidity algorithms to a dataset.

Examples

```
head(get_elixhauser_poa())
str(get_elixhauser_poa())
```

get_icd_codes

*Get ICD Codes***Description**

Retrieve a copy of the internal lookup table for all known ICD codes.

Usage

```
get_icd_codes(with.descriptions = FALSE, with.hierarchy = FALSE)
```

Arguments

`with.descriptions`

Logical scalar, if TRUE include the description of the codes.

`with.hierarchy` Logical scalar, if TRUE include the ICD hierarchy.

Details**Sources:**

There are five sources of ICD codes.

- `cms`: Codes from the ICD-9-CM, ICD-9-PCS, ICD-10-CM, and ICD-10-PCS standards.
- `who`: Codes from the World Health Organization.
- `cdc`: For ICD-10, CDC mortality codes, not CDC-hosted ICD-10-CM files. ICD-10-CM uses the canonical `cms` source. CDC ICD-9 extracts are also retained under `cdc`.
- `ihacpa`: ICD-10-AM codes from the Independent Health and Aged Care Pricing Authority.
- `socialstyrelsen`: ICD-10-SE codes from Sweden's National Board of Health and Welfare.

Fiscal, Financial, and Calendar Years:

When reporting years there is a mix of fiscal, financial, and calendar years.

Fiscal years are the United States Federal Government fiscal years, running from October 1 to September 30. For example, fiscal year 2013 started October 1, 2012 and ended on September 30, 2013.

Financial years are the Australian financial years used for IHACPA data, running from July 1 to June 30.

Calendar years run January 1 to December 31.

Within the ICD data there are columns `known_start`, `known_end`, `assignable_start`, `assignable_end`, `desc_start` and `desc_end`. For ICD codes with `src == "cms"`, these are fiscal years. For codes with `src == "ihacpa"`, these are financial years. For codes with `src == "cdc"`, `src == "socialstyrelsen"`, or `src == "who"` these are calendar years.

`known_start` is the first fiscal, financial, or calendar year (depending on source) that the medicalcoder package has definitive source data for. ICD-9-CM started in the United States in fiscal year 1980. The CDC extracts included in medicalcoder span fiscal years 1997–2012; the CMS ICD-9-CM/PCS extracts start in fiscal year 2006 and run through fiscal year 2015. As such 1997 is the earliest "known start" for ICD-9 within medicalcoder.

known_end is the last fiscal, financial, or calendar year (depending on source) for which we have definitive source data. For ICD-9-CM and ICD-9-PCS, CMS provides data through fiscal year 2015, while the CDC extracts stop at fiscal year 2012. For ICD-10-CM and ICD-10-PCS, which are active, it is just the last year of known data. ICD-10 from the WHO ends in 2021.

CMS annual tables represent the selected release within each fiscal year, including April updates where incorporated. Integer validity years do not distinguish October and April effective dates within the same fiscal year.

Header and Assignable Codes:

"Assignable" indicates that the code is the most granular for the source. Ideally codes are reported with the greatest level of detail but that is not always the case. Also, the greatest level of detail can differ between sources. Example: C86 is a header code for cms and who because codes C86.0, C86.1, C86.2, C86.3, C86.4, C86.5, and C86.6 all exist in both standards. No code with a fifth digit exists in the who so all these four digit codes are 'assignable.' In the cms standard, C86.0 was assignable through fiscal year 2024. In fiscal year 2025 codes C86.00 and C86.01 were added making C86.0 a header code and C86.00 and C86.01 assignable codes.

Value

a data.frame

The default return has the following columns:

- icdv: Integer vector indicating if the code is from ICD-9 or ICD-10
- dx: Integer vector. 1L if the code is diagnostic (ICD-9-CM, ICD-10-CM, ICD-10-AM, ICD-10-SE, WHO, CDC Mortality), or 0L if the code is procedural (ICD-9-PCS, ICD-10-PCS)
- full_code: Character vector with the ICD code and any relevant decimal point
- code: Character vector with the compact ICD code omitting any relevant decimal point
- src: Character vector reporting the source of the information. See Details.
- known_start: Integer vector reporting the first known year of use. See Details.
- known_end: Integer vector reporting the last known year of use. See Details.
- assignable_start: Integer vector reporting the first known year the code was assignable. See Details.
- assignable_end: Integer vector reporting the last known year the code was assignable. See Details.

When with.descriptions = TRUE there are the following additional columns:

- desc: Character vector of descriptions. For cms codes descriptions from CMS are used preferentially over CDC.
- desc_start: Integer vector of the first year the description was used.
- desc_end: Integer vector of the last year the description was used.

When with.hierarchy = TRUE there are the following additional columns:

- chapter
- subchapter

- category
- subcategory
- subclassification
- subsubclassification
- extension

See Also

`is_icd()`, `lookup_icd_codes()`, `vignette(topic = "icd", package = "medicalcoder")`

Examples

```
icd_codes <- get_icd_codes()
str(icd_codes)

# Explore the change in the assignable year for C86 code between CMS and
# WHO
subset(get_icd_codes(), grepl("^C86$", full_code))
subset(get_icd_codes(), grepl("^C86\\.\\.\\d$", full_code))
subset(get_icd_codes(), grepl("^C86\\.\\.0(\\d|$)", full_code))

is_icd("C86", headerok = FALSE) # FALSE
is_icd("C86", headerok = TRUE)  # TRUE
is_icd("C86", headerok = TRUE, src = "cdc") # Not a CDC mortality code

lookup_icd_codes("^C86\\.\\.0\\.\\d*", regex = TRUE)
```

get_pccc_codes

Pediatric Complex Chronic Conditions ICD Codes

Description

Retrieve a copy of internal lookup tables for the ICD codes mapping to the Pediatric Complex Chronic Conditions (PCCC) conditions and subconditions by variant.

Usage

```
get_pccc_codes()
```

Value

a `data.frame` with the following columns

- `icdv`: Integer vector indicating if the code is from ICD-9 or ICD-10.
- `dx`: Integer vector. 1L if the code is diagnostic (ICD-9-CM, ICD-10-CM, ICD-10-AM, ICD-10-SE, WHO, CDC Mortality), or 0L if the code is procedural (ICD-9-PCS, ICD-10-PCS).
- `full_code`: Character vector with the ICD code and any relevant decimal point.

- `code`: Character vector with the compact ICD code omitting any relevant decimal point.
- `condition`: Character vector of the conditions.
- `subcondition`: Character vector of the subconditions.
- `transplant_flag`: Integer vector indicating if the code is associated with a transplant.
- `tech_dep_flag`: Integer vector indicating if the code is associated with technology dependence.
- `pccc_<variant>`: Integer vector indicating if the code is part of the v2.0, v2.1, v3.0, or v3.1 variant.

See Also

- [get_pccc_conditions\(\)](#) for a reference of the PCCC conditions and subconditions.
- [get_icd_codes\(\)](#) for the lookup table of all ICD codes.
- [comorbidities\(\)](#) for applying comorbidity algorithms to a dataset.

Examples

```
head(get_pccc_codes())
str(get_pccc_codes())
```

get_pccc_conditions	<i>Pediatric Complex Chronic Condition and Subconditions</i>
---------------------	--

Description

Retrieve a copy of internal lookup tables for the syntactically valid and human readable labels of the Pediatric Complex Chronic Conditions (PCCC) conditions and subconditions.

Usage

```
get_pccc_conditions()
```

Value

A data.frame with the following character columns:

- `condition`: Syntactically valid name for the condition
- `subcondition`: Syntactically valid name for the subcondition
- `condition_label`: Human-readable label for the condition
- `subcondition_label`: Human-readable label for the subcondition

See Also

- [get_pccc_codes\(\)](#) for the lookup table of ICD codes used for the PCCC.
- [comorbidities\(\)](#) for applying comorbidity algorithms to a dataset.

Examples

```
get_pccc_conditions()
```

icd_compact_to_full	<i>Convert ICD Compact Codes to Full Codes</i>
---------------------	--

Description

Take an assumed ICD compact code string and convert to a full code based on the ICD version (9L or 10L) and type (diagnostic or procedure). This method only formats strings and does not validate the code(s).

Usage

```
icd_compact_to_full(x, icdv, dx)
```

Arguments

x	Character vector
icdv	Integer vector of allowed ICD versions. Use 9L and/or 10L. Defaults to both.
dx	Integer vector indicating allowed code type(s): 1L for diagnostic (ICD-9-CM, ICD-10-CM, ICD-10-AM, ICD-10-SE, CDC mortality, WHO), 0L for procedural (ICD-9-PCS, ICD-10-PCS). Defaults to both.

Value

A character vector the same length as x.

See Also

- [get_icd_codes\(\)](#) to retrieve the internal lookup table of ICD codes.
- [lookup_icd_codes\(\)](#) for retrieving details on a specific set of ICD codes.
- [is_icd\(\)](#) to test if a string is a known ICD code.

Other ICD tools: [is_icd\(\)](#), [lookup_icd_codes\(\)](#)

is_icd	<i>Is ICD</i>
--------	---------------

Description

Answer the question "is the character string x a valid ICD code?" ICD codes should be character vectors. `is_icd` will assess for both "full codes" (decimal point present when appropriate) and "compact codes" (decimal point omitted).

ICD-10 code "C00" is a header code because the four-character codes C00.0, C00.1, C00.2, C00.3, C00.4, C00.5, C00.6, C00.7, C00.8, and C00.9 exist. Those four-character codes are assignable (as of 2025) because no five-character descendants (e.g., C00.40) exist.

When the source is the World Health Organization (WHO), CDC Mortality, or Socialstyrelsen, years refer to calendar years. CMS sources use the U.S. federal fiscal year, which starts on October 1 (e.g., fiscal year 2024 runs 2023-10-01 to 2024-09-30). IHACPA sources use the Australian financial year, which starts on July 1 and ends on June 30.

Usage

```
is_icd(  
  x,  
  icdv = c(9L, 10L),  
  dx = c(1L, 0L),  
  src = c("cdc", "cms", "ihacpa", "socialstyrelsen", "who"),  
  year,  
  headerok = FALSE,  
  ever.assignable = missing(year),  
  warn.ambiguous = TRUE,  
  full.codes = TRUE,  
  compact.codes = TRUE  
)
```

Arguments

x	Character vector of ICD codes (full or compact form).
icdv	Integer vector of allowed ICD versions. Use 9L and/or 10L. Defaults to both.
dx	Integer vector indicating allowed code type(s): 1L for diagnostic (ICD-9-CM, ICD-10-CM, ICD-10-AM, ICD-10-SE, CDC mortality, WHO), 0L for procedural (ICD-9-PCS, ICD-10-PCS). Defaults to both.
src	Character vector of code sources. One or more of "cdc", "cms", "ihacpa", "socialstyrelsen", and "who". Defaults to all. CDC and CMS are from the United States (ICD-9/10-CM and ICD-9/10-PCS), IHACPA from Australia (ICD-10-AM), Socialstyrelsen from Sweden (ICD-10-SE), and the World Health Organization (ICD-10).
year	Numeric scalar. Calendar, fiscal, or financial year to reference. Default is the most current year available per source. For ICD-9, CMS data run through fiscal

	year 2015 and CDC extracts through 2012; ICD-10 sources are updated annually. Calendar year for WHO, CDC mortality, and Socialstyrelsen. U.S. federal fiscal year for CMS. Australian financial year for IHACPA.
headerok	Logical scalar. If FALSE (default), only assignable codes are considered valid; if TRUE, header codes are also accepted.
ever.assignable	Logical scalar. If TRUE then ignore year and return TRUE if the x was ever an assignable code.
warn.ambiguous	Logical scalar. If TRUE (default), warn when a code matches more than one ICD version and/or type (e.g., both CM and PCS).
full.codes	Logical scalar. If TRUE (default), match codes that include the decimal point where applicable.
compact.codes	Logical scalar. If TRUE (default), match codes without the decimal point.

Details

Similarly for ICD-9-CM: "055" is a header for measles; 055.0, 055.1, 055.2, 055.8, and 055.9 are assignable. Codes 055.3–055.6 do not exist. Code 055.7 is a header because 055.71 and 055.72 exist.

Some codes change status across years. For example, ICD-9-CM 516.3 was assignable in fiscal years 1997–2011 for the CDC extracts (2006–2011 for CMS) and became a header in 2012–2015.

Value

A logical vector the same length as x.

See Also

- `get_icd_codes()` to retrieve the internal lookup table of ICD codes.
- `lookup_icd_codes()` for retrieving details on a specific set of ICD codes.
- `icd_compact_to_full()` converts a string from a compact format to the full format based on ICD version and type (diagnostic or procedure).

Other ICD tools: `icd_compact_to_full()`, `lookup_icd_codes()`

Examples

```
#####
# Some ICD-9 diagnostic codes
x <- c("136.2", "718.60", "642.02")

is_icd(x, icdv = 9L, dx = 1L)
is_icd(x, icdv = 9L, dx = 0L)
is_icd(x, icdv = 10L, dx = 1L)
is_icd(x, icdv = 10L, dx = 0L)

is_icd(x, icdv = 9L, dx = 1L, headerok = TRUE)
is_icd(x, icdv = 9L, dx = 1L, year = 2006)
```

```
#####
# ICD code with, or without a dot. The ICD-9 diagnostic code 799.3 and ICD-9
# procedure code 79.93 both become 7993 when assessed against the ICD code look
# up tables. As such "7993" is a valid ICD-9 diagnostic and procedure code,
# whereas 799.3 is only a valid dx code, and 79.93 is only a valid pr code.
# Further, codes such as ".7993", "7.993", "7993.", are all non-valid codes.

x <- c("7993", ".7993", "7.993", "79.93", "799.3", "7993.")
data.frame(
  x,
  dx = is_icd(x, icdv = 9L, dx = 1L),
  pr = is_icd(x, icdv = 9L, dx = 0L)
)

#####
# example of a ICD-9 code that was assignable, but became a header when
# more descriptive codes were introduced: ICD-9 diagnostic code 516.3
lookup_icd_codes(paste0("516.3", c("", as.character(0:9))))

# ICD-9 code 516.3 was an assignable code through fiscal year 2011.
is_icd("516.3")

# If `year` is omitted, and `ever.assignable = FALSE` then the `year` is
# implied to be the max `known_end` year for ICD codes matched by `icdv`,
# `dx`, and `src`.
is_icd("516.3", ever.assignable = FALSE)

# when `year` is provided then `ever.assignable` is `FALSE` by default and
# the return is TRUE when 516.3 was assignable and FALSE otherwise.
is_icd("516.3", year = 2015)
is_icd("516.3", year = 2011)

# when year is a non-assignable year, but `ever.assignable = TRUE` the return
# will be TRUE. Useful if you know the data is retrospective and collected
# through fiscal year 2015.
is_icd("516.3", year = 2015, ever.assignable = TRUE)

#####
# Consider the string E010
# - This could be an ICD-9-CM full code
# - Could be an ICD-10-CM compact code
lookup_icd_codes("E010")
subset(get_icd_codes(with.descriptions = TRUE), grepl("^E010$", code))

is_icd("E010")
is_icd("E010", icdv = 9L) # FALSE because it is a header code and was never assignable
is_icd("E010", icdv = 9L, ever.assignable = TRUE) # FALSE
is_icd("E010", icdv = 9L, headerok = TRUE) # TRUE
```

Description

Functions for working with ICD codes.

ICD-10 code "C00" is a header code because the four-character codes C00.0, C00.1, C00.2, C00.3, C00.4, C00.5, C00.6, C00.7, C00.8, and C00.9 exist. Those four-character codes are assignable (as of 2025) because no five-character descendants (e.g., C00.40) exist.

When the source is the World Health Organization (WHO), CDC Mortality, or Socialstyrelsen, years refer to calendar years. CMS sources use the U.S. federal fiscal year, which starts on October 1 (e.g., fiscal year 2024 runs 2023-10-01 to 2024-09-30). IHACPA sources use the Australian financial year, which starts on July 1 and ends on June 30.

Usage

```
lookup_icd_codes(
  x,
  regex = FALSE,
  full.codes = TRUE,
  compact.codes = TRUE,
  ...
)
```

Arguments

<code>x</code>	Character vector of ICD codes (full or compact form). When <code>regex = TRUE</code> , <code>x</code> must contain at least one non-empty, non-missing string.
<code>regex</code>	Logical scalar. If <code>TRUE</code> , treat <code>x</code> as regular expressions; if <code>FALSE</code> , use exact matching.
<code>full.codes</code>	Logical scalar. If <code>TRUE</code> (default), match codes that include the decimal point where applicable.
<code>compact.codes</code>	Logical scalar. If <code>TRUE</code> (default), match codes without the decimal point.
<code>...</code>	Passed to <code>base::grep()</code> when <code>regex = TRUE</code>

Details

ICD codes should be character vectors. These tools work with either "full codes" (decimal point present when appropriate) or "compact codes" (decimal point omitted).

Similarly for ICD-9-CM: "055" is a header for measles; 055.0, 055.1, 055.2, 055.8, and 055.9 are assignable. Codes 055.3–055.6 do not exist. Code 055.7 is a header because 055.71 and 055.72 exist.

Some codes change status across years. For example, ICD-9-CM 516.3 was assignable in fiscal years 1997–2011 for the CDC extracts (2006–2011 for CMS) and became a header in 2012–2015.

Value

A data frame with one or more rows per input, including columns

- `match_type`: did the input match a full or compact code

- `icdv`: ICD version (9L or 10L)
- `dx`: diagnostic code (1L) or procedure code (0L)
- `full_code`: the full code string
- `code`: the compact code string
- `src`: the source CMS, CDC, WHO, IHACPA, or Socialstyrelsen
- year ranges (`known_*`, `assignable_*`).

See Also

- [`get\_icd\_codes\(\)`](#) to retrieve the internal lookup table of ICD codes.
- [`is\_icd\(\)`](#) to test if a string is a known ICD code.
- [`icd\_compact\_to\_full\(\)`](#) converts a string from a compact format to the full format based on ICD version and type (diagnostic or procedure).

Other ICD tools: [`icd\_compact\_to\_full\(\)`](#), [`is\_icd\(\)`](#)

mdcr

Synthetic Data

Description

Synthetic Data

Usage

mdcr

Format

mdcr is a `data.frame` with 4 columns. Each row is for one ICD code.

- `patid`: patient identifier, integer values
- `icdv`: ICD version; integer values, 9L or 10L
- `dx`: indicator column for ICD diagnostic (1L) or procedure (0L) codes
- `code`: ICD code; character values

See Also

Other datasets: [`mdcr\_longitudinal`](#)

mdcr_longitudinal	<i>Synthetic Longitudinal Data</i>
-------------------	------------------------------------

Description

Synthetic Longitudinal Data

Usage

```
mdcr_longitudinal
```

Format

mdcr_longitudinal is a `data.frame` with 4 columns. The codes are expected to be treated as diagnostic codes. Warning: there are a few ICD-9 codes which could match to procedure codes.

- patid: patient identifier, integer values
- date: date the diagnostic code was recorded
- icdv: ICD version 9L or 10L, integer valued
- code: ICD codes; character values

See Also

Other datasets: [mdcr](#)

summary.medicalcoder_comorbidities	<i>Summaries of Comorbidities</i>
------------------------------------	-----------------------------------

Description

Build summaries (counts and percentages) for each comorbidity and other summary statistics by method.

Usage

```
## S3 method for class 'medicalcoder_comorbidities'  
summary(object, ...)
```

Arguments

object	a <code>medicalcoder_comorbidities</code> object generated by calling comorbidities()
...	additional parameters, not currently used

Details

If a `medicalcoder_comorbidities` object has been modified so that it no longer has the structure required by `medicalcoder`'s summary methods, `summary` falls back to the next applicable summary method with a warning.

Value

Either a list or a `data.frame`.

Examples

```
pccc_v3.1_results <-
  comorbidities(data = mdcr,
    icd.codes = "code",
    id.vars = "patid",
    dx.var = "dx",
    method = "pccc_v3.1",
    flag.method = 'current',
    poa = 1L)
summary(pccc_v3.1_results)

charlson_results <-
  comorbidities(data = mdcr,
    icd.codes = "code",
    id.vars = "patid",
    dx.var = "dx",
    method = "charlson_quan2011",
    flag.method = 'current',
    poa = 1L)
summary(charlson_results)

elixhauser_results <-
  comorbidities(data = mdcr,
    icd.codes = "code",
    id.vars = "patid",
    dx.var = "dx",
    method = "elixhauser_ahrq2025",
    primarydx = 1L,
    flag.method = 'current',
    poa = 1L)
summary(elixhauser_results)
```

Description

Build summaries (counts and percentages) for each Pediatric Complex Chronic Condition (PCCC) condition and subcondition.

Usage

```
## S3 method for class 'medicalcoder_comorbidities_with_subconditions'  
summary(object, ...)
```

Arguments

object	a medicalcoder_comorbidities_with_subconditions object generated by calling comorbidities() with subconditions = TRUE. This is currently only applicable to PCCC.
...	additional parameters, not currently used

Value

a data.frame with five columns.

1. condition the primary condition
2. subcondition the subcondition(s) within the condition. There will be a row where subcondition is NA which is used to report the count and percent_of_cohort for the condition overall.
3. count the number of rows in object with the applicable condition and subcondition.
4. percent_of_cohort: a numeric value within [0, 100] for the percent of rows in object with the flagged condition and subcondition.
5. percent_of_those_with_condition: a numeric value within [0, 100] for the subset of rows in object with the primary condition and the flagged subcondition. Will be NA for the primary condition.

See Also

[comorbidities\(\)](#), [vignette\(topic = "pccc", package = "medicalcoder"\)](#)

Examples

```
pccc_v3.1_subcondition_results <-  
  comorbidities(data = mdc,  
                icd.codes = "code",  
                id.vars = "patid",  
                dx.var = "dx",  
                method = "pccc_v3.1",  
                flag.method = 'current',  
                poa = 1L,  
                subconditions = TRUE)  
summary(pccc_v3.1_subcondition_results)
```

Index

* ICD tools

icd_compact_to_full, [17](#)

is_icd, [18](#)

lookup_icd_codes, [20](#)

* datasets

mdcr, [22](#)

mdcr_longitudinal, [23](#)

* icd tools

get_icd_codes, [13](#)

base::grep(), [21](#)

comorbidities, [2](#)

comorbidities(), [9](#), [11](#), [12](#), [16](#), [23](#), [25](#)

get_charlson_codes, [8](#)

get_charlson_codes(), [9](#), [11](#)

get_charlson_index_scores, [9](#)

get_charlson_index_scores(), [9](#)

get_elixhauser_codes, [10](#)

get_elixhauser_codes(), [9](#), [11](#), [12](#)

get_elixhauser_index_scores, [11](#)

get_elixhauser_index_scores(), [10](#), [12](#)

get_elixhauser_poa, [12](#)

get_elixhauser_poa(), [10](#), [11](#)

get_icd_codes, [13](#)

get_icd_codes(), [9](#), [10](#), [16](#), [17](#), [19](#), [22](#)

get_pccc_codes, [15](#)

get_pccc_codes(), [9](#), [11](#), [16](#)

get_pccc_conditions, [16](#)

get_pccc_conditions(), [16](#)

icd_compact_to_full, [17](#)

icd_compact_to_full(), [19](#), [22](#)

is_icd, [18](#)

is_icd(), [15](#), [17](#), [22](#)

lookup_icd_codes, [20](#)

lookup_icd_codes(), [15](#), [17](#), [19](#)

mdcr, [22](#), [23](#)

mdcr_longitudinal, [22](#), [23](#)

summary.medicalcoder_comorbidities, [23](#)

summary.medicalcoder_comorbidities_with_subconditions,
[24](#)