

Package ‘minter’

October 1, 2026

Title Effect Sizes for Meta-Analysis of Interactions from Factorial Experiments

Version 0.2.0

Description Compute effect sizes and their sampling variances from factorial experimental designs. The package supports calculation of simple effects, overall effects, and interaction effects for use in factorial meta-analyses. See Gurevitch et al. (2000) <[doi:10.1086/303337](https://doi.org/10.1086/303337)>, Morris et al. (2007) <[doi:10.1890/06-0442](https://doi.org/10.1890/06-0442)>, Lajeunesse (2011) <[doi:10.1890/11-0423.1](https://doi.org/10.1890/11-0423.1)> and Macartney et al. (2022) <[doi:10.1016/j.neubiorev.2022.104554](https://doi.org/10.1016/j.neubiorev.2022.104554)>.

License MIT + file LICENSE

Encoding UTF-8

URL <https://fdecunta.github.io/minter/>

BugReports <https://github.com/fdecunta/minter/issues>

Depends R (>= 3.5)

LazyData true

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

Config/roxygen2/version 8.1.0

Config/Needs/website rmarkdown

NeedsCompilation no

Author Facundo Decunta [aut, cre] (ORCID:
<<https://orcid.org/0009-0004-5774-1085>>),
Shinichi Nakagawa [ctb],
Daniel Noble [ctb]

Maintainer Facundo Decunta <fdecunta@agro.uba.ar>

Repository CRAN

Date/Publication 2026-10-01 18:20:02 UTC

Contents

lnCVR_ind	2
lnCVR_inter	4
lnCVR_main	6
lnRR_ind	8
lnRR_inter	10
lnRR_main	12
lnVR_ind	14
lnVR_inter	16
lnVR_main	17
SMD_ind	19
SMD_inter	21
SMD_main	24
time_lnCVR	26
time_lnRR	28
time_lnVR	30
time_SMD	32
Index	35

lnCVR_ind	<i>Individual Effect: Log Coefficient Of Variation Ratio</i>
-----------	--

Description

Computes the Log of the Coefficient of Variation Ratio between Factor A and the Control treatment.

Usage

```
lnCVR_ind(  
  data,  
  col_names = c("yi", "vi"),  
  append = TRUE,  
  Ctrl_mean,  
  Ctrl_sd,  
  Ctrl_n,  
  A_mean,  
  A_sd,  
  A_n  
)
```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE

Ctrl_mean	Mean outcome from the Control treatment
Ctrl_sd	Standard deviation from the control treatment
Ctrl_n	Sample size from the control treatment
A_mean	Mean outcome from the treatment
A_sd	Standard deviation from the treatment
A_n	Sample size from the treatment

Details

$$\ln CVR_{ind} = \ln \left(\frac{CV_A}{CV_{Ctrl}} \right) + \frac{1}{2(n_A - 1)} - \frac{1}{2(n_{Ctrl} - 1)}$$

$$var(\ln CVR_{ind}) = \frac{sd_{Ctrl}^2}{n_{Ctrl} \bar{X}_{Ctrl}^2} + \frac{1}{2(n_{Ctrl} - 1)} + \frac{sd_A^2}{n_A \bar{X}_A^2} + \frac{1}{2(n_A - 1)}$$

This assumes no correlation between mean and variance (Nakagawa et al. 2015) and is computed as the sum of lnRR and lnVR variances.

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Nakagawa, S., Poulin, R., Mengersen, K., Reinhold, K., Engqvist, L., Lagisz, M., & Senior, A. M. (2015). Meta-analysis of variation: ecological and evolutionary applications and beyond. *Methods in Ecology and Evolution*, 6(2), 143-152.

Examples

```
data <- data.frame(
  study_id = 1:3,
  control_mean = c(8.5, 12.3, 6.8),
  control_sd = c(1.8, 2.9, 1.4),
  control_n = c(18, 24, 16),
  nutrient_mean = c(11.2, 16.7, 9.3),
  nutrient_sd = c(3.1, 4.8, 2.7),
  nutrient_n = c(19, 22, 17)
)

result <- lnCVR_ind(
  data = data,
```

```

Ctrl_mean = "control_mean", Ctrl_sd = "control_sd", Ctrl_n = "control_n",
A_mean = "nutrient_mean", A_sd = "nutrient_sd", A_n = "nutrient_n"
)

```

InCVR_inter

Interaction Effect: Log Coefficient of Variation Ratio

Description

Computes the interaction effect between Factors A and B in factorial experiments on the coefficient of variation ratio.

Usage

```

InCVR_inter(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  Ctrl_mean,
  Ctrl_sd,
  Ctrl_n,
  A_mean,
  A_sd,
  A_n,
  B_mean,
  B_sd,
  B_n,
  AB_mean,
  AB_sd,
  AB_n
)

```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
Ctrl_mean	Mean outcome from the Control treatment
Ctrl_sd	Standard deviation from the control treatment
Ctrl_n	Sample size from the control treatment
A_mean	Mean outcome from the treatment
A_sd	Standard deviation from the treatment
A_n	Sample size from the treatment

B_mean	Mean outcome from the B treatment
B_sd	Standard deviation from the B treatment
B_n	Sample size from the B treatment
AB_mean	Mean outcome from the interaction AxB treatment
AB_sd	Standard deviation from the interaction AxB treatment
AB_n	Sample size from the interaction AxB treatment

Details

$$\ln CVR_{inter} = \ln \left(\frac{CV_{AB}/CV_B}{CV_A/CV_{Ctrl}} \right) + \frac{1}{2(n_{AB} - 1)} - \frac{1}{2(n_A - 1)} - \frac{1}{2(n_B - 1)} + \frac{1}{2(n_{Ctrl} - 1)}$$

$$var(\ln CVR_{inter}) = var(\ln RR_{inter}) + var(\ln VR_{inter})$$

This follows the assumption of no correlation between mean and variance.

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

Examples

```
# Interaction effect logCVR (Light x Nutrients)
data <- data.frame(
  study_id = 1:2,
  control_mean = c(7.3, 8.9),
  control_sd = c(1.4, 1.7),
  control_n = c(20, 18),
  light_mean = c(12.8, 14.2),
  light_sd = c(3.1, 3.5),
  light_n = c(19, 20),
  nutrients_mean = c(9.6, 11.1),
  nutrients_sd = c(1.9, 2.2),
  nutrients_n = c(21, 17),
  light_nutrients_mean = c(18.4, 20.7),
  light_nutrients_sd = c(4.8, 5.3),
  light_nutrients_n = c(18, 19)
)

result <- lnCVR_inter(
  data = data,
  Ctrl_mean = "control_mean",
```

```
Ctrl_sd = "control_sd",
Ctrl_n = "control_n",
A_mean = "light_mean",
A_sd = "light_sd",
A_n = "light_n",
B_mean = "nutrients_mean",
B_sd = "nutrients_sd",
B_n = "nutrients_n",
AB_mean = "light_nutrients_mean",
AB_sd = "light_nutrients_sd",
AB_n = "light_nutrients_n"
)
```

lnCVR_main	<i>Main Effect: Log Coefficient Of Variation Ration</i>
------------	---

Description

Computes the main effect of Factor A across levels of Factor B in factorial experiments on the coefficient of variation.

Usage

```
lnCVR_main(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  Ctrl_mean,
  Ctrl_sd,
  Ctrl_n,
  A_mean,
  A_sd,
  A_n,
  B_mean,
  B_sd,
  B_n,
  AB_mean,
  AB_sd,
  AB_n
)
```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE

Ctrl_mean	Mean outcome from the Control treatment
Ctrl_sd	Standard deviation from the control treatment
Ctrl_n	Sample size from the control treatment
A_mean	Mean outcome from the treatment
A_sd	Standard deviation from the treatment
A_n	Sample size from the treatment
B_mean	Mean outcome from the B treatment
B_sd	Standard deviation from the B treatment
B_n	Sample size from the B treatment
AB_mean	Mean outcome from the interaction AxB treatment
AB_sd	Standard deviation from the interaction AxB treatment
AB_n	Sample size from the interaction AxB treatment

Details

$$\ln CVR_{main} = \frac{1}{2} \ln \left(\frac{CV_{AB} CV_A}{CV_B CV_{Ctrl}} \right) + \frac{1}{2} \left(\frac{1}{2(n_{AB} - 1)} + \frac{1}{2(n_A - 1)} - \frac{1}{2(n_B - 1)} - \frac{1}{2(n_{Ctrl} - 1)} \right)$$

$$var(\ln CVR_{main}) = var(\ln RR_{main}) + var(\ln VR_{main})$$

This follows the assumption of no correlation between mean and variance.

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

Examples

```
data <- data.frame(
  study_id = 1:2,
  control_mean = c(14.2, 16.8), control_sd = c(2.8, 3.1), control_n = c(16, 14),
  irrigation_mean = c(19.5, 22.1), irrigation_sd = c(5.2, 5.8), irrigation_n = c(15, 16),
  co2_mean = c(16.8, 19.4), co2_sd = c(3.1, 3.6), co2_n = c(17, 13),
  irrigation_co2_mean = c(24.3, 27.9), irrigation_co2_sd = c(6.8, 7.4), irrigation_co2_n = c(14, 15)
)

result <- lnCVR_main(
  data = data,
  Ctrl_mean = "control_mean", Ctrl_sd = "control_sd", Ctrl_n = "control_n",
```

```

A_mean = "irrigation_mean", A_sd = "irrigation_sd", A_n = "irrigation_n",
B_mean = "co2_mean", B_sd = "co2_sd", B_n = "co2_n",
AB_mean = "irrigation_co2_mean", AB_sd = "irrigation_co2_sd", AB_n = "irrigation_co2_n"
)

```

lnRR_ind

Individual effect: Log Response Ratio

Description

Computes the individual or simple effect of Factor A over the Control.

Usage

```

lnRR_ind(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  Ctrl_mean,
  Ctrl_sd,
  Ctrl_n,
  A_mean,
  A_sd,
  A_n
)

```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
Ctrl_mean	Mean outcome from the Control treatment
Ctrl_sd	Standard deviation from the control treatment
Ctrl_n	Sample size from the control treatment
A_mean	Mean outcome from the experimental treatment
A_sd	Standard deviation from the experimental treatment
A_n	Sample size from the experimental treatment

Details

It is the classic Log Response Ratio (lnRR), which can also be computed with metafor's `escalc()` function using `measure = "ROM"`.

The log response ratio of Factor A over Control is computed as:

Formulas:

$$\ln RR_{ind} = \ln \left(\frac{\bar{X}_A}{\bar{X}_{Ctrl}} \right)$$

$$\text{var}(\ln RR_{ind}) = \frac{sd_A^2}{n_A \bar{X}_A^2} + \frac{sd_{Ctrl}^2}{n_{Ctrl} \bar{X}_{Ctrl}^2}$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named `yi` (effect size) and `vi` (sampling variance). If `append = TRUE`, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Morris, W. F., Hufbauer, R. A., Agrawal, A. A., Bever, J. D., Borowicz, V. A., Gilbert, G. S., ... & Vázquez, D. P. (2007). Direct and interactive effects of enemies and mutualists on plant performance: a meta-analysis. *Ecology*, 88(4), 1021-1029. <https://doi.org/10.1890/06-0442>

Lajeunesse, M. J. (2011). On the meta-analysis of response ratios for studies with correlated and multi-group designs. *Ecology*, 92(11), 2049-2055. <https://doi.org/10.1890/11-0423.1>

Examples

```
data <- data.frame(
  study_id = 1:3,
  control_mean = c(10, 15, 12),
  control_sd = c(2.1, 3.2, 2.8),
  control_n = c(20, 25, 18),
  drought_mean = c(12, 18, 14),
  drought_sd = c(2.3, 3.5, 3.1),
  drought_n = c(22, 24, 20)
)

# Compute individual effect of drought vs control
result <- lnRR_ind(
  data = data,
  Ctrl_mean = "control_mean",
  Ctrl_sd = "control_sd",
  Ctrl_n = "control_n",
  A_mean = "drought_mean",
  A_sd = "drought_sd",
```

```

    A_n = "drought_n"
  )

```

lnRR_inter

Interaction effect: Log Response Ratio

Description

Computes the interaction effect between factors A and B in factorial data.

Usage

```

lnRR_inter(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  Ctrl_mean,
  Ctrl_sd,
  Ctrl_n,
  A_mean,
  A_sd,
  A_n,
  B_mean,
  B_sd,
  B_n,
  AB_mean,
  AB_sd,
  AB_n
)

```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
Ctrl_mean	Mean outcome from the Control treatment
Ctrl_sd	Standard deviation from the control treatment
Ctrl_n	Sample size from the control treatment
A_mean	Mean outcome from the treatment
A_sd	Standard deviation from the treatment
A_n	Sample size from the treatment
B_mean	Mean outcome from the B treatment

B_sd	Standard deviation from the B treatment
B_n	Sample size from the B treatment
AB_mean	Mean outcome from the interaction AxB treatment
AB_sd	Standard deviation from the interaction AxB treatment
AB_n	Sample size from the interaction AxB treatment

Details

$$\ln RR_{inter} = (\ln \bar{X}_{AB} - \ln \bar{X}_B) - (\ln \bar{X}_A - \ln \bar{X}_{Ctrl})$$

$$var(\ln RR_{inter}) = \frac{sd_{AB}^2}{n_{AB} \bar{X}_{AB}^2} + \frac{sd_A^2}{n_A \bar{X}_A^2} + \frac{sd_B^2}{n_B \bar{X}_B^2} + \frac{sd_{Ctrl}^2}{n_{Ctrl} \bar{X}_{Ctrl}^2}$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Morris, W. F., Hufbauer, R. A., Agrawal, A. A., Bever, J. D., Borowicz, V. A., Gilbert, G. S., ... & Vázquez, D. P. (2007). Direct and interactive effects of enemies and mutualists on plant performance: a meta-analysis. *Ecology*, 88(4), 1021-1029. <https://doi.org/10.1890/06-0442>

Examples

```
data <- data.frame(
  study_id = 1:2,
  control_mean = c(25, 28), control_sd = c(3.2, 3.8), control_n = c(15, 17),
  predation_mean = c(18, 20), predation_sd = c(2.9, 3.1), predation_n = c(16, 18),
  competition_mean = c(22, 24), competition_sd = c(3.0, 3.5), competition_n = c(14, 16),
  pred_comp_mean = c(12, 15), pred_comp_sd = c(2.1, 2.6), pred_comp_n = c(15, 17)
)

# Compute interaction effect between predation and competition
result <- lnRR_inter(
  data = data,
  Ctrl_mean = "control_mean", Ctrl_sd = "control_sd", Ctrl_n = "control_n",
  A_mean = "predation_mean", A_sd = "predation_sd", A_n = "predation_n",
  B_mean = "competition_mean", B_sd = "competition_sd", B_n = "competition_n",
  AB_mean = "pred_comp_mean", AB_sd = "pred_comp_sd", AB_n = "pred_comp_n"
)
```

lnRR_main

*Main effect: Log Response Ratio***Description**

Computes the main effect of Factor A across levels of Factor B, analogous to the main effect in a factorial ANOVA.

Usage

```
lnRR_main(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  method = "nakagawa",
  Ctrl_mean,
  Ctrl_sd,
  Ctrl_n,
  A_mean,
  A_sd,
  A_n,
  B_mean,
  B_sd,
  B_n,
  AB_mean,
  AB_sd,
  AB_n
)
```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
method	Method to compute lnRR. Can be either "nakagawa" or "morris". Default is "nakagawa".
Ctrl_mean	Mean outcome from the Control treatment
Ctrl_sd	Standard deviation from the control treatment
Ctrl_n	Sample size from the control treatment
A_mean	Mean outcome from the A treatment
A_sd	Standard deviation from the A treatment
A_n	Sample size from the A treatment
B_mean	Mean outcome from the B treatment

B_sd	Standard deviation from the B treatment
B_n	Sample size from the B treatment
AB_mean	Mean outcome from the interaction AxB treatment
AB_sd	Standard deviation from the interaction AxB treatment
AB_n	Sample size from the interaction AxB treatment

Details

There are two ways of computing the lnRR. One is the original method used by Morris et al. 2007, and the other is the one proposed by Shinichi Nakagawa (in prep). Default method is 'nakagawa':

Nakagawa formula

$$lnRR_{main} = \frac{1}{2} \ln\left(\frac{\bar{X}_A \bar{X}_{AB}}{\bar{X}_B \bar{X}_{Ctrl}}\right)$$

$$var(lnRR_{main}) = \frac{1}{4} \left(\frac{sd_A^2}{n_A \bar{X}_A^2} + \frac{sd_B^2}{n_B \bar{X}_B^2} + \frac{sd_{AB}^2}{n_{AB} \bar{X}_{AB}^2} + \frac{sd_{Ctrl}^2}{n_{Ctrl} \bar{X}_{Ctrl}^2} \right)$$

Morris formula

$$lnRR_{main} = \ln\left(\frac{\bar{X}_A + \bar{X}_{AB}}{\bar{X}_B + \bar{X}_{Ctrl}}\right)$$

$$var(lnRR_{main}) = \left(\frac{1}{\bar{X}_A + \bar{X}_{AB}}\right)^2 \left(\frac{sd_A^2}{n_A} + \frac{sd_{AB}^2}{n_{AB}}\right) + \left(\frac{1}{\bar{X}_B + \bar{X}_{Ctrl}}\right)^2 \left(\frac{sd_B^2}{n_B} + \frac{sd_{Ctrl}^2}{n_{Ctrl}}\right)$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

- Morris, W. F., Hufbauer, R. A., Agrawal, A. A., Bever, J. D., Borowicz, V. A., Gilbert, G. S., ... & Vázquez, D. P. (2007). Direct and interactive effects of enemies and mutualists on plant performance: a meta-analysis. *Ecology*, 88(4), 1021-1029. <https://doi.org/10.1890/06-0442>
- Lajeunesse, M. J. (2011). On the meta-analysis of response ratios for studies with correlated and multi-group designs. *Ecology*, 92(11), 2049-2055. <https://doi.org/10.1890/11-0423.1>
- Macartney, E. L., Lagisz, M., & Nakagawa, S. (2022). The relative benefits of environmental enrichment on learning and memory are greater when stressed: A meta-analysis of interactions in rodents. *Neuroscience & Biobehavioral Reviews*, 135, 104554. <https://doi.org/10.1016/j.neubiorev.2022.104554>

Examples

```
# Example data for 2x2 factorial design (Fertilization x Warming)
data <- data.frame(
  study_id = 1:2,
  control_mean = c(10, 12), control_sd = c(2.0, 2.5), control_n = c(20, 18),
  fertilization_mean = c(15, 16), fertilization_sd = c(2.2, 2.8), fertilization_n = c(20, 19),
  warming_mean = c(11, 13), warming_sd = c(2.1, 2.6), warming_n = c(21, 17),
  fert_warm_mean = c(17, 19), fert_warm_sd = c(2.4, 3.0), fert_warm_n = c(19, 20)
)

# Compute main effect of fertilization
result <- lnRR_main(
  data = data,
  Ctrl_mean = "control_mean", Ctrl_sd = "control_sd", Ctrl_n = "control_n",
  A_mean = "fertilization_mean", A_sd = "fertilization_sd", A_n = "fertilization_n",
  B_mean = "warming_mean", B_sd = "warming_sd", B_n = "warming_n",
  AB_mean = "fert_warm_mean", AB_sd = "fert_warm_sd", AB_n = "fert_warm_n"
)
```

InVR_ind

Individual effect: Log of Variability Ratio

Description

Computes the Log of the Variability Ratio between a Factor A and the Control treatment in factorial experiments.

Usage

```
lnVR_ind(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  Ctrl_sd,
  Ctrl_n,
  A_sd,
  A_n
)
```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
Ctrl_sd	Standard deviation from the control treatment

Ctrl_n	Sample size from the control treatment
A_sd	Standard deviation from the treatment
A_n	Sample size from the treatment

Details

$$\ln V R_{ind} = \ln \left(\frac{sd_A}{sd_{Ctrl}} \right) + \frac{1}{2(n_A - 1)} - \frac{1}{2(n_{Ctrl} - 1)}$$

$$var(\ln V R_{ind}) = \frac{1}{2(n_A - 1)} + \frac{1}{2(n_{Ctrl} - 1)}$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Nakagawa, S., Poulin, R., Mengersen, K., Reinhold, K., Engqvist, L., Lagisz, M., & Senior, A. M. (2015). Meta-analysis of variation: ecological and evolutionary applications and beyond. *Methods in Ecology and Evolution*, 6(2), 143-152.

Examples

```
# Example focusing on variability differences (Herbivory effect)
data <- data.frame(
  study_id = 1:3,
  control_sd = c(2.1, 1.8, 2.5),
  control_n = c(20, 22, 18),
  herbivory_sd = c(3.2, 2.9, 3.8),
  herbivory_n = c(21, 20, 19)
)

result <- lnVR_ind(
  data = data,
  Ctrl_sd = "control_sd",
  Ctrl_n = "control_n",
  A_sd = "herbivory_sd",
  A_n = "herbivory_n"
)
```

lnVR_inter	<i>Interaction effect: Log Variability Ratio</i>
------------	--

Description

Computes the interaction of Factors A and B measured as the log of the variability ratio.

Usage

```
lnVR_inter(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  Ctrl_sd,
  Ctrl_n,
  A_sd,
  A_n,
  B_sd,
  B_n,
  AB_sd,
  AB_n
)
```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
Ctrl_sd	Standard deviation from the control treatment
Ctrl_n	Sample size from the control treatment
A_sd	Standard deviation from the A treatment
A_n	Sample size from the A treatment
B_sd	Standard deviation from the B treatment
B_n	Sample size from the B treatment
AB_sd	Standard deviation from the interaction AxB treatment
AB_n	Sample size from the interaction AxB treatment

Details

$$lnVR_{inter} = \ln \left(\frac{sd_{AB}/sd_B}{sd_A/sd_{Ctrl}} \right) + \frac{1}{2(n_{AB} - 1)} - \frac{1}{2(n_A - 1)} - \frac{1}{2(n_B - 1)} + \frac{1}{2(n_{Ctrl} - 1)}$$

$$var(lnVR_{inter}) = \frac{1}{2(n_{AB} - 1)} + \frac{1}{2(n_A - 1)} + \frac{1}{2(n_B - 1)} + \frac{1}{2(n_{Ctrl} - 1)}$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

Examples

```
# Example for interaction effect in 2x2 factorial focusing on variability (Drought x Temperature)
data <- data.frame(
  study_id = 1:2,
  control_sd = c(1.8, 2.1), control_n = c(22, 19),
  drought_sd = c(2.6, 2.9), drought_n = c(20, 21),
  temperature_sd = c(2.0, 2.3), temperature_n = c(21, 18),
  drought_temp_sd = c(3.2, 3.6), drought_temp_n = c(19, 20)
)

result <- lnVR_inter(
  data = data,
  Ctrl_sd = "control_sd", Ctrl_n = "control_n",
  A_sd = "drought_sd", A_n = "drought_n",
  B_sd = "temperature_sd", B_n = "temperature_n",
  AB_sd = "drought_temp_sd", AB_n = "drought_temp_n"
)
```

lnVR_main

Main Effect: Log of the Variability Ratio

Description

Computes the overall log of the variability ratio for Factor A across levels of Factor B.

Usage

```
lnVR_main(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  Ctrl_sd,
  Ctrl_n,
  A_sd,
  A_n,
  B_sd,
  B_n,
```

```

    AB_sd,
    AB_n
  )

```

Arguments

<code>data</code>	Data frame containing the variables used.
<code>col_names</code>	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
<code>append</code>	Logical. Append the results to data. Default is TRUE
<code>Ctrl_sd</code>	Standard deviation from the control treatment
<code>Ctrl_n</code>	Sample size from the control treatment
<code>A_sd</code>	Standard deviation from the A treatment
<code>A_n</code>	Sample size from the A treatment
<code>B_sd</code>	Standard deviation from the B treatment
<code>B_n</code>	Sample size from the B treatment
<code>AB_sd</code>	Standard deviation from the interaction AxB treatment
<code>AB_n</code>	Sample size from the interaction AxB treatment

Details

$$lnVR_{main} = \frac{1}{2} \ln \left(\frac{sd_{AB}sd_A}{sd_Bsd_{Ctrl}} \right) + \frac{1}{2} \left(\frac{1}{2(n_{AB} - 1)} + \frac{1}{2(n_A - 1)} - \frac{1}{2(n_B - 1)} - \frac{1}{2(n_{Ctrl} - 1)} \right)$$

$$var(lnVR_{main}) = \frac{1}{4} \left(\frac{1}{2(n_{AB} - 1)} + \frac{1}{2(n_A - 1)} + \frac{1}{2(n_B - 1)} + \frac{1}{2(n_{Ctrl} - 1)} \right)$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If `append = TRUE`, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

Examples

```

# Example for main effect in 2x2 factorial focusing on variability (Fire x Grazing)
data <- data.frame(
  study_id = 1:2,
  control_sd = c(2.0, 2.3), control_n = c(20, 18),
  fire_sd = c(2.8, 3.1), fire_n = c(19, 20),
  grazing_sd = c(2.2, 2.5), grazing_n = c(21, 17),

```

```

    fire_grazing_sd = c(3.5, 3.8), fire_grazing_n = c(18, 19)
  )

  result <- lnVR_main(
    data = data,
    Ctrl_sd = "control_sd", Ctrl_n = "control_n",
    A_sd = "fire_sd", A_n = "fire_n",
    B_sd = "grazing_sd", B_n = "grazing_n",
    AB_sd = "fire_grazing_sd", AB_n = "fire_grazing_n"
  )

```

SMD_ind

*Individual effect: Standardized Mean Difference***Description**

Computes the effect of Factor A over the Control.

Usage

```

SMD_ind(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  hedges_correction = TRUE,
  Ctrl_mean,
  Ctrl_sd,
  Ctrl_n,
  A_mean,
  A_sd,
  A_n
)

```

Arguments

<code>data</code>	Data frame containing the variables used.
<code>col_names</code>	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
<code>append</code>	Logical. Append the results to data. Default is TRUE
<code>hedges_correction</code>	Boolean. If TRUE correct for small-sample bias. Default is TRUE.
<code>Ctrl_mean</code>	Mean outcome from the Control treatment
<code>Ctrl_sd</code>	Standard deviation from the control treatment
<code>Ctrl_n</code>	Sample size from the control treatment
<code>A_mean</code>	Mean outcome from the experimental treatment
<code>A_sd</code>	Standard deviation from the experimental treatment
<code>A_n</code>	Sample size from the experimental treatment

Details

It is the classic Standardized Mean Difference (SMD), which can also be computed with metafor's `escalc()` function using `measure = "SMD"`.

The SMD of Factor A over the Control is computed as:

$$d_{ind} = \frac{\bar{X}_A - \bar{X}_{Ctrl}}{S_{pooled}} \cdot J(m)$$

where the pooled standard deviation is:

$$S_{pooled} = \sqrt{\frac{(n_A - 1)sd_A^2 + (n_{Ctrl} - 1)sd_{Ctrl}^2}{n_A + n_{Ctrl} - 2}}$$

And the Hedges correction:

$$J(m) = 1 - \frac{3}{4m - 1}$$

with :

$$m = n_A + n_{Ctrl} - 2$$

The sampling variance is:

$$var(d_{ind}) = \frac{1}{n_A} + \frac{1}{n_{Ctrl}} + \frac{d^2}{2(n_A + n_{Ctrl})}$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named `yi` (effect size) and `vi` (sampling variance). If `append = TRUE`, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Gurevitch, J., Morrison, J. A., & Hedges, L. V. (2000). The interaction between competition and predation: a meta-analysis of field experiments. *The American Naturalist*, 155(4), 435-453.

Morris, W. F., Hufbauer, R. A., Agrawal, A. A., Bever, J. D., Borowicz, V. A., Gilbert, G. S., ... & Vázquez, D. P. (2007). Direct and interactive effects of enemies and mutualists on plant performance: a meta-analysis. *Ecology*, 88(4), 1021-1029. <https://doi.org/10.1890/06-0442>

Examples

```

data <- data.frame(
  study_id = 1:3,
  control_mean = c(45.2, 52.8, 38.9),
  control_sd = c(8.1, 11.2, 7.3),
  control_n = c(18, 23, 16),
  pollinator_exclusion_mean = c(28.7, 35.4, 22.1),
  pollinator_exclusion_sd = c(6.8, 9.1, 5.9),
  pollinator_exclusion_n = c(20, 22, 18)
)

# With Hedges' correction (default)
result <- SMD_ind(
  data = data,
  Ctrl_mean = "control_mean",
  Ctrl_sd = "control_sd",
  Ctrl_n = "control_n",
  A_mean = "pollinator_exclusion_mean",
  A_sd = "pollinator_exclusion_sd",
  A_n = "pollinator_exclusion_n",
  hedges_correction = TRUE
)

# Without Hedges' correction
result_no_hedges <- SMD_ind(
  data = data,
  Ctrl_mean = "control_mean",
  Ctrl_sd = "control_sd",
  Ctrl_n = "control_n",
  A_mean = "pollinator_exclusion_mean",
  A_sd = "pollinator_exclusion_sd",
  A_n = "pollinator_exclusion_n",
  hedges_correction = FALSE
)

```

SMD_inter

*Interaction effect: Standardized mean difference***Description**

Computes the interaction effect between factors A and B in factorial data.

Usage

```

SMD_inter(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,

```

```

    hedges_correction = TRUE,
    Ctrl_mean,
    Ctrl_sd,
    Ctrl_n,
    A_mean,
    A_sd,
    A_n,
    B_mean,
    B_sd,
    B_n,
    AB_mean,
    AB_sd,
    AB_n
  )

```

Arguments

<code>data</code>	Data frame containing the variables used.
<code>col_names</code>	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
<code>append</code>	Logical. Append the results to data. Default is TRUE
<code>hedges_correction</code>	Logical. Apply or not Hedges' correction for small-sample bias. Default is TRUE
<code>Ctrl_mean</code>	Mean outcome from the Control treatment
<code>Ctrl_sd</code>	Standard deviation from the control treatment
<code>Ctrl_n</code>	Sample size from the control treatment
<code>A_mean</code>	Mean outcome from the treatment
<code>A_sd</code>	Standard deviation from the treatment
<code>A_n</code>	Sample size from the treatment
<code>B_mean</code>	Mean outcome from the B treatment
<code>B_sd</code>	Standard deviation from the B treatment
<code>B_n</code>	Sample size from the B treatment
<code>AB_mean</code>	Mean outcome from the interaction AxB treatment
<code>AB_sd</code>	Standard deviation from the interaction AxB treatment
<code>AB_n</code>	Sample size from the interaction AxB treatment

Details

The interaction is computed as:

$$d_{inter} = \frac{(\bar{X}_{AB} - \bar{X}_B) - (\bar{X}_A - \bar{X}_{Ctrl})}{S_{pooled}} \cdot J(m)$$

With the pooled standard deviation:

$$S_{pooled} = \sqrt{\frac{(n_A - 1)sd_A^2 + (n_B - 1)sd_B^2 + (n_{AB} - 1)sd_{AB}^2 + (n_{Ctrl} - 1)sd_{Ctrl}^2}{n_A + n_B + n_{AB} + n_{Ctrl} - 4}}$$

And the Hedges correction as:

$$J(m) = 1 - \frac{3}{4m - 1}$$

with:

$$m = n_A + n_B + n_{AB} + n_{Ctrl} - 4$$

The sampling variance is computed as:

$$var(d_{inter}) = \frac{1}{n_A} + \frac{1}{n_B} + \frac{1}{n_{AB}} + \frac{1}{n_{Ctrl}} + \frac{d_{inter}^2}{2(n_A + n_B + n_{AB} + n_{Ctrl})}$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Gurevitch, J., Morrison, J. A., & Hedges, L. V. (2000). The interaction between competition and predation: a meta-analysis of field experiments. *The American Naturalist*, 155(4), 435-453.

Morris, W. F., Hufbauer, R. A., Agrawal, A. A., Bever, J. D., Borowicz, V. A., Gilbert, G. S., ... & Vázquez, D. P. (2007). Direct and interactive effects of enemies and mutualists on plant performance: a meta-analysis. *Ecology*, 88(4), 1021-1029. <https://doi.org/10.1890/06-0442>

Examples

```
data <- data.frame(
  study_id = 1:2,
  control_mean = c(24.8, 27.2), control_sd = c(4.1, 4.6), control_n = c(18, 16),
  salinity_mean = c(19.3, 21.7), salinity_sd = c(3.8, 4.2), salinity_n = c(17, 18),
  temperature_mean = c(28.9, 31.4), temperature_sd = c(4.7, 5.1), temperature_n = c(19, 15),
  salt_temp_mean = c(15.2, 17.8), salt_temp_sd = c(3.1, 3.5), salt_temp_n = c(16, 17)
)

result <- SMD_inter(
  data = data,
  Ctrl_mean = "control_mean", Ctrl_sd = "control_sd", Ctrl_n = "control_n",
  A_mean = "salinity_mean", A_sd = "salinity_sd", A_n = "salinity_n",
  B_mean = "temperature_mean", B_sd = "temperature_sd", B_n = "temperature_n",
  AB_mean = "salt_temp_mean", AB_sd = "salt_temp_sd", AB_n = "salt_temp_n"
```

)

SMD_main	<i>Main effect: Standardized Mean Difference</i>
----------	--

Description

Computes the main effect of Factor A across levels of Factor B, analogous to the main effect in a factorial ANOVA.

Usage

```
SMD_main(  
  data,  
  col_names = c("yi", "vi"),  
  append = TRUE,  
  hedges_correction = TRUE,  
  Ctrl_mean,  
  Ctrl_sd,  
  Ctrl_n,  
  A_mean,  
  A_sd,  
  A_n,  
  B_mean,  
  B_sd,  
  B_n,  
  AB_mean,  
  AB_sd,  
  AB_n  
)
```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
hedges_correction	Boolean. If TRUE correct for small-sample bias. Default is TRUE.
Ctrl_mean	Mean outcome from the Control treatment
Ctrl_sd	Standard deviation from the control treatment
Ctrl_n	Sample size from the control treatment
A_mean	Mean outcome from the A treatment
A_sd	Standard deviation from the A treatment

A_n	Sample size from the A treatment
B_mean	Mean outcome from the B treatment
B_sd	Standard deviation from the B treatment
B_n	Sample size from the B treatment
AB_mean	Mean outcome from the interaction AxB treatment
AB_sd	Standard deviation from the interaction AxB treatment
AB_n	Sample size from the interaction AxB treatment

Details

The main SMD of Factor A is computed as:

$$d_{main} = \frac{(\bar{X}_A + \bar{X}_{AB}) - (\bar{X}_B + \bar{X}_{Ctrl})}{2S_{pooled}} \cdot J(m)$$

With the pooled standard deviation:

$$S_{pooled} = \sqrt{\frac{(n_A - 1)sd_A^2 + (n_B - 1)sd_B^2 + (n_{AB} - 1)sd_{AB}^2 + (n_{Ctrl} - 1)sd_{Ctrl}^2}{n_A + n_B + n_{AB} + n_{Ctrl} - 4}}$$

And the Hedges correction as:

$$J(m) = 1 - \frac{3}{4m - 1}$$

with:

$$m = n_A + n_B + n_{AB} + n_{Ctrl} - 4$$

The sampling variance is computed as:

$$var(d_{main}) = \frac{1}{4} \left[\frac{1}{n_A} + \frac{1}{n_B} + \frac{1}{n_{AB}} + \frac{1}{n_{Ctrl}} + \frac{d_{main}^2}{2(n_A + n_B + n_{AB} + n_{Ctrl})} \right]$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

- Gurevitch, J., Morrison, J. A., & Hedges, L. V. (2000). The interaction between competition and predation: a meta-analysis of field experiments. *The American Naturalist*, 155(4), 435-453.
- Morris, W. F., Hufbauer, R. A., Agrawal, A. A., Bever, J. D., Borowicz, V. A., Gilbert, G. S., ... & Vázquez, D. P. (2007). Direct and interactive effects of enemies and mutualists on plant performance: a meta-analysis. *Ecology*, 88(4), 1021-1029. <https://doi.org/10.1890/06-0442>

Examples

```
# Main effect of Mycorrhiza in 2x2 factorial design (AMF x Phosphorus)
data <- data.frame(
  study_id = 1:2,
  control_mean = c(12.4, 15.1), control_sd = c(2.8, 3.2), control_n = c(16, 14),
  mycorrhizae_mean = c(18.7, 21.3), mycorrhizae_sd = c(3.4, 3.9), mycorrhizae_n = c(15, 16),
  phosphorus_mean = c(14.9, 17.8), phosphorus_sd = c(3.1, 3.6), phosphorus_n = c(17, 13),
  myco_phos_mean = c(22.1, 25.4), myco_phos_sd = c(4.2, 4.8), myco_phos_n = c(14, 15)
)

result <- SMD_main(
  data = data,
  Ctrl_mean = "control_mean", Ctrl_sd = "control_sd", Ctrl_n = "control_n",
  A_mean = "mycorrhizae_mean", A_sd = "mycorrhizae_sd", A_n = "mycorrhizae_n",
  B_mean = "phosphorus_mean", B_sd = "phosphorus_sd", B_n = "phosphorus_n",
  AB_mean = "myco_phos_mean", AB_sd = "myco_phos_sd", AB_n = "myco_phos_n"
)
```

time_InCVR

Log Coefficient of Variation Ratio: Interaction Between Treatment and Time

Description

Log Coefficient of Variation Ratio: Interaction Between Treatment and Time

Usage

```
time_InCVR(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  t0_Ctrl_mean,
  t0_Ctrl_sd,
  t1_Ctrl_mean,
  t1_Ctrl_sd,
  Ctrl_n,
  Ctrl_cor,
  t0_Exp_mean,
  t0_Exp_sd,
  t1_Exp_mean,
  t1_Exp_sd,
  Exp_n,
  Exp_cor
)
```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
t0_Ctrl_mean	Sample mean from the control group at time 0
t0_Ctrl_sd	Standard deviation from the control group at time 0
t1_Ctrl_mean	Sample mean from the control group at time 1
t1_Ctrl_sd	Standard deviation from the control group at time 1
Ctrl_n	Sample size of the control group
Ctrl_cor	Number or numeric vector. Correlation between the means of the control group at t0 and t1
t0_Exp_mean	Sample mean from the experimental group at time 0
t0_Exp_sd	Standard deviation from the experimental group at time 0
t1_Exp_mean	Sample mean from the experimental group at time 1
t1_Exp_sd	Standard deviation from the experimental group at time 1
Exp_n	Sample size of the experimental group
Exp_cor	Number or numeric vector. Correlation between the means of the experimental group at t0 and t1

Formulas

$$\ln CVR_{f:t} = \ln \left(\frac{CV_{t1,Exp}/CV_{t1,Ctrl}}{CV_{t0,Exp}/CV_{t0,Ctrl}} \right)$$

$$var(\ln CVR_{f:t}) = var(\ln RR_{f:t}) + var(\ln VR_{f:t})$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Shinichi Nakagawa and Daniel Noble, personal communication.

Examples

```
# Pre-post design for coefficient of variation changes over time (Disturbance experiment)
data <- data.frame(
  study_id = 1:2,
  pre_control_mean = c(12.8, 15.4), pre_control_sd = c(2.6, 3.1),
  post_control_mean = c(13.2, 15.9), post_control_sd = c(2.7, 3.2),
  control_n = c(20, 18),
  pre_disturbed_mean = c(12.9, 15.2), pre_disturbed_sd = c(2.5, 3.0),
  post_disturbed_mean = c(8.7, 10.1), post_disturbed_sd = c(3.8, 4.3),
  disturbed_n = c(19, 21)
)

result <- time_lnCVR(
  data = data,
  t0_Ctrl_mean = "pre_control_mean", t0_Ctrl_sd = "pre_control_sd",
  t1_Ctrl_mean = "post_control_mean", t1_Ctrl_sd = "post_control_sd",
  Ctrl_n = "control_n", Ctrl_cor = 0.8,
  t0_Exp_mean = "pre_disturbed_mean", t0_Exp_sd = "pre_disturbed_sd",
  t1_Exp_mean = "post_disturbed_mean", t1_Exp_sd = "post_disturbed_sd",
  Exp_n = "disturbed_n", Exp_cor = 0.5
)
```

time_lnRR

Log Response Ratio: Interaction Between Treatment and Time

Description

Log Response Ratio: Interaction Between Treatment and Time

Usage

```
time_lnRR(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  t0_Ctrl_mean,
  t0_Ctrl_sd,
  t1_Ctrl_mean,
  t1_Ctrl_sd,
  Ctrl_n,
  Ctrl_cor,
  t0_Exp_mean,
  t0_Exp_sd,
  t1_Exp_mean,
  t1_Exp_sd,
  Exp_n,
  Exp_cor
)
```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
t0_Ctrl_mean	Sample mean from the control group at time 0
t0_Ctrl_sd	Standard deviation from the control group at time 0
t1_Ctrl_mean	Sample mean from the control group at time 1
t1_Ctrl_sd	Standard deviation from the control group at time 1
Ctrl_n	Sample size of the control group
Ctrl_cor	Number or numeric vector. Correlation between the means of the control group at t0 and t1
t0_Exp_mean	Sample mean from the experimental group at time 0
t0_Exp_sd	Standard deviation from the experimental group at time 0
t1_Exp_mean	Sample mean from the experimental group at time 1
t1_Exp_sd	Standard deviation from the experimental group at time 1
Exp_n	Sample size of the experimental group
Exp_cor	Number or numeric vector. Correlation between the means of the experimental group at t0 and t1

Formulas

$$\ln RR_{f.t} = \ln \left(\frac{\bar{X}_{t1,Exp} / \bar{X}_{t1,Ctrl}}{\bar{X}_{t0,Exp} / \bar{X}_{t0,Ctrl}} \right)$$

$$var(\ln RR_{f.t}) = \frac{sd_{t0,Exp}^2}{n_{Exp} \bar{x}_{t0,Exp}^2} + \frac{sd_{t1,Exp}^2}{n_{Exp} \bar{x}_{t1,Exp}^2} - 2r_{Exp,t0t1} \frac{sd_{t0,Exp} sd_{t1,Exp}}{n_{Exp} \bar{x}_{t0,Exp} \bar{x}_{t1,Exp}} + \frac{sd_{t0,Ctrl}^2}{n_{Ctrl} \bar{x}_{t0,Ctrl}^2} + \frac{sd_{t1,Ctrl}^2}{n_{Ctrl} \bar{x}_{t1,Ctrl}^2} - 2r_{Ctrl,t0t1} \frac{sd_{t0,Ctrl} sd_{t1,Ctrl}}{n_{Ctrl} \bar{x}_{t0,Ctrl} \bar{x}_{t1,Ctrl}}$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Shinichi Nakagawa and Daniel Noble, personal communication.

Examples

```
data <- data.frame(
  study_id = 1:2,
  pre_control_mean = c(8.4, 10.2),      # Control before restoration
  pre_control_sd = c(1.8, 2.1),
  post_control_mean = c(8.9, 10.7),     # Control after restoration period
  post_control_sd = c(1.9, 2.2),
  control_n = c(22, 18),
  pre_restoration_mean = c(8.6, 10.1), # Restoration sites before
  pre_restoration_sd = c(1.9, 2.0),
  post_restoration_mean = c(15.3, 17.8), # Restoration sites after
  post_restoration_sd = c(3.2, 3.7),
  restoration_n = c(20, 19)
)

result <- time_InRR(
  data = data,
  t0_Ctrl_mean = "pre_control_mean", t0_Ctrl_sd = "pre_control_sd",
  t1_Ctrl_mean = "post_control_mean", t1_Ctrl_sd = "post_control_sd",
  Ctrl_n = "control_n", Ctrl_cor = 0.7, # Correlation within control sites
  t0_Exp_mean = "pre_restoration_mean", t0_Exp_sd = "pre_restoration_sd",
  t1_Exp_mean = "post_restoration_mean", t1_Exp_sd = "post_restoration_sd",
  Exp_n = "restoration_n", Exp_cor = 0.6 # Correlation within restoration sites
)

# Using different correlations for each study
result2 <- time_InRR(
  data = data,
  t0_Ctrl_mean = "pre_control_mean", t0_Ctrl_sd = "pre_control_sd",
  t1_Ctrl_mean = "post_control_mean", t1_Ctrl_sd = "post_control_sd",
  Ctrl_n = "control_n", Ctrl_cor = c(0.6, 0.8),
  t0_Exp_mean = "pre_restoration_mean", t0_Exp_sd = "pre_restoration_sd",
  t1_Exp_mean = "post_restoration_mean", t1_Exp_sd = "post_restoration_sd",
  Exp_n = "restoration_n", Exp_cor = c(0.5, 0.7)
)
```

time_InVR

Log of Variability Ratio: Interaction Between Treatment and Time

Description

Log of Variability Ratio: Interaction Between Treatment and Time

Usage

```
time_InVR(
  data,
  col_names = c("yi", "vi"),
```

```

    append = TRUE,
    t0_Ctrl_sd,
    t1_Ctrl_sd,
    Ctrl_n,
    Ctrl_cor,
    t0_Exp_sd,
    t1_Exp_sd,
    Exp_n,
    Exp_cor
  )

```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
t0_Ctrl_sd	Standard deviation from the control group at time 0
t1_Ctrl_sd	Standard deviation from the control group at time 1
Ctrl_n	Sample size of the control group
Ctrl_cor	Number or numeric vector. Correlation between the means of the control group at t0 and t1
t0_Exp_sd	Standard deviation from the experimental group at time 0
t1_Exp_sd	Standard deviation from the experimental group at time 1
Exp_n	Sample size of the experimental group
Exp_cor	Number or numeric vector. Correlation between the means of the experimental group at t0 and t1

Formulas

$$\ln VR = \ln \left(\frac{sd_{t1,Exp}/sd_{t1,Ctrl}}{sd_{t0,Exp}/sd_{t0,Ctrl}} \right)$$

$$var(\ln VR) = \frac{(1 - r_{Exp,t0t1}^2)}{n_{Exp} - 1} + \frac{(1 - r_{Ctrl,t0t1}^2)}{n_{Ctrl} - 1}$$

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Shinichi Nakagawa and Daniel Noble, personal communication.

Examples

```

data <- data.frame(
  study_id = 1:2,
  pre_control_sd = c(2.1, 2.4),
  post_control_sd = c(2.2, 2.5),
  control_n = c(24, 19),
  pre_invaded_sd = c(2.0, 2.3),
  post_invaded_sd = c(4.1, 4.6),
  invaded_n = c(21, 22)
)

result <- time_lnVR(
  data = data,
  t0_Ctrl_sd = "pre_control_sd", t1_Ctrl_sd = "post_control_sd",
  Ctrl_n = "control_n", Ctrl_cor = 0.6,
  t0_Exp_sd = "pre_invaded_sd", t1_Exp_sd = "post_invaded_sd",
  Exp_n = "invaded_n", Exp_cor = 0.4
)

```

time_SMD	<i>Standardized Mean Difference: Interaction Between Treatment and Time</i>
----------	---

Description

Standardized Mean Difference: Interaction Between Treatment and Time

Usage

```

time_SMD(
  data,
  col_names = c("yi", "vi"),
  append = TRUE,
  hedges_correction = TRUE,
  t0_Ctrl_mean,
  t0_Ctrl_sd,
  t1_Ctrl_mean,
  t1_Ctrl_sd,
  Ctrl_n,
  Ctrl_cor,
  t0_Exp_mean,
  t0_Exp_sd,
  t1_Exp_mean,
  t1_Exp_sd,
  Exp_n,
  Exp_cor
)

```

Arguments

data	Data frame containing the variables used.
col_names	Vector of two strings to name the output columns for the effect size and its sampling variance. Default is 'yi' and 'vi'.
append	Logical. Append the results to data. Default is TRUE
hedges_correction	Logical. Apply or not Hedges' correction for small-sample bias. Default is TRUE.
t0_Ctrl_mean	Sample mean from the control group at time 0
t0_Ctrl_sd	Standard deviation from the control group at time 0
t1_Ctrl_mean	Sample mean from the control group at time 1
t1_Ctrl_sd	Standard deviation from the control group at time 1
Ctrl_n	Sample size of the control group
Ctrl_cor	Number or numeric vector. Correlation between the means of the control group at t0 and t1
t0_Exp_mean	Sample mean from the experimental group at time 0
t0_Exp_sd	Standard deviation from the experimental group at time 0
t1_Exp_mean	Sample mean from the experimental group at time 1
t1_Exp_sd	Standard deviation from the experimental group at time 1
Exp_n	Sample size of the experimental group
Exp_cor	Number or numeric vector. Correlation between the means of the experimental group at t0 and t1

Details**Formulas**

$$d_{f:t} = \frac{(\bar{X}_{t1,Exp} - \bar{X}_{t1,Ctrl}) - (\bar{X}_{t0,Exp} - \bar{X}_{t0,Ctrl})}{S_{pooled}} \cdot J$$

Pooled standard deviation:

$$S_{pooled} = \sqrt{\frac{(n_{Exp} - 1)(sd_{t0,Exp}^2 + sd_{t1,Exp}^2) + (n_{Ctrl} - 1)(sd_{t0,Ctrl}^2 + sd_{t1,Ctrl}^2)}{2(n_{Exp} + n_{Ctrl} - 2)}}$$

Sampling variance:

$$var(d_{f:t}) = \frac{2(1 - r_{Exp})}{n_{Exp}} + \frac{2(1 - r_{Ctrl})}{n_{Ctrl}} + \frac{d^2}{2(n_{Exp} + n_{Ctrl})}$$

where r_{Exp} and r_{Ctrl} are the correlations between time points within each group.

Value

A data frame containing the effect sizes and their sampling variance. By default, the columns are named yi (effect size) and vi (sampling variance). If append = TRUE, the results are appended to the input data; otherwise, only the computed effect size columns are returned.

Author(s)

Facundo Decunta - fdecunta@agro.uba.ar

References

Shinichi Nakagawa and Daniel Noble, personal communication.

Examples

```
# Pre-post design for standardized mean difference with time interaction (Conservation experiment)
data <- data.frame(
  study_id = 1:2,
  pre_control_mean = c(18.3, 21.7), pre_control_sd = c(4.1, 4.8),
  post_control_mean = c(18.8, 22.1), post_control_sd = c(4.2, 4.9),
  control_n = c(16, 14),
  pre_conservation_mean = c(18.1, 21.4), pre_conservation_sd = c(4.0, 4.7),
  post_conservation_mean = c(26.7, 31.2), post_conservation_sd = c(5.8, 6.4),
  conservation_n = c(15, 16)
)

result <- time_SMD(
  data = data,
  t0_Ctrl_mean = "pre_control_mean", t0_Ctrl_sd = "pre_control_sd",
  t1_Ctrl_mean = "post_control_mean", t1_Ctrl_sd = "post_control_sd",
  Ctrl_n = "control_n", Ctrl_cor = 0.9,
  t0_Exp_mean = "pre_conservation_mean", t0_Exp_sd = "pre_conservation_sd",
  t1_Exp_mean = "post_conservation_mean", t1_Exp_sd = "post_conservation_sd",
  Exp_n = "conservation_n", Exp_cor = 0.7,
  hedges_correction = TRUE
)

# Without Hedges' correction
result_no_hedges <- time_SMD(
  data = data,
  t0_Ctrl_mean = "pre_control_mean", t0_Ctrl_sd = "pre_control_sd",
  t1_Ctrl_mean = "post_control_mean", t1_Ctrl_sd = "post_control_sd",
  Ctrl_n = "control_n", Ctrl_cor = 0.9,
  t0_Exp_mean = "pre_conservation_mean", t0_Exp_sd = "pre_conservation_sd",
  t1_Exp_mean = "post_conservation_mean", t1_Exp_sd = "post_conservation_sd",
  Exp_n = "conservation_n", Exp_cor = 0.7,
  hedges_correction = FALSE
)
```

Index

[lnCVR_ind](#), 2
[lnCVR_inter](#), 4
[lnCVR_main](#), 6
[lnRR_ind](#), 8
[lnRR_inter](#), 10
[lnRR_main](#), 12
[lnVR_ind](#), 14
[lnVR_inter](#), 16
[lnVR_main](#), 17

[SMD_ind](#), 19
[SMD_inter](#), 21
[SMD_main](#), 24

[time_lnCVR](#), 26
[time_lnRR](#), 28
[time_lnVR](#), 30
[time_SMD](#), 32