

Package ‘mixedbiastest’

September 18, 2026

Type Package

Title Bias Diagnostic for Linear Mixed Models

Version 1.0.3

Date 2026-09-18

Maintainer Andrew T. Karl <akar1@asu.edu>

Description Provides a function to perform bias diagnostics on linear mixed models fitted with `lmer()` from the 'lme4' package. Implements permutation tests for assessing the bias of fixed effects, as described in Karl and Zimmerman (2021) <[doi:10.1016/j.jspi.2020.06.004](https://doi.org/10.1016/j.jspi.2020.06.004)>. Karl and Zimmerman (2020) <[doi:10.17632/tmynggddfm.1](https://doi.org/10.17632/tmynggddfm.1)> provide R code for implementing the test using 'mvglmmRank' output. Development of this package was assisted by 'GPT o1-preview' for code structure and documentation.

Depends R (>= 3.5.0)

Imports lme4, Matrix, ggplot2, rlang

Suggests plm, lmerTest, testthat (>= 3.0.0)

License GPL-3

Encoding UTF-8

LazyData true

Config/testthat/edition 3

NeedsCompilation no

Config/roxygen2/version 8.0.0

Author Andrew T. Karl [cre, aut] (ORCID:
<<https://orcid.org/0000-0002-5933-8706>>)

Repository CRAN

Date/Publication 2026-09-18 16:50:02 UTC

Contents

mixedbiastest-package	2
example_data	3

list_fixed_effects	3
mixedbiastest	4
plot.mixedbiastest	7
print.mixedbiastest	7
Index	8

mixedbiastest-package	<i>mixedbiastest: Bias Diagnostics for Linear Mixed Models</i>
-----------------------	--

Description

The ‘mixedbiastest’ package provides a function to perform bias diagnostics on linear mixed models fitted with ‘lmer’ from the ‘lme4’ package. It implements permutation tests for assessing the bias of fixed effects, as described in Karl and Zimmerman (2021).

Details

The methods in this package are designed for Gaussian linear mixed models with diagonal random-effects covariance matrices and homoskedastic residual errors with covariance $\sigma^2 I_n$. Models with more general random-effects structures or residual covariance patterns are currently not supported. While the bias diagnostic of Karl and Zimmerman (2021) is derived for general linear mixed models with arbitrary random-effects and residual covariance matrices G and R , the current **mixedbiastest** implementation focuses on the practically important case described above. Extending the package to handle correlated random effects or more general residual covariance structures would require additional work on both the underlying linear algebra and the permutation scheme, and is therefore left for future research.

Functions

- `mixedbiastest` Performs the bias diagnostic test.
- `print.mixedbiastest` Prints the results of the bias diagnostic.
- `plot.mixedbiastest` Plots the permutation distributions and observed test statistics for each fixed effect.
- `list_fixed_effects` List Fixed Effects from an merMod Object.

Acknowledgments

Development of this package was assisted by GPT o1-preview and GPT 5 Pro, which helped in constructing the structure of much of the code and the roxygen documentation. The code is based on the R code provided by Karl and Zimmerman (2020).

Author(s)

- Maintainer:** Andrew T. Karl <akar1@asu.edu> ([ORCID](#))
- Authors:
- Andrew T. Karl <akar1@asu.edu> ([ORCID](#))

References

Karl, A. T., & Zimmerman, D. L. (2021). A diagnostic for bias in linear mixed model estimators induced by dependence between the random effects and the corresponding model matrix. *Journal of Statistical Planning and Inference*, 212, 70–80. doi:10.1016/j.jspi.2020.06.004

Karl, A., & Zimmerman, D. (2020). Data and Code Supplement for 'A Diagnostic for Bias in Linear Mixed Model Estimators Induced by Dependence Between the Random Effects and the Corresponding Model Matrix'. Mendeley Data, V1. doi:10.17632/tmynggddfm.1

example_data

Example Dataset for the mixedbiastest Package

Description

A dataset containing 97 observations of three variables: y, x, and group.

Usage

```
example_data
```

Format

A data frame with 97 rows and 3 variables:

y Numeric response variable.

x Numeric predictor variable.

group Integer indicating group membership.

list_fixed_effects

List Fixed Effects from a merMod Object

Description

This function lists the fixed effects coefficients from an 'lmerMod'/'merMod' object, providing the index and name of each coefficient. This can help users construct contrast vectors ('k_list') for use with the 'mixedbiastest' function. Only retained model-matrix columns are listed when the fit is rank deficient.

Usage

```
list_fixed_effects(model)
```

Arguments

model An object that inherits from class merMod, such as an lmerMod or glmerMod object fitted using `lmer` or `glmer` from the **lme4** package.

Value

A data frame with two columns:

Index The index of each fixed effect coefficient.

Coefficient The name of each fixed effect coefficient.

Acknowledgments

Development of this package was assisted by GPT o1-preview, which helped in constructing the structure of much of the code and the roxygen documentation. The code is based on the R code provided by Karl and Zimmerman (2020).

Examples

```
if (requireNamespace("plm", quietly = TRUE) && requireNamespace("lme4", quietly = TRUE)) {
  library(lme4)
  data("Gasoline", package = "plm")
  # Fit a random effects model using lme4
  mixed_model <- lmer(lgaspcar ~ lincomep + lrpmpg + lcarpcap + (1 | country),
    data = Gasoline, REML = FALSE)

  # List fixed effects
  fixed_effects <- list_fixed_effects(mixed_model)
  print(fixed_effects)
}
```

mixedbiastest

Bias Diagnostic for Linear Mixed Models

Description

Performs a permutation test to assess the bias of fixed effects in a linear mixed model fitted with [lmer](#). This function computes the test statistic and performs the permutation test, returning an object of class "mixedbiastest".

Usage

```
mixedbiastest(model, n_permutations = 10000, k_list = NULL, verbose = FALSE)
```

Arguments

model	An object of class <code>lmerMod</code> (or a subclass, such as <code>lmerModLmerTest</code>) fitted using lmer from the lme4 package. Models fitted with glmer or with non-identity residual covariance structures (for example, non-unit weights) are not currently supported.
n_permutations	Integer. Number of permutations to perform (default is 10000). Must be a single positive integer no larger than <code>.Machine\$integer.max</code> .

<code>k_list</code>	Optional list of numeric vectors. Each vector specifies a linear combination of fixed effects to test. If <code>NULL</code> , each fixed effect is tested individually. Vectors must be finite and follow the order returned by <code>list_fixed_effects(model)</code> , after any rank-deficient columns are dropped. The list must be nonempty; supplied list names must be nonempty and unique.
<code>verbose</code>	Logical. If <code>TRUE</code> , prints detailed messages during execution.

Details

The implementation follows Karl and Zimmerman (2021) and is currently restricted to:

- Gaussian linear mixed models fitted by `lmer` (no GLMMs).
- Diagonal random-effects covariance matrices (i.e., a block-diagonal G with scalar blocks for each random-effect coefficient), including diagonal terms specified with `diag()` in recent versions of **lme4**.
- Homoskedastic residual errors with covariance $\sigma^2 I_n$ (no observation weights or residual correlation structures).

In particular, models fitted with `glmer` or with non-identity residual covariance structures (for example, non-unit observation weights) are beyond the scope of the current implementation.

Random effects are permuted separately within each coefficient of each random-effects term. Automatically scaled fixed-effect predictors are handled on the original coefficient scale, including the intercept adjustment. A singular fit produces a warning; zero variance components are retained as zero. Results retain full numerical precision. The two-sided permutation p-value uses the correction $(1 + B)/(1 + M)$, where B is the number of sampled absolute statistics at least as large as the observed absolute statistic, and M is `n_permutations`. Use `set.seed()` before calling this function for reproducible permutations.

While the diagnostic of Karl and Zimmerman (2021) is formulated for general linear mixed models with arbitrary covariance matrices G and R , this function implements the special case of Gaussian `lmer` models with diagonal G and homoskedastic residual errors. Extending `mixedbiastest()` to correlated random effects or more general residual covariance structures would require substantial additional work on the underlying linear algebra and permutation scheme, and is left for future research.

See the `list_fixed_effects` function if you would like to construct contrasts of fixed effects to be used as `k_list`.

Value

An object of class `"mixedbiastest"` containing:

`results_table` A data frame with the test results for each fixed effect or contrast, including bias estimates and permutation p-values.

`permutation_values` A list of numeric vectors containing permutation values for each fixed effect or contrast.

`model` The original `lmerMod` model object provided as input.

Acknowledgments

Development of this package was assisted by GPT o1-preview and GPT 5 Pro, which helped in constructing the structure of much of the code and the roxygen documentation. The code is based on the R code provided by Karl and Zimmerman (2020).

References

Karl, A. T., & Zimmerman, D. L. (2021). A diagnostic for bias in linear mixed model estimators induced by dependence between the random effects and the corresponding model matrix. *Journal of Statistical Planning and Inference*, 212, 70-80. doi:10.1016/j.jspi.2020.06.004

Karl, A., & Zimmerman, D. (2020). Data and Code Supplement for "A Diagnostic for Bias in Linear Mixed Model Estimators Induced by Dependence Between the Random Effects and the Corresponding Model Matrix". Mendeley Data, V1. doi:10.17632/tmynggddfm.1

Examples

```
if (requireNamespace("plm", quietly = TRUE) && requireNamespace("lme4", quietly = TRUE)) {
  library(lme4)
  data("Gasoline", package = "plm")
  mixed_model <- lmer(lgaspcar ~ lincomep + lrpmpg + lcarpcap + (1 | country),
    data = Gasoline)
  result <- mixedbiastest(mixed_model)
  print(result); plot(result)
}
if (requireNamespace("lme4", quietly = TRUE)) {
  library(lme4)
  example_model <- lmer(y ~ x + (1 | group), data = example_data)
  result2 <- mixedbiastest(example_model)
  print(result2); plot(result2)

  # Simulate data
  set.seed(123)
  n_groups <- 30
  n_obs_per_group <- 10
  group <- rep(1:n_groups, each = n_obs_per_group)
  x <- runif(n_groups * n_obs_per_group)
  beta0 <- 2; beta1 <- 5
  sigma_u <- 1; sigma_e <- 0.5
  u <- rnorm(n_groups, 0, sigma_u)
  e <- rnorm(n_groups * n_obs_per_group, 0, sigma_e)
  y <- beta0 + beta1 * x + u[group] + e

  data_sim <- data.frame(y = y, x = x, group = factor(group))
  model3 <- lmer(y ~ x + (1 | group), data = data_sim)
  result3 <- mixedbiastest(model3, verbose = TRUE)
  plot(result3)
}
```

plot.mixedbiastest	<i>Plot Method for Bias Diagnostic Results</i>
--------------------	--

Description

Plots the permutation distributions and observed test statistics for each fixed effect.

Usage

```
## S3 method for class 'mixedbiastest'
plot(x, bins = 30, ...)
```

Arguments

x	An object of class "mixedbiastest".
bins	Integer, number of bins for the histograms (default 30).
...	Additional arguments (currently not used).

Value

A ggplot object (returned invisibly) showing permutation distributions for all fixed effects.

print.mixedbiastest	<i>Print Method for Bias Diagnostic Results</i>
---------------------	---

Description

Prints the results of the bias diagnostic in a formatted table.

Usage

```
## S3 method for class 'mixedbiastest'
print(x, ...)
```

Arguments

x	An object of class "mixedbiastest".
...	Additional arguments (currently not used).

Value

The input object, returned invisibly.

Index

* **datasets**

example_data, [3](#)

example_data, [3](#)

glmer, [3–5](#)

list_fixed_effects, [2, 3, 5](#)

lmer, [3–5](#)

mixedbiastest, [2, 4](#)

mixedbiastest-package, [2](#)

plot.mixedbiastest, [2, 7](#)

print.mixedbiastest, [2, 7](#)