

Package ‘rjd3providers’

September 23, 2026

Type Package

Title Interface to 'JDemetra+' 3.x Time Series Analysis Software

Version 3.9.0

Description Interface to 'JDemetra+' 3.x (<<https://github.com/jdemetra>>) time series analysis software. It offers full access to txt, csv, xml and spreadsheets files which are meant to be read by 'JDemetra+' Graphical User Interface.

License EUPL

URL <https://github.com/rjdverse/rjd3providers>,
<https://rjdverse.github.io/rjd3providers/>

BugReports <https://github.com/rjdverse/rjd3providers/issues>

Depends R (>= 4.1.0)

Imports rJava (>= 1.0-6), rjd3jars (>= 0.0.6), rjd3toolkit (>= 3.9.0)

Suggests spelling

Config/roxygen2/version 8.1.0

Encoding UTF-8

Language en-GB

SystemRequirements Java (>= 21)

Collate 'providers.R' 'jd3spreadsheet.R' 'jd3txt.R' 'jd3xml.R'
'options.R' 'rjd3providers-package.R' 'zzz.R'

RoxygenNote 7.3.3

NeedsCompilation no

Author Jean Palate [aut],
Alessandro Piovani [aut, cre, cph],
Tanguy Barthelemy [aut, art],
Eulalie Delaune [aut]

Maintainer Alessandro Piovani <alessandro.piovani@istat.it>

Repository CRAN

Date/Publication 2026-09-23 14:10:02 UTC

Contents

.obs_format 2

.obs_gathering 3

.spreadsheet_moniker 4

.txt_moniker 5

.xml_moniker 5

get_providers_option 6

providers_option 6

set_spreadsheet_paths 7

set_txt_paths 7

set_xml_paths 8

spreadsheet_change_file 8

spreadsheet_content 9

spreadsheet_data 10

spreadsheet_id_to_properties 11

spreadsheet_name 12

spreadsheet_properties_to_id 12

spreadsheet_series 13

txt_change_file 14

txt_content 15

txt_data 16

txt_id_to_properties 18

txt_name 18

txt_properties_to_id 19

txt_series 20

xml_change_file 21

xml_content 22

xml_data 23

xml_id_to_properties 23

xml_name 24

xml_properties_to_id 25

xml_series 25

Index 27

.obs_format	<i>Generates the Java object for data formats</i>
-------------	---

Description

Generates the Java object for data formats

Usage

```
.obs_format(  
  locale = NULL,  
  dateFmt = NULL,  
  numberFmt = NULL,  
  ignoreNumberGrouping = TRUE  
)
```

Arguments

<code>locale</code>	Locale language. Null to use the default
<code>dateFmt</code>	Format of the date. Null to use the default of the locale
<code>numberFmt</code>	Format of the number. Null to use the default of the locale
<code>ignoreNumberGrouping</code>	Ignore number grouping

Value

An internal Java object.

Examples

```
.obs_format(locale = "french-be")
```

<code>.obs_gathering</code>	<i>Generates the Java object for automatic aggregation of the data</i>
-----------------------------	--

Description

Generates the Java object for automatic aggregation of the data

Usage

```
.obs_gathering(  
  period = 0,  
  aggregationType = NULL,  
  allowPartialAggregation = FALSE,  
  cleanMissing = TRUE  
)
```

Arguments

period	The annual frequency of the series. If 0, the frequency.
aggregationType	The type of the aggregation to be applied on the series (only used if "period" is different from 0).
allowPartialAggregation	Specifies if the aggregation is performed or not when they are missing periods.
cleanMissing	Specifies if missing values at the beginning and at the end of the data are removed from the series.

Value

An internal Java object.

Examples

```
.obs_gathering(period=4, aggregationType="Sum")
```

`.spreadsheet_moniker` *Generates a java moniker for the corresponding id.*

Description

Generates a java moniker for the corresponding id.

Usage

```
.spreadsheet_moniker(id)
```

Arguments

id	Identifier of the requested information.
----	--

Value

An internal Java moniker.

Examples

```
.spreadsheet_moniker("toy_id")
```

.txt_moniker	<i>Generates a java moniker for the corresponding id.</i>
--------------	---

Description

Generates a java moniker for the corresponding id.

Usage

```
.txt_moniker(id)
```

Arguments

id	Identifier of the requested information.
----	--

Value

An internal java moniker.

Examples

```
.txt_moniker("toy_id")
```

.xml_moniker	<i>Generates a java moniker for the corresponding id.</i>
--------------	---

Description

Generates a java moniker for the corresponding id.

Usage

```
.xml_moniker(id)
```

Arguments

id	Identifier of the requested information.
----	--

Value

An internal java moniker.

Examples

```
.xml_moniker("toy_id")
```

get_providers_option	Set an option for providers
----------------------	-----------------------------

Description

Set an option for providers

Usage

```
get_providers_option(name)
```

Arguments

name	Name of the option
------	--------------------

Value

The requested option or NULL if it doesn't exist

Examples

```
providers_option("test", "DUMMY")  
get_providers_option("test")
```

providers_option	Set an option for providers
------------------	-----------------------------

Description

Set an option for providers

Usage

```
providers_option(name, obj)
```

Arguments

name	Name of the option
obj	Option

Value

Invisibly NULL

Examples

```
providers_option("test", "DUMMY")
```

set_spreadsheet_paths *Set the paths to spreadsheet files (to be used with relative identifiers).*

Description

Set the paths to spreadsheet files (to be used with relative identifiers).

Usage

```
set_spreadsheet_paths(paths)
```

Arguments

paths The folders containing the spreadsheet files Only used in relative addresses.

Value

No output.

Examples

```
set_spreadsheet_paths(system.file("extdata", package = "rjd3providers"))
```

set_txt_paths *Set the paths to txt files (to be used with relative identifiers)*

Description

Set the paths to txt files (to be used with relative identifiers)

Usage

```
set_txt_paths(paths)
```

Arguments

paths The folders containing the txt files Only used in relative addresses.

Value

An internal java moniker

Examples

```
set_txt_paths(system.file("extdata", package = "rjd3providers"))
```

set_xml_paths	<i>Set the paths to xml files (to be used with relative identifiers).</i>
---------------	---

Description

Set the paths to xml files (to be used with relative identifiers).

Usage

```
set_xml_paths(paths)
```

Arguments

paths	The folders containing the xml files. Only used in relative addresses.
-------	--

Value

No output.

Examples

```
set_xml_paths(system.file("extdata", package = "rjd3providers"))
```

spreadsheet_change_file	<i>Change the file of a spreadsheet moniker.</i>
-------------------------	--

Description

Change the file of a spreadsheet moniker.

Usage

```
spreadsheet_change_file(id, nfile, ofile = NULL)
```

Arguments

id	Identifier of a series or of a collection of series.
nfile	New file name.
ofile	Old file name. NULL or "" to change any file to the new file.

Value

Returns the new identifier.

Examples

```
set_spreadsheet_paths(system.file("extdata", package = "rjd3providers"))
xls_all <- spreadsheet_data("Insee.xlsx", 1)
id<-xls_all$moniker$id
spreadsheet_change_file(id, "test.xlsx")
```

spreadsheet_content	<i>Provides the content of a spreadsheet designed for time series.</i>
---------------------	--

Description

Provides the content of a spreadsheet designed for time series.

Usage

```
spreadsheet_content(file)
```

Arguments

file	The considered workbook.
------	--------------------------

Value

Provides all the names of the time series contained in the workbook, organized by worksheet; the output is a list of lists of names.

Examples

```
set_spreadsheet_paths(system.file("extdata", package = "rjd3providers"))
print(spreadsheet_content("Insee.xlsx"))
```

spreadsheet_data	<i>Retrieves all the time series in a specified sheet from a spreadsheet file.</i>
------------------	--

Description

Retrieves all the time series in a specified sheet from a spreadsheet file.

Usage

```
spreadsheet_data(
  file,
  sheet = 1,
  gathering.period = 0,
  gathering.aggregation = c("None", "Sum", "Average", "First", "Last", "Max", "Min"),
  gathering.partialAggregation = FALSE,
  gathering.cleanMissing = TRUE,
  fullNames = FALSE
)
```

Arguments

file	The spreadsheet file.
sheet	The name or the 1-based position of the sheet containing the requested data.
gathering.period	The annual frequency of the transformed series. If 0, the actual frequency is used.
gathering.aggregation	The type of the aggregation to be applied on the series (only used if "period" is different from 0).
gathering.partialAggregation	Specifies if the aggregation is performed or not when they are missing periods.
gathering.cleanMissing	Specifies if missing values at the beginning or at the end of the data are removed from the series.
fullNames	Specifies if full names (containing the name of the sheet and the name of the series) are used or not.

Value

A ts collection with all the series.

Examples

```
set_spreadsheet_paths(system.file("extdata", package = "rjd3providers"))
xls_all <- spreadsheet_data("Insee.xlsx", 1)
```

```
txt_all <- spreadsheet_data("Insee.xlsx", "FRANCE Textile")
```

spreadsheet_id_to_properties

Gets the list of the properties corresponding to the identifier of a moniker.

Description

Gets the list of the properties corresponding to the identifier of a moniker.

Usage

```
spreadsheet_id_to_properties(id)
```

Arguments

id Identifier of a series or of a collection of series.

Details

When the period in the gathering list is defined, the user must specify the aggregation type ("Sum", "Average", "First", "Last", "Min", "Max") and some additional parameters (partial aggregation and suppression of leading/trailing missing values).

Value

Returns a list with the elements of the id: file, sheet, series, gathering); the gathering is a list with the following items: period (-1 by default), the aggregation ("None"), partialAggregation (FALSE), includeMissing (FALSE).

See Also

[spreadsheet_properties_to_id\(\)](#)

Examples

```
set_spreadsheet_paths(system.file("extdata", package = "rjd3providers"))
xls_s1_3 <- spreadsheet_series("Insee.xlsx", 1, 3)
id<-xls_s1_3$moniker$id
print(spreadsheet_id_to_properties(id))
```

spreadsheet_name	<i>Gets the name of the spreadsheet provider.</i>
------------------	---

Description

Gets the name of the spreadsheet provider.

Usage

```
spreadsheet_name()
```

Value

The name of the spreadsheet provider, to be used in monikers.

Examples

```
print(spreadsheet_name())
```

spreadsheet_properties_to_id	<i>Generates the id corresponding to a list of spreadsheet properties.</i>
------------------------------	--

Description

Generates the id corresponding to a list of spreadsheet properties.

Usage

```
spreadsheet_properties_to_id(props)
```

Arguments

props	The properties defining the identifier.
-------	---

Value

The identifier corresponding to the properties.

Examples

```
set_spreadsheet_paths(system.file("extdata", package = "rjd3providers"))
xls_s1_3 <- spreadsheet_series("Insee.xlsx", 1, 3)
id<-xls_s1_3$moniker$id
source<-spreadsheet_name()
props<-spreadsheet_id_to_properties(xls_s1_3$moniker$id)
props$gathering$period<-4
props$gathering$aggregation<-"Max"
M<-rjd3toolkit::to_ts(spreadsheet_name(), spreadsheet_properties_to_id(props))
props$gathering$aggregation<-"Min"
m<-rjd3toolkit::to_ts(spreadsheet_name(), spreadsheet_properties_to_id(props))
ts.plot(ts.union(M$data,m$data), col=c("red", "blue"))
```

spreadsheet_series	<i>Retrieves a time series from a spreadsheet file.</i>
--------------------	---

Description

Retrieves a time series from a spreadsheet file.

Usage

```
spreadsheet_series(
  file,
  sheet = 1,
  series = 1,
  gathering.period = 0,
  gathering.aggregation = c("None", "Sum", "Average", "First", "Last", "Max", "Min"),
  gathering.partialAggregation = FALSE,
  gathering.cleanMissing = TRUE,
  fullName = TRUE
)
```

Arguments

file	The spreadsheet file.
sheet	The name or the 1-based position of the sheet containing the requested data.
series	The name or the 1-based position of the series in the selected sheet.
gathering.period	The annual frequency of the transformed series. If 0, the actual frequency is used.
gathering.aggregation	The type of the aggregation to be applied on the series (only used if "period" is different from 0).

txt_content	<i>Provides the content of a text file designed for time series</i>
-------------	---

Description

Provides the content of a text file designed for time series

Usage

```
txt_content(
  file,
  fmt.locale = NULL,
  fmt.date = NULL,
  fmt.number = NULL,
  fmt.ignoreNumberGrouping = TRUE,
  gathering.period = 0,
  gathering.aggregation = c("None", "Sum", "Average", "First", "Last", "Max", "Min"),
  gathering.partialAggregation = FALSE,
  gathering.cleanMissing = TRUE,
  charset = NULL,
  delimiter = c("TAB", "SEMICOLON", "COMMA", "SPACE"),
  txtQualifier = c("NONE", "QUOTE", "DOUBLE_QUOTE"),
  header = TRUE,
  skip = 0
)
```

Arguments

file	The text file
fmt.locale	Locale language. Null to use the default
fmt.date	Format of the date. Null to use the default of the locale
fmt.number	Format of the number. Null to use the default of the locale
fmt.ignoreNumberGrouping	Ignore number grouping
gathering.period	The annual frequency of the series. If 0, the frequency
gathering.aggregation	The type of the aggregation to be applied on the series (only used if "period" is different from 0)
gathering.partialAggregation	Specifies if the aggregation is performed or not when they are missing periods
gathering.cleanMissing	Specifies if missing values at the beginning or at the end of the data are removed from the series.
charset	Specifies the charset

delimiter	Specifies the delimiter. Should be in ("TAB", "SEMICOLON", "COMMA", "SPACE")
txtQualifier	Character used to qualify text. Should be in ("NONE", "QUOTE", "DOUBLE_QUOTE")
header	The file contains headers
skip	Skips some lines

Value

Provides all the names of the time series contained in the text file

Examples

```
set_txt_paths(system.file("extdata", package = "rjd3providers"))
txt_all <- txt_content("ABS.csv", delimiter = "COMMA")
```

txt_data	<i>Retrieves all the time series in a text file (.txt, .csv...)</i>
----------	---

Description

Retrieves all the time series in a text file (.txt, .csv...)

Usage

```
txt_data(
  file,
  fmt.locale = NULL,
  fmt.date = NULL,
  fmt.number = NULL,
  fmt.ignoreNumberGrouping = TRUE,
  gathering.period = 0,
  gathering.aggregation = c("None", "Sum", "Average", "First", "Last", "Max", "Min"),
  gathering.partialAggregation = FALSE,
  gathering.cleanMissing = TRUE,
  charset = NULL,
  delimiter = c("TAB", "SEMICOLON", "COMMA", "SPACE"),
  txtQualifier = c("NONE", "QUOTE", "DOUBLE_QUOTE"),
  header = TRUE,
  skip = 0
)
```

Arguments

file	The text file
fmt.locale	Locale language. Null to use the default
fmt.date	Format of the date. Null to use the default of the locale
fmt.number	Format of the number. Null to use the default of the locale
fmt.ignoreNumberGrouping	Ignore number grouping
gathering.period	The annual frequency of the transformed series. If 0, the actual frequency is used.
gathering.aggregation	The type of the aggregation to be applied on the series (only used if "period" is different from 0)
gathering.partialAggregation	Specifies if the aggregation is performed or not when they are missing periods
gathering.cleanMissing	Specifies if missing values at the beginning or at the end of the data are removed from the series.
charset	Specifies the charset
delimiter	Specifies the delimiter. Should be in ("TAB", "SEMICOLON", "COMMA", "SPACE")
txtQualifier	Character used to qualify text. Should be in ("NONE", "QUOTE", "DOUBLE_QUOTE")
header	The file contains headers
skip	Skips some lines

Value

A ts collection with all the series

Examples

```
set_txt_paths(system.file("extdata", package = "rjd3providers"))
all <- txt_data("ABS.csv", delimiter = "COMMA")
```

txt_id_to_properties	<i>Gets the list of the properties corresponding to the identifier of a moniker</i>
----------------------	---

Description

Gets the list of the properties corresponding to the identifier of a moniker

Usage

```
txt_id_to_properties(id)
```

Arguments

id	Identifier of a series or of a collection of series.
----	--

Value

Returns a list with the elements of the id: file , series, format, gathering,

Examples

```
set_txt_paths(system.file("extdata", package = "rjd3providers"))
txt_15 <- txt_series("ABS.csv", series = 15, delimiter = "COMMA")
id<-txt_15$moniker$id
print(txt_id_to_properties(id))
```

txt_name	<i>Gets the name of the text provider</i>
----------	---

Description

Gets the name of the text provider

Usage

```
txt_name()
```

Value

The name of the text provider, to be used in monikers

Examples

```
txt_name()
```

```
txt_properties_to_id
```

Generates the id corresponding to a list of a text properties.

Description

Generates the id corresponding to a list of a text properties.

Usage

```
txt_properties_to_id(props)
```

Arguments

props The properties defining the identifier.

Value

The identifier corresponding to the properties.

Examples

```
set_txt_paths(system.file("extdata", package = "rjd3providers"))
txt_15 <- txt_series("ABS.csv", series = 15, delimiter = "COMMA")
id<-txt_15$moniker$id
source<-txt_name()
props<-txt_id_to_properties(id)
props$gathering$period<-4
props$gathering$aggregation<-"Max"
M<-rjd3toolkit::to_ts(txt_name(), txt_properties_to_id(props))
props$gathering$aggregation<-"Min"
m<-rjd3toolkit::to_ts(txt_name(), txt_properties_to_id(props))
ts.plot(ts.union(M$data,m$data), col=c("red", "blue"))
```

txt_series

*Retrieves a time series from a a text file (.txt, .csv...)***Description**

Retrieves a time series from a a text file (.txt, .csv...)

Usage

```
txt_series(
  file,
  series,
  fmt.locale = NULL,
  fmt.date = NULL,
  fmt.number = NULL,
  fmt.ignoreNumberGrouping = TRUE,
  gathering.period = 0,
  gathering.aggregation = c("None", "Sum", "Average", "First", "Last", "Max", "Min"),
  gathering.partialAggregation = FALSE,
  gathering.cleanMissing = TRUE,
  charset = NULL,
  delimiter = c("TAB", "SEMICOLON", "COMMA", "SPACE"),
  txtQualifier = c("NONE", "QUOTE", "DOUBLE_QUOTE"),
  header = TRUE,
  skip = 0
)
```

Arguments

file	The text file
series	The name or the 1-based position of the series in the selected sheet
fmt.locale	Locale language. Null to use the default
fmt.date	Format of the date. Null to use the default of the locale
fmt.number	Format of the number. Null to use the default of the locale
fmt.ignoreNumberGrouping	Ignore number grouping
gathering.period	The annual frequency of the transformed series. If 0, the actual frequency is used.
gathering.aggregation	The type of the aggregation to be applied on the series (only used if "period" is different from 0)
gathering.partialAggregation	Specifies if the aggregation is performed or not when they are missing periods

gathering.cleanMissing	Specifies if missing values at the beginning or at the end of the data are removed from the series.
charset	Specifies the charset
delimiter	Specifies the delimiter. Should be in ("TAB", "SEMICOLON", "COMMA", "SPACE")
txtQualifier	Character used to qualify text. Should be in ("NONE", "QUOTE", "DOUBLE_QUOTE")
header	The file contains headers
skip	Skips some lines

Value

Returns the specified time series

Examples

```
set_txt_paths(system.file("extdata", package = "rjd3providers"))
txt_15 <- txt_series("ABS.csv", series = 15, delimiter = "COMMA")
txt_09 <- txt_series("ABS.csv", series = "0.2.09.10.M", delimiter = "COMMA")
```

xml_change_file	<i>Change the file of an xml moniker.</i>
-----------------	---

Description

Change the file of an xml moniker.

Usage

```
xml_change_file(id, nfile, ofile = NULL)
```

Arguments

id	Identifier of a series or of a collection of series.
nfile	New file name.
ofile	Old file name. NULL or "" to change any file to the new file.

Value

The new identifier.

Examples

```
set_xml_paths(system.file("extdata", package = "rjd3providers"))
xml_1_5 <- xml_series("Prod.xml", 1, 5, charset = "iso-8859-1")
id<-xml_1_5$moniker$id
xml_change_file(id, "test.xml")
```

xml_content

Provides the content of an xml file designed for time series.

Description

Provides the content of an xml file designed for time series.

Usage

```
xml_content(file, charset = NULL)
```

Arguments

file	The considered file.
charset	The character set used in the file (NULL to use the default).

Value

Provides all the names of the time series contained in the file, grouped by collection.

Examples

```
set_xml_paths(system.file("extdata", package = "rjd3providers"))
xml_content("Prod.xml")
print(xml_content)
```

xml_data	<i>Retrieves all the time series in a specified collection from an xml file.</i>
----------	--

Description

Retrieves all the time series in a specified collection from an xml file.

Usage

```
xml_data(file, collection = 1, charset = NULL, fullNames = FALSE)
```

Arguments

file	The xml file.
collection	The name or the 1-based position of the collection containing the requested data.
charset	The character set used in the file
fullNames	Specifies if full names (containing the name of the sheet and the name of the series) are used or not.

Value

A ts collection with all the series.

Examples

```
set_xml_paths(system.file("extdata", package = "rjd3providers"))
xml_1 <- xml_data("Prod.xml", 1, charset = "iso-8859-1")
xml_all <- xml_data("Prod.xml", "industrial production", charset = "iso-8859-1")
```

xml_id_to_properties	<i>Gets the list of the properties corresponding to the identifier of a moniker.</i>
----------------------	--

Description

Gets the list of the properties corresponding to the identifier of a moniker.

Usage

```
xml_id_to_properties(id)
```

Arguments

id Identifier of a series or of a collection of series.

Value

Returns a list with the elements of the id: file, collection, series, charset, fullnames.

Examples

```
set_xml_paths(system.file("extdata", package = "rjd3providers"))
xml_1_5 <- xml_series("Prod.xml", 1, 5, charset = "iso-8859-1")
xml_id_to_properties(xml_1_5$moniker$id)
xml_1 <- xml_data("Prod.xml", 1, charset = "iso-8859-1")
xml_id_to_properties(xml_1$moniker$id)
```

xml_name

Gets the name of the xml provider.

Description

Gets the name of the xml provider.

Usage

```
xml_name()
```

Value

The name of the xml provider, to be used in monikers.

Examples

```
xml_name()
```

xml_properties_to_id *Generates the id corresponding to a list of an xml properties.*

Description

Generates the id corresponding to a list of an xml properties.

Usage

```
xml_properties_to_id(props)
```

Arguments

props The properties defining the identifier.

Value

The identifier corresponding to the properties.

Examples

```
set_xml_paths(system.file("extdata", package = "rjd3providers"))
xml_1_5 <- xml_series("Prod.xml", 1, 5, charset = "iso-8859-1")
q <- xml_id_to_properties(xml_1_5$moniker$id)
q$series <- 50
xml_properties_to_id(q)
```

xml_series *Retrieves a time series from an xml file*

Description

Retrieves a time series from an xml file

Usage

```
xml_series(file, collection = 1, series = 1, charset = NULL, fullName = TRUE)
```

Arguments

file	The xml file.
collection	The name or the 1-based position of the collection containing the requested data.
series	The name or the 1-based position of the series in the selected collection.
charset	The character set used in the file.
fullName	Specifies if a full name (containing the name of the collection and the name of the series) is used or not.

Value

Returns the specified time series

Examples

```
set_xml_paths(system.file("extdata", package = "rjd3providers"))
xml_1_5 <- xml_series("Prod.xml", 1, 5, charset = "iso-8859-1")
xml_cn <- xml_series("Prod.xml", "industrial production",
  "Construction navale", charset = "iso-8859-1")
```

Index

.obs_format, [2](#)
.obs_gathering, [3](#)
.spreadsheet_moniker, [4](#)
.txt_moniker, [5](#)
.xml_moniker, [5](#)

get_providers_option, [6](#)

providers_option, [6](#)

set_spreadsheet_paths, [7](#)
set_txt_paths, [7](#)
set_xml_paths, [8](#)
spreadsheet_change_file, [8](#)
spreadsheet_content, [9](#)
spreadsheet_data, [10](#)
spreadsheet_id_to_properties, [11](#)
spreadsheet_name, [12](#)
spreadsheet_properties_to_id, [12](#)
spreadsheet_properties_to_id(), [11](#)
spreadsheet_series, [13](#)

txt_change_file, [14](#)
txt_content, [15](#)
txt_data, [16](#)
txt_id_to_properties, [18](#)
txt_name, [18](#)
txt_properties_to_id, [19](#)
txt_series, [20](#)

xml_change_file, [21](#)
xml_content, [22](#)
xml_data, [23](#)
xml_id_to_properties, [23](#)
xml_name, [24](#)
xml_properties_to_id, [25](#)
xml_series, [25](#)