

Package ‘rjd3workspace’

September 29, 2026

Type Package

Title Wrangling 'JDemetra+ 3.x' Workspaces

Version 3.9.0

Description R Interface to 'JDemetra+ 3.x'(<<https://github.com/jdemetra>>). It offers several functions to manipulate 'JDemetra+' workspaces, which can be read by the software and can store several seasonal adjusted series along with user-defined calendars or regression variables.

License EUPL

URL <https://github.com/rjdverse/rjd3workspace>,
<https://rjdverse.github.io/rjd3workspace/>

BugReports <https://github.com/rjdverse/rjd3workspace/issues>

Depends R (>= 4.1.0)

Imports methods, rJava (>= 1.0-6), rjd3jars (>= 0.0.6), rjd3providers (>= 3.9.0), rjd3toolkit (>= 3.9.0), rjd3tramoseats (>= 3.9.0), rjd3x13 (>= 3.9.0), tools, utils

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/roxygen2/version 8.1.0

Config/testthat/edition 3

Encoding UTF-8

SystemRequirements Java (>= 21)

Collate 'deprecated.R' 'rjd3workspace-package.R' 'utils.R' 'saitem.R' 'saprocessing.R' 'update_path.R' 'workspace.R' 'zzz.R'

NeedsCompilation no

Author Jean Palate [aut],
Alain Quartier-la-Tente [aut] (ORCID:
<<https://orcid.org/0000-0001-7890-3857>>),
Tanguy Barthelemy [aut, cre, art],
Anna Smyk [aut],
Eulalie Delaune [aut]

Maintainer Tanguy Barthelemy <timeserieswithjdemetraandr@gmail.com>

Repository CRAN

Date/Publication 2026-09-29 12:40:02 UTC

Contents

.jd2r_spec	3
add_calendar	3
add_sa_item	4
add_variables	6
deprecated-rjd3workspace	7
get-results	10
get-specification	11
get_context	12
get_metadata	12
jsap_make_copy	13
jsap_refresh	14
jsap_sai	17
jws_add	18
jws_compute	18
jws_new	19
jws_open	20
read_calendars	21
read_sai	21
read_sap	22
read_variables	23
regarima_read_spec	24
regarima_write_spec	25
replace_sa_item	25
sai_name	26
sap_sai_count	27
save_workspace	28
set_comment	29
set_context	30
set_name	31
set_priority	32
set_raw_data	33
set_specification	34
set_ts	35
set_ts_metadata	36
spreadsheet_update_path	37
tramoseats_read_spec	38
tramoseats_write_spec	39
tramo_read_spec	39
tramo_write_spec	40
transfer_sa_item	41
txt_update_path	42

Examples

```

library("rjd3toolkit")

# French calendar
french_calendar <- national_calendar(
  days = list(
    # Bastille Day
    fixed_day(7, 14),
    # End of 2nd WW
    fixed_day(5, 8, validity = list(start = "1982-05-08")),
    special_day("NEWYEAR"),
    special_day("CHRISTMAS"),
    special_day("MAYDAY"),
    special_day("EASTERMONDAY"),
    special_day("ASCENSION"),
    special_day("WHITMONDAY"),
    special_day("ASSUMPTION"),
    special_day("ALLSAINTSDAY"),
    special_day("ARMISTICE")
  )
)

# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
  package = "rjd3workspace")

jws <- jws_open(file)

# Add calendar to the workspace
add_calendar(jws, "French Calendar", french_calendar)
get_context(jws) # The workspace already contained a Test Calendar

```

add_sa_item

Add a SA-item to a SAProcessing

Description

Add a SA-item to a SAProcessing

Usage

```

add_sa_item(jsap, name, x, spec)

## S3 method for class 'ts'
add_sa_item(jsap, name, x, spec)

## Default S3 method:

```

```
add_sa_item(jsap, name, x, spec)

## S3 method for class 'jobRef'
add_sa_item(jsap, name, x, spec)
```

Arguments

jsap	SAProcessing.
name	name of the SA-item to be added.
x	either a seasonal adjustment model (from <code>rjd3x13::x13()</code> or <code>rjd3tramoseats::tramoseats()</code>), a SA-item object, "ts" object.
spec	specification to use when x is a "ts" object.

Value

NULL returned invisibly#'

Examples

```
dir <- tempdir()

# Raw series
y <- rjd3toolkit::ABS$X0.2.09.10.M

# Creating an empty workspace and SAProcessing
jws <- jws_new()
jsap1 <- jws_sap_new(jws, "sap1")

# Adding SA-item as estimation result

# Estimation with rjd3x13
add_sa_item(jsap1, name = "series_1", x = rjd3x13::x13(y))

# Estimation with rjd3tramoseats
add_sa_item(jsap1, name = "series_2", x = rjd3tramoseats::tramoseats(y))

# Adding SA-item as raw series + specification
add_sa_item(jsap1, name = "series_3", x = y, rjd3x13::x13_spec("RSA3"))
add_sa_item(jsap1, name = "series_4", x = y, rjd3tramoseats::tramoseats_spec("RSAFull"))

jsai1 <- jsap_sai(jsap = jsap1, idx = 1L)
# Adding SA-item from a Workspace
add_sa_item(jsap = jsap1, name = "series_1_bis", x = jsai1)

rws <- read_workspace(jws)
rws$processing$sap1$series_4

# Writing the workspace
save_workspace(jws, file.path(dir, "workspace.xml"))
```

add_variables	<i>Add a Variable to a JD+ Workspace</i>
---------------	--

Description

Adds a single time series variable to a specified group within a JD+ workspace..

Usage

```
add_variables(jws, ...)
```

Arguments

jws	A JD+ workspace object (Java pointer).
...	Additional arguments passed to <code>rjd3toolkit::complete_modelling_context()</code> as:
group	A character string indicating the name of the group in which to store the variable.
y	A ts object (R time series) to be added. Only a single time series can be added at a time.
name	A character string naming the variable.
overwrite	a Boolean to indicate whether a variable already present should be replaced

Details

For the time being, if the group does not already exist, a new group is created, but the group will be named after name, not group.

Value

No return value (NULL returned invisibly). This function is used for its side effect of modifying the workspace.

Limitations

- Cannot add multiple variables at once.
- Does not support dynamic ts objects with metadata.
- If group does not exist, a new group is created but named after the variable name, not the intended group.

See Also

`rjd3toolkit::modelling_context()` to create multiple variables and groups at once, and `read_variables()`, `write_variables()` to import/export variables.

Examples

```
# Create a Workspace
my_ws <- jws_new()

# Add one variable
add_variables(
  jws = my_ws,
  group = "reg1",
  y = AirPassengers,
  name = "x1"
)

# Add 2 named variables
add_variables(
  jws = my_ws,
  group = "reg1",
  y = list(a = mdeaths, b = ldeaths),
  name = "DeathMale"
)

# Add a list of variables (or a MTS)
add_variables(
  jws = my_ws,
  group = "reg1",
  y = rjd3toolkit::ABS
)
add_variables(
  jws = my_ws,
  group = "reg1",
  y = Seatbelts
)
```

deprecated-rjd3workspace

Deprecated functions

Description

Deprecated functions

Usage

```
.jmp_sa_count(jmp)
.jsap_sa_count(jmp)
.jsap_sai_count(jsap)
.jmp_name(jmp)
.jsap_name(jsap)
.jmp_sa(jmp, idx)
.jsap_sa(jsap, idx)
.jsap_sai(jsap, idx)
.jmp_sa_name(jmp)
.jsap_sa_name(jsap)
.jsap_sai_names(jsap)
.jmp_load(jmp)
.jsa_read(jsa)
.jsa_results(jsa, items = NULL)
.jsai_results(jsa, items = NULL)
.jsa_jresults(jsa)
.jsai_jresults(jsa)
.jsa_metadata(jsa, key)
.jsai_metadata(jsai, key)
.jsa_ts_metadata(jsa, key)
.jsai_ts_metadata(jsa, key)
.jws_sap_count(jws)
.jws_open(file)
.jread_workspace(jws, compute = TRUE)
```

```
.jread_sap(jsap)

.jws_new(modelling_context = NULL)

.jws_sap_new(jws, name)

.jws_make_copy(jws)

.jsap_make_copy(jsap)

.jws_compute(jws)

.jws_sap(jws, idx)

.jsai_name(jsai)

.jsap_refresh(
  jsap,
  policy = c("FreeParameters", "Complete", "Outliers_StochasticComponent", "Outliers",
    "FixedParameters", "FixedAutoRegressiveParameters", "Fixed"),
  period = 0,
  start = NULL,
  end = NULL,
  info = c("All", "Data", "None")
)

.jws_refresh(
  jws,
  policy = c("FreeParameters", "Complete", "Outliers_StochasticComponent", "Outliers",
    "FixedParameters", "FixedAutoRegressiveParameters", "Fixed"),
  period = 0,
  start = NULL,
  end = NULL,
  info = c("All", "Data", "None")
)

transfer_series(
  jsap_from,
  jsap_to,
  selected_sa_items,
  print_indications = TRUE
)

.jws_add(jws, jsap)

set_domain_specification(jsap, idx, spec)
```

```
get_domain_specification(jsai)
```

```
get_point_specification(jsai)
```

Arguments

```
jmp, idx, jws, name, jsa, jsai, jsap, items, key, file, compute
```

Parameters.

```
policy, period, start, end, info, modelling_context, jsap_from
```

Parameters.

```
jsap_to, selected_sa_items, print_indications, spec
```

Parameters.

Value

The same value as returned by the corresponding non-deprecated function. The returned object represents an encoded identifier for a spreadsheet series or collection.

get-results

Extract results from a SA-item

Description

`get_results()` extracts the results of a SA-item. `jsai_results()` extracts specific output of the model of the SA-item. `jsai_jresults()` extracts the Java object of the results of a SA-item.

Usage

```
get_results(jsai)
```

```
jsai_results(jsai, items = NULL)
```

```
jsai_jresults(jsai)
```

Arguments

`jsai` Java SA-item object.

`items` vector of characters containing the variables to extract. See [rjd3x13::x13_dictionary\(\)](#) or [rjd3tramoseats::tramoseats_dictionary\(\)](#). By default, extracts all the possible variables.

Value

List with all the results of the adjustment.

get-specification	<i>Get Specification in a Sa-Item</i>
-------------------	---------------------------------------

Description

get_estimation_specification() extract the estimation specification, get_reference_specification() reference specification, , get_result_specification() result specification

Usage

```
get_reference_specification(jsai)
```

```
get_estimation_specification(jsai)
```

```
get_result_specification(jsai)
```

Arguments

jsai Java SA-item object.

Value

the requested specification

References

More information on different types of specifications in JDemetra+ documentation: <https://doc.jdemetra.org/t-gui-sa-modelling-features#Spec-Def-App>

Examples

```
# Load a Workspace to modify
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

jws <- jws_open(file)

# Select SAProcessing with the target SA-item
jsap1 <- jws_sap(jws, 1)
jsai1 <- jsap_sai(jsap1, 1)

# Get the reference specification in targeted SA-item
get_reference_specification(jsai1)

# Get the estimation specification in targeted SA-item
get_estimation_specification(jsai1)

# Get the result specification in targeted SA-item
get_result_specification(jsai1)
```

get_context	<i>Get Context from Workspace</i>
-------------	-----------------------------------

Description

Get Context from Workspace

Usage

```
get_context(jws)
```

Arguments

jws the Workspace.

Value

The modelling context (list object with Calendars and Variables).

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Get context
my_context <- get_context(jws)
```

get_metadata	<i>Extract Metadata from a SA-Item</i>
--------------	--

Description

Extract specific metadata or time series metadata of a SA-item.

Usage

```
get_metadata(jsai, key)

get_ts_metadata(jsai, key)
```

Arguments

jsai	Java SA-item object.
key	key of the metadata.

Value

The corresponding metadata (character, numeric...)

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Select SAProcessing
jsap1 <- jws_sap(jws, 1)

# Select SA-item (as java object)
jsai1 <- jsap_sai(jsap1, 3)

# Extract the comment as metadata
get_metadata(jsai1, "comment")

# Extract the ts metadata
get_metadata(jsai1, "@id")
get_metadata(jsai1, "@source")
get_metadata(jsai1, "@timestamp")
```

jsap_make_copy

*Copy a Workspace or SA-Processing***Description**

Copy a Workspace or SA-Processing

Usage

```
jsap_make_copy(jsap)

jws_make_copy(jws)
```

Arguments

jws, jsap	Java Workspace or SA-Processing
-----------	---------------------------------

Details

The copy of a SA-processing will be made in the same workspace. The modelling context of the workspace is also copied.

Value

Returns a Java object workspace or SA-Processing

References

More information on workspaces in JDemetra+ Graphical User Interface: <https://doc.jdemetra.org/t-gui-sa-modelling-features/>

See Also

[read_workspace\(\)](#), [read_sap\(\)](#)

Examples

```
# Create an empty 'JDemetra+' Workspace
jws <- jws_new()

# Add an empty SA-Processing
jsap <- jws_sap_new(jws, "sap1")

# Make a copy of the workspace
jws2 <- jws_make_copy(jws)

# Make a copy of sap1 in jws2
jsap2 <- jsap_make_copy(jsap)
```

jsap_refresh

Refresh a Workspace or SA-Processing

Description

Refresh a Workspace or SA-Processing

Usage

```
jsap_refresh(
  jsap,
  policy = c("FreeParameters", "Complete", "Outliers_StochasticComponent", "Outliers",
    "FixedParameters", "FixedAutoRegressiveParameters", "Fixed", "Current"),
  period = 0,
  start = NULL,
```

```

    end = NULL,
    info = c("All", "Data", "None")
  )

  jws_refresh(
    jws,
    policy = c("FreeParameters", "Complete", "Outliers_StochasticComponent", "Outliers",
      "FixedParameters", "FixedAutoRegressiveParameters", "Fixed", "Current"),
    period = 0,
    start = NULL,
    end = NULL,
    info = c("All", "Data", "None")
  )

```

Arguments

policy	refresh policy to apply (see details).
period, start, end	additional parameters used to specify the span When policy = "Outliers" or policy = "Outliers_StochasticComponent" period: numeric, number of observations in a year (12, 4...), compulsory, if mis-specified or missing, re-estimation with refreshed specification won't work. end has to be specified as the date from which outliers will be re-identified
info	indication on how data should be refreshed • All: data and metadata will be refreshed (default) • Data: data will be refreshed, not metadata • None: nor data neither metadata will be refreshed, to be used for updating specifications only.
jws, jsap	Java Workspace or SA-Processing

Details

A particular selection of parameters to be kept fixed or re-estimated is called a revision policy. Workspace has to be computed before refresh When refreshing data, empty your cache by restarting your R session, before refreshing, otherwise the specification will be refreshed but the new data will not be taken into account.

Available refresh policies are:

1. **Fixed:** applying the current pre-adjustment reg-arma model and replacing forecasts by new raw data points; X11 (or SEATS) and Benchmarking part parameters are untouched.
2. **FixedParameters:** pre-adjustment reg-arma model is partially modified: regression coefficients will be re-estimated but regression variables, Arima orders and coefficients are unchanged; X11 (or SEATS) and Benchmarking part parameters are untouched.
3. **FixedAutoRegressiveParameters:** same as FixedParameters but Arima Moving Average coefficients (MA) are also re-estimated, Auto-regressive (AR) coefficients are kept fixed; X11 (or SEATS) and Benchmarking part parameters are untouched.

4. **FreeParameters:** all regression and Arima model coefficients are re-estimated, regression variables and Arima orders are kept fixed; X11 (or SEATS) and Benchmarking part parameters are untouched.
5. **Outliers:** regression variables and Arima orders are kept fixed, but outliers will be re-detected on the defined span, thus all regression and Arima model coefficients are re-estimated; X11 (or SEATS) and Benchmarking part parameters are untouched.
6. **Outliers_StochasticComponent:** same as "Outliers" but Arima model orders (p,d,q)(P,D,Q) can also be re-identified; X11 (or SEATS) and Benchmarking part parameters are untouched.
7. **Complete:** All the parameters are re-identified and re-estimated, unless constrained in the reference spec. X11 (or SEATS) and Benchmarking part parameters are entirely reset to values in the reference specification.

Value

refreshed workspace or SAP

References

More information on revision policies in JDemetra+ documentation: <https://doc.jdemetra.org/a-rev-policies>

Examples

```
# Load workspace
file <- system.file("workspaces", "workspace_test_refresh.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)
txt_update_path(
  jws = jws,
  new_path = system.file("extdata", "IPI_nace4.csv",
                        package = "rjd3workspace")
)
jws_compute(jws)

# Read current workspace: reference spec and estimation spec
jws1 <- jws_make_copy(jws)
rws <- read_workspace(jws1, compute = TRUE)
rws$processing$`SAProcessing-1`$`RF0811`$referenceSpec
rws$processing$`SAProcessing-1`$`RF0811`$estimationSpec

# Refresh workspace COMPLETE
jws2 <- jws_make_copy(jws)
jws_refresh(jws2, policy = "Complete")

# Read refreshed workspace: new estimation spec
rws2 <- read_workspace(jws2, compute = TRUE)
rws2$processing$`SAProcessing-1`$`RF0811`$estimationSpec
```

```
# Refresh workspace Outliers (like "lastoutliers in the GUI, but with custom start date)
jws3 <- jws_make_copy(jws)
jws_refresh(jws3, policy = "Outliers", period = 12, end = c(2020, 4))

# Read refreshed workspace: new estimation spec
rws3 <- read_workspace(jws3, compute = TRUE)
rws3$processing$`SAProcessing-1`$`RF0811`$estimationSpec
```

jsap_sai

*Extract a SA-Processing or a SA-Item***Description**

Functions allowing to extract a SA-Processing from a Workspace using its order number (index) and a SA-Item from a SA-Processing its order number (index). The original object is unaltered.

Usage

```
jsap_sai(jsap, idx)
```

```
jws_sap(jws, idx)
```

Arguments

idx	index of the object to extract.
jws, jsap	Workspace or SA-Processing.

Value

Returns a Javaobject SA-Processing or SA-Item.

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Compute the workspace to enable accessing its components
jws_compute(jws)

# Extract 2nd SA-Processing
jsap2 <- jws_sap(jws, 2)

# Extract 3rd SA-item
```

```
jsai3 <- jsap_sai(jsap2, 3)
```

jws_add*Add a SA-Processing to a Workspace*

Description

Add a SA-Processing to a Workspace

Usage

```
jws_add(jws, jsap)
```

Arguments

jws, jsap Java Workspace or SA-Processing

Value

Invisibly NULL

jws_compute*Compute a Workspace*

Description

jws_compute() allows to extract all the SA-Items as Javaobject.

Usage

```
jws_compute(jws)
```

Arguments

jws a workspace

Value

Invisibly NULL

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Compute the workspace to access its components
jws_compute(jws)
```

jws_new	<i>Create a Workspace or SA-Processing</i>
---------	--

Description

Functions creating a 'JDemetra+' Workspace (`jws_new()`) and adding a new SA-Processing (`jws_sap_new()`). A modelling context can be added to a workspace, it will be valid for all its SA-Processings.

Usage

```
jws_new(modelling_context = NULL)

jws_sap_new(jws, name)
```

Arguments

modelling_context	a list of variables and calendars
jws	a Javaworkspace object.
name	name of the new SA-Processing to be added (character).

Details

A modelling context is a list of variables to be used as external regressors in modelling processes (Reg-Arima or Tramo) or calendars to be used to generate calendar regressors. It can be created with `rjd3toolkit::modelling_context()` function or retrieved from another workspace (`((set_context))`)

Value

Returns a Javaobject workspace or SA-Processing.

References

More information on workspaces in JDemetra+ Graphical User Interface: <https://doc.jdemetra.org/t-gui-sa-modelling-features/>

See Also

[read_workspace\(\)](#), [read_sap\(\)](#)

Examples

```
# Create an empty 'JDemetra+' Workspace
jws <- jws_new()
# Add an empty SA-Processing
jsap <- jws_sap_new(jws, "sap1")
```

jws_open

Open an existing 'JDemetra+' Workspace

Description

jws_open() opens an existing Workspace (as a Java pointer) and jws_compute() computes it (allowing to extract all the SA-Items as Java objects).

Usage

```
jws_open(file)
```

Arguments

file path to Workspace xml master file By default a dialog box opens.

Value

a Javaworkspace

See Also

[read_workspace\(\)](#) to transform the workspace in a R list.

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Compute the workspace to enable access its components
jws_compute(jws)
```

read_calendars	<i>Read a Calendar file</i>
----------------	-----------------------------

Description

The calendar file is a xml file like the one JDemetra+ would write when defining a calendar in the Graphical User Interface.

Usage

```
read_calendars(file)
```

Arguments

file	path to a calendar file (in xml format)
------	---

Value

a list of JD3_CALENDAR objects

Examples

```
file <- system.file("workspaces", "workspace_test", "Calendars",  
                    "Calendars.xml", package = "rjd3workspace")  
my_calendar <- read_calendars(file)  
my_calendar
```

read_sai	<i>Read an SA-item</i>
----------	------------------------

Description

read_sai() extracts all the information of a SA-item (see details).

Usage

```
read_sai(jsai)
```

Arguments

jsai	Java SA-item object.
------	----------------------

Details

A SA-item contains more information than just the results of an estimation. Full information is extracted with the `read_sai()` function that returns a list of 5 objects:

- `ts`: raw time series.
- `referenceSpec`: initial specification. Reference when refreshing and relaxing constraints.
- `estimationSpec`: specification used for the current estimation.
- `resultSpec`: specification containing all parameters stemming from `estimationSpec` (fully identified model).
- `results`: results of the estimation.

Value

a list

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Select SAProcessing
jsap1 <- jws_sap(jws, 1)

# Select SA-item (as java object)
jsai1 <- jsap_sai(jsap1, 3)

# read SA-item
read_sai(jsai = jsai1)
```

read_sap

Read all SA-Items from a Workspace or SA-Processing

Description

Functions reading all SA-Items from a Workspace (`read_workspace()`) or a SA-Processing (`read_sap()`) and allowing to access them as R lists. Whereas functions `jread_sap()` and `jread_workspace()` only return corresponding Java objects

Usage

```
read_sap(jsap)

jread_sap(jsap)

read_workspace(jws, compute = TRUE)

jread_workspace(jws, compute = TRUE)
```

Arguments

jsap	Java SA-Processing.
jws	Java Workspace.
compute	compute or not the workspace (to get the estimation results).

Value

list or Java object

Examples

```
# Load workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Read workspace
jread_workspace(jws, compute = FALSE)

rws <- read_workspace(jws)

# Read sap
sap <- jws_sap(jws, 1)
jread_sap(sap)
read_sap(sap)
```

read_variables	<i>Read auxiliary regressors file</i>
----------------	---------------------------------------

Description

The variables (regressors) file is a xml file like the one JDemetra+ would write when setting-up user defined regressors in the Graphical User Interface.

Usage

```
read_variables(file)
```

Arguments

```
file          xml format
```

Value

A named list of time series objects.

Examples

```
file <- system.file("workspaces", "workspace_test", "Variables",
                    "Vars-1.xml", package = "rjd3workspace")
my_regressors <- read_variables(file)
class(my_regressors)
str(my_regressors)
```

regarima_read_spec	<i>Read a Reg-Arima specification file</i>
--------------------	--

Description

The specification file is a xml file like the one JDemetra+ would write when defining a specification in the Graphical User Interface.

Usage

```
regarima_read_spec(file)
```

Arguments

```
file          xml format,
```

Value

```
list
```

Examples

```
file <- system.file("workspaces", "workspace_test", "RegArimaSpec",
                    "RegArimaSpec-1.xml", package = "rjd3workspace")
my_spec<-regarima_read_spec(file)
class(my_spec)
str(my_spec)
```

regarima_write_spec	<i>Write a Reg-Arima specification file</i>
---------------------	---

Description

The specification file is a xml file like the one JDemetra+ would write when defining a specification in the Graphical User Interface.

Usage

```
regarima_write_spec(spec, file)
```

Arguments

spec	a specification created with <code>rjd3x13::regarima_spec</code>
file	xml format

Value

NULL returned invisibly

Examples

```
# Creating a spec from default
regarima_spec <- rjd3x13::regarima_spec("rg3")

# Forcing multiplicative model
regarima_spec_d <- rjd3toolkit::set_transform(
  regarima_spec ,
  fun = "Log",
  outliers = TRUE
)

# Writing the specification in a xml file
spec_path <- tempfile(fileext = ".xml")
regarima_write_spec(regarima_spec_d, file = spec_path)
```

replace_sa_item	<i>Replace or Remove a SA-item</i>
-----------------	------------------------------------

Description

`replace_sa_item()` replaces a SA-item in a `SAProcessing` and `remove_sa_item()` removes a SA-item from a `SAProcessing` `remove_all_sa_item()` removes all SA-item from a `SAProcessing`

Usage

```
replace_sa_item(jsap, idx, jsai)

remove_sa_item(jsap, idx)

remove_all_sa_item(jsap)
```

Arguments

- jsap SProcessing to be modified.
- idx index of the target SA-item.
- jsai new SA-item (for replacement).

Value

NULL returned invisibly

sai_name	<i>Get the name of a SProcessing or one (or all) Sa-item</i>
----------	--

Description

Functions to retrieve the name of a SProcessing (sap_name()) or Sa-item (sai_name()) or all SA-item (sap_sai_names()) .

Usage

```
sai_name(jsai)

sap_name(jsap)

sap_sai_names(jsap)
```

Arguments

- jsap, jsai the object to retrieve the name from.

Value

A vector character.

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Extract 2nd SA-Processing
jsap_2 <- jws_sap(jws, 2)

# Retrieve the name
sap_name(jsap_2)

# Retrieve all the SA-items names
sap_sai_names(jsap_2)
```

sap_sai_count	<i>Count SA-Processings or SA-Items</i>
---------------	---

Description

Functions counting the SA-Processings in a Workspace (`ws_sap_count`) or the SA-Items in a SA-Processing (`sap_sai_count`).

Usage

```
sap_sai_count(jsap)

ws_sap_count(jws)
```

Arguments

jws, jsap Workspace or SA-Processing.

Value

Returns an integer.

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)
```

```
# Count the SA-Processings
ws_sap_count(jws)

# Count the SA-Items
# In SAP 1
sap1 <- jws_sap(jws, 1)
sap_sai_count(sap1)
```

save_workspace	<i>Save Workspace</i>
----------------	-----------------------

Description

Function allowing to write a workspace as a collection of xml files readable by JDemetra+ Graphical User Interface.

Usage

```
save_workspace(jws, file, replace = FALSE, verbose = TRUE)
```

Arguments

jws	Workspace object to export.
file	path where to export the 'JDemetra+' Workspace (.xml file).
replace	boolean indicating if the Workspace should be replaced if it already exists.
verbose	Boolean indicating whether to print additional information. Default is TRUE.

Value

A boolean indicating if the saving was successful.

Examples

```
dir <- tempdir()
jws <- jws_new()
jsap1 <- jws_sap_new(jws, "sap1")
y <- rjd3toolkit::ABS$X0.2.09.10.M

add_sa_item(jsap1, name = "serie_1", x = y, rjd3x13::x13_spec())
save_workspace(jws, file.path(dir, "workspace.xml"))
```

set_comment	<i>Get/Set Comment from a SA-item</i>
-------------	---------------------------------------

Description

Get/Set Comment from a SA-item

Usage

```
set_comment(jsap, idx, comment)
```

```
get_comment(jsai)
```

Arguments

jsap	SAProcessing to be modified.
idx	index of the target SA-item.
comment	character containing the comment.
jsai	a SA-item.

Value

NULL returned invisibly

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

jws <- jws_open(file)

# Select SAProcessing
jsap1 <- jws_sap(jws, 1L)

# Add a comment
set_comment(jsap1, 2L, "data collection changed in 2012")

jsai2 <- jsap_sai(jsap1, 2L)
get_comment(jsai2)
```

set_context	<i>Set Context of a Workspace</i>
-------------	-----------------------------------

Description

Set Context of a Workspace

Usage

```
set_context(jws, modelling_context = NULL)
```

Arguments

jws a Javaworkspace object.
 modelling_context a list of variables and calendars

Value

Invisibly NULL

Examples

```
library("rjd3toolkit")

# French calendar
french_calendar <- national_calendar(
  days = list(
    # Bastille Day
    fixed_day(7, 14),
    # End of 2nd WW
    fixed_day(5, 8, validity = list(start = "1982-05-08")),
    special_day("NEWYEAR"),
    special_day("CHRISTMAS"),
    special_day("MAYDAY"),
    special_day("EASTERMONDAY"),
    special_day("ASCENSION"),
    special_day("WHITMONDAY"),
    special_day("ASSUMPTION"),
    special_day("ALLSAINTSDAY"),
    special_day("ARMISTICE")
  )
)

# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
  package = "rjd3workspace")

jws <- jws_open(file)
```

```
# Creating a new context
new_context <- modelling_context(
  calendars = list(FR = french_calendar),
  variables = list(a = AirPassengers)
)

# Set the context
set_context(jws, new_context)
```

set_name	<i>Set the name of a SA-item</i>
----------	----------------------------------

Description

Set the name of a SA-item

Usage

```
set_name(jsap, idx, name)
```

Arguments

jsap	SAProcessing to be modified.
idx	index of the target SA-item.
name	character corresponding to the new name

Value

NULL returned invisibly

See Also

[sai_name\(\)](#)

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

jws <- jws_open(file)

# Select SAProcessing
sap1 <- jws_sap(jws,1)

# Select SA-item
sai1 <- jsap_sai(sap1,3) # java object sai
```

```
# set name
set_name(sap1,3,"RF1011_1")

# check
sai1 <- jsap_sai(sap1,3) # reload sai
sai_name(sai1) #get name
```

set_priority	<i>Get/Set SA-item Priority</i>
--------------	---------------------------------

Description

Get/Set SA-item Priority

Usage

```
set_priority(jsap, idx, priority = 0L)

get_priority(jsai)
```

Arguments

jsap	SAProcessing to be modified.
idx	index of the target SA-item.
priority	integer containing the priority.
jsai	a SA-item.

Value

set_priority returns NULL invisibly. get_priority returns the priority (an integer).

Examples

```
# Load a workspace
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

my_jws <- jws_open(file)

# Select the first SA-Processing and SA-Item
jsap <- jws_sap(my_jws, 1)
jsai <- jsap_sai(jsap, 1L)

# Change priority
set_priority(jsap, idx = 1L, priority = 3L)
```

```
# Retrieve priority
get_priority(jsai)
```

set_raw_data	<i>Get/Set Raw Data in a SA-item</i>
--------------	--------------------------------------

Description

Get/Set Raw Data in a SA-item

Usage

```
set_raw_data(jsap, idx, y)

get_raw_data(jsai)
```

Arguments

jsap	SAProcessing to be modified.
idx	index of the target SA-item.
y	new raw time series.
jsai	a SA-item.

Value

NULL returned invisibly (set) or TS object (get)

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

jws <- jws_open(file)

# Select SAProcessing
sap1 <- jws_sap(jws, 1)

# Select SA-item
sai1 <- jsap_sai(sap1, 3) # java object sai
tail(get_raw_data(sai1))

new_raw_data <- rjd3toolkit::ABS$X0.2.15.10.M
set_raw_data(sap1, 3, new_raw_data)
```

```
sai1 <- jsap_sai(sap1,3) # reload SA-item
tail(get_raw_data(sai1)) # get raw data
```

set_specification	<i>Set Specification in a Sa-Item</i>
-------------------	---------------------------------------

Description

Set Specification in a Sa-Item

Usage

```
set_specification(jsap, idx, spec)

set_reference_specification(jsap, idx, spec)
```

Arguments

jsap	SAProcessing to be modified.
idx	index of the target SA-item.
spec	new specification generated with <code>rjd3x13::x13_spec()</code> or <code>rjd3tramoseats::tramoseats_spec()</code>

Value

NULL returned invisibly

References

More information on different types of specifications in JDemetra+ documentation: <https://doc.jdemetra.org/t-gui-sa-modelling-features#Spec-Def-App>

Examples

```
# Create a (customized) spec) spec
library(rjd3x13)

spec <- rjd3x13::x13_spec("rsa3") |>
  rjd3toolkit::set_basic(type = "From", d0 = "2012-01-01")

# Load a Workspace to modify
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")
jws <- jws_open(file)

# Select SAProcessing with the target SA-item
sap1 <- jws_sap(jws, 1)
```

```
# Set specification in targeted SA-item
set_specification(sap1, 2, spec)

# Set reference specification in selected SA-item
set_reference_specification(sap1, 3, spec)
```

set_ts

Get/Set the (JDemetra+) time series of a SA-item

Description

(JDemetra+) time series contains more information than raw data, which can be manipulated with `set_raw_data()` and `get_raw_data()`

Usage

```
set_ts(jsap, idx, y)

get_ts(jsai)
```

Arguments

jsap	SAProcessing to be modified.
idx	index of the target SA-item.
y	a "full" time series (jd3-like).
jsai	a SA-item.

Value

NULL returned invisibly

Examples

```
# Load a workspace
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

my_jws <- jws_open(file)

library("rjd3providers")
data_path <- system.file("extdata", "IPI_nace4.csv", package = "rjd3workspace")

ts_object <- txt_series(
  file = data_path,
  series = 1L,
  delimiter = "SEMICOLON",
  fmt.date = "dd/MM/yyyy")
```

```

)

# Select the first SA-Processing
jsap <- jws_sap(my_jws, 1L)

# Change the ts object
set_ts(jsap = jsap, idx = 1L, ts_object)

jsai1 <- jsap_sai(jsap, 1L)
jsai2 <- jsap_sai(jsap, 2L)
jsai3 <- jsap_sai(jsap, 3L)

# Get the ts object
get_ts(jsai1)
get_ts(jsai2)
get_ts(jsai3)

```

set_ts_metadata	<i>Set (JDemetra+) Metadata of a SA-item</i>
-----------------	--

Description

Function to set the metadata of a SA-item.

XXX_ts_metadata() set the time series metadata of a SA-item (provider, source of the data...).

XXX_metadata() set any metadata to a SA-Item.

set_XXX() uses the metadata of another SA-item while put_XXX() allows to update a specific key with a new information.

Usage

```

set_ts_metadata(jsap, idx, ref_jsai)

put_ts_metadata(jsap, idx, key, value)

set_metadata(jsap, ref_jsai, idx)

put_metadata(jsap, idx, key, value)

```

Arguments

jsap	SAProcessing to be modified.
idx	index of the target SA-item.
ref_jsai	a reference SA-item containing the metadata.
key	key of the metadata.
value	value of the metadata.

Value

NULL returned invisibly.

Examples

```
# Change the file of a given item
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

jws <- jws_open(file)
jsap <- jws_sap(jws, 1)
jsai <- jsap_sai(jsap, 1)
nid <- rjd3providers::txt_change_file(get_ts_metadata(jsai, "@id"), "test.csv")
put_ts_metadata(jsap, 1, "@id", nid)

jsai <- jsap_sai(jsap, 1)
get_ts_metadata(jsai, "@id")
```

spreadsheet_update_path

Update the path to raw data in a workspace (spreadsheet)

Description

Update the path to raw data in a workspace (spreadsheet)

Usage

```
spreadsheet_update_path(jws, new_path, idx_sap = NULL, idx_sai = NULL)
```

Arguments

jws	workspace object
new_path	new path to the spreadsheet containing raw data
idx_sap	index (or indices) of the SAProcessing(s)
idx_sai	index (or indices) of the SA-item(s).

Details

The spreadsheet file must be a .xlsx file. .xls files are not accepted in JDemetra+ v3.x.

Value

This function returns either NULL if the update was successful, or an error.

Examples

```
# Load a workspace
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

my_ws <- jws_open(file)

# Update the entire second SA-Processing of the `my_ws` workspace with a new path to raw data
spreadsheet_update_path(
  jws = my_ws,
  new_path = system.file("extdata", "IPI_nace4.xlsx", package = "rjd3workspace"),
  idx_sap = 2
)

# Select one (the 2nd) SA-item from second SA-Processing
sap2 <- jws_sap(my_ws, 2)
sai2 <- jsap_sai(sap2, 2)

# Check path
get_ts_metadata(sai2, "@id")
```

tramoseats_read_spec *Read a Tramo-Seats specification file*

Description

The specification file is a xml file like the one JDemetra+ would write when defining a specification in the Graphical User Interface.

Usage

```
tramoseats_read_spec(file)
```

Arguments

file xml format,

Value

list

Examples

```
file <- system.file("workspaces", "workspace_test", "TramoSeatsSpec",
  "TramoSeatsSpec-1.xml", package = "rjd3workspace")
my_spec<- tramoseats_read_spec(file)
class(my_spec)
str(my_spec)
```

tramoseats_write_spec *Write a Tramo-Seats specification file*

Description

The specification file is a xml file like the one JDemetra+ would write when defining a specification in the Graphical User Interface.

Usage

```
tramoseats_write_spec(spec, file)
```

Arguments

spec	a specification created with <code>rjd3tramoseats::tramoseats_spec</code>
file	xml format

Value

NULL returned invisibly

Examples

```
# Creating a spec from default
tramoseats_spec <- rjd3tramoseats::tramoseats_spec("tr3")

# Forcing multiplicative model
tramoseats_spec_d <- rjd3toolkit::set_transform(
  tramoseats_spec ,
  fun = "Log",
  outliers = TRUE
)

# Writing the specification in a xml file
spec_path <- tempfile(fileext = ".xml")
tramoseats_write_spec(tramoseats_spec_d, file = spec_path)
```

tramo_read_spec *Read a Tramo specification file*

Description

The specification file is a xml file like the one JDemetra+ would write when defining a specification in the Graphical User Interface.

Usage

```
tramo_read_spec(file)
```

Arguments

file xml format,

Value

list

Examples

```
file <- system.file("workspaces", "workspace_test", "TramoSpec",
                    "TramoSpec-1.xml", package = "rjd3workspace")
my_spec<- tramo_read_spec(file)
class(my_spec)
str(my_spec)
```

tramo_write_spec	<i>Write a Tramo specification file</i>
------------------	---

Description

The specification file is a xml file like the one JDemetra+ would write when defining a specification in the Graphical User Interface.

Usage

```
tramo_write_spec(spec, file)
```

Arguments

spec a specification created with `rjd3tramoseats::tramo_spec`

file xml format

Value

NULL returned invisibly

Examples

```
# Creating a spec from default
tramo_spec <- rjd3tramoseats::tramo_spec("tr3")

# Forcing multiplicative model
tramo_spec_d <- rjd3toolkit::set_transform(
  tramo_spec ,
  fun = "Log",
  outliers = TRUE
)

# Writing the specification in a xml file
spec_path <- tempfile(fileext = ".xml")
tramo_write_spec(tramo_spec_d, file = spec_path)
```

transfer_sa_item	<i>Copy & paste SA-items from one SA-Processing to another</i>
------------------	--

Description

Copy & paste SA-items from one SA-Processing to another

Usage

```
transfer_sa_item(
  jsap_from,
  jsap_to,
  selected_sa_items,
  print_indications = TRUE
)
```

Arguments

jsap_from	SA-Processing from which to take the SA-items
jsap_to	SA-Processing to which paste the SA-items
selected_sa_items	vector containing the SA-items names to be updated.
print_indications	A boolean to print indications on the processing status (optional)

Details

If selected_sa_items is missing, all SA-items from jsap_from will be copied.

Value

NULL returned invisibly

txt_update_path	<i>Update the path to raw data in a workspace (txt/csv file)</i>
-----------------	--

Description

Update the path to raw data in a workspace (txt/csv file)

Usage

```
txt_update_path(jws, new_path, idx_sap = NULL, idx_sai = NULL)
```

Arguments

jws	workspace object
new_path	new path to the csv/txt file containing raw data.
idx_sap	index (or indices) of the SAProcessing(s)
idx_sai	index (or indices) of the SA-item(s).

Value

This function returns either NULL if the update was successful, or an error

Examples

```
# Load a workspace
file <- system.file("workspaces", "workspace_test.xml", package = "rjd3workspace")

my_ws <- jws_open(file)

# Update the entire second SA-Processing of the `my_ws` workspace with a new path to raw data
txt_update_path(
  jws = my_ws,
  new_path = system.file("extdata", "IPI_nace4.csv", package = "rjd3workspace"),
  idx_sap = 1
)

# Select one (the 2nd) SA-item from first SA-Processing
sap1 <- jws_sap(my_ws, 1)
sai2 <- jsap_sai(sap1, 2)

# Check path
get_ts_metadata(sai2, "@id")
```

write_calendars	<i>Write a Calendar file</i>
-----------------	------------------------------

Description

The calendar file is a xml file like the one JDemetra+ would write when defining a calendar in the Graphical User Interface. Calendars can be defined with `rjd3toolkit::national_calendar`

Usage

```
write_calendars(calendars, file, verbose = TRUE)
```

Arguments

calendars	named list of calendars or a JD3_CALENDAR object
file	xml format
verbose	Boolean indicating whether to print additional information. Default is TRUE.

Details

If calendars is a single calendar (JD3_CALENDAR object), it will be named cal by default. If calendars is a list of calendars (JD3_CALENDAR object). Then they all must be named. Else, a error is risen.

Value

NULL returned invisibly

Examples

```
library("rjd3toolkit")
BE <- national_calendar(list(
  fixed_day(7, 21),
  special_day("NEWYEAR"),
  special_day("CHRISTMAS"),
  special_day("MAYDAY"),
  special_day("EASTERMONDAY"),
  special_day("ASCENSION"),
  special_day("WHITMONDAY"),
  special_day("ASSUMPTION"),
  special_day("ALLSAINTSDAY"),
  special_day("ARMISTICE")
))

calendar_path <- tempfile(pattern = "calendar", fileext = ".xml")

write_calendars(BE, file = calendar_path)
write_calendars(list(BEL_cal = BE), file = calendar_path)
```

write_variables	<i>Write regressors file</i>
-----------------	------------------------------

Description

Write regressors file

Usage

```
write_variables(vars, file)
```

Arguments

vars	A named list of ts objects.
file	Path to the output XML file.

Value

No return value (NULL returned invisibly). This function writes variables to file for use in JD+.

Examples

```
# Load a Workspace
file <- system.file("workspaces", "workspace_test.xml",
                    package = "rjd3workspace")

jws <- jws_open(file)

# Get context
my_context <- get_context(jws)
vars <- my_context$variables[[1L]]

# Writing the regressors in a xml file
variable_path <- tempfile(fileext = ".xml")
write_variables(vars, file = variable_path)
```

x13_read_spec	<i>Read a X13 specification file</i>
---------------	--------------------------------------

Description

The specification file is a xml file like the one JDemetra+ would write when defining a specification in the Graphical User Interface.

Usage

```
x13_read_spec(file)
```

Arguments

file xml format,

Value

list

Examples

```
file <- system.file("workspaces", "workspace_test", "X13Spec",
                    "X13Spec-1.xml", package = "rjd3workspace")
my_spec<-x13_read_spec(file)
class(my_spec)
str(my_spec)
```

x13_write_spec	<i>Write a X13 specification file</i>
----------------	---------------------------------------

Description

The specification file is a xml file like the one JDemetra+ would write when defining a specification in the Graphical User Interface.

Usage

```
x13_write_spec(spec, file)
```

Arguments

spec a specification created with `rjd3x13::x13_spec`
 file xml format

Value

NULL returned invisibly

Examples

```
# Creating a spec from default
x13_spec <- rjd3x13::x13_spec("rsa3")

# Forcing multiplicative model
x13_spec_d <- rjd3toolkit::set_transform(
  x13_spec ,
  fun = "Log",
  outliers = TRUE
)

# Writing the specification in a xml file
spec_path <- tempfile(fileext = ".xml")
x13_write_spec(x13_spec_d, file = spec_path)
```

Index

.jd2r_spec, [3](#)
.jmp_load (deprecated-rjd3workspace), [7](#)
.jmp_name (deprecated-rjd3workspace), [7](#)
.jmp_sa (deprecated-rjd3workspace), [7](#)
.jmp_sa_count
 (deprecated-rjd3workspace), [7](#)
.jmp_sa_name
 (deprecated-rjd3workspace), [7](#)
.jread_sap (deprecated-rjd3workspace), [7](#)
.jread_workspace
 (deprecated-rjd3workspace), [7](#)
.jsa_jresults
 (deprecated-rjd3workspace), [7](#)
.jsa_metadata
 (deprecated-rjd3workspace), [7](#)
.jsa_read (deprecated-rjd3workspace), [7](#)
.jsa_results
 (deprecated-rjd3workspace), [7](#)
.jsa_ts_metadata
 (deprecated-rjd3workspace), [7](#)
.jsai_jresults
 (deprecated-rjd3workspace), [7](#)
.jsai_metadata
 (deprecated-rjd3workspace), [7](#)
.jsai_name (deprecated-rjd3workspace), [7](#)
.jsai_results
 (deprecated-rjd3workspace), [7](#)
.jsai_ts_metadata
 (deprecated-rjd3workspace), [7](#)
.jsap_make_copy
 (deprecated-rjd3workspace), [7](#)
.jsap_name (deprecated-rjd3workspace), [7](#)
.jsap_refresh
 (deprecated-rjd3workspace), [7](#)
.jsap_sa (deprecated-rjd3workspace), [7](#)
.jsap_sa_count
 (deprecated-rjd3workspace), [7](#)
.jsap_sa_name
 (deprecated-rjd3workspace), [7](#)
.jsap_sai (deprecated-rjd3workspace), [7](#)
.jsap_sai_count
 (deprecated-rjd3workspace), [7](#)
.jsap_sai_names
 (deprecated-rjd3workspace), [7](#)
.jws_add (deprecated-rjd3workspace), [7](#)
.jws_compute
 (deprecated-rjd3workspace), [7](#)
.jws_make_copy
 (deprecated-rjd3workspace), [7](#)
.jws_new (deprecated-rjd3workspace), [7](#)
.jws_open (deprecated-rjd3workspace), [7](#)
.jws_refresh
 (deprecated-rjd3workspace), [7](#)
.jws_sap (deprecated-rjd3workspace), [7](#)
.jws_sap_count
 (deprecated-rjd3workspace), [7](#)
.jws_sap_new
 (deprecated-rjd3workspace), [7](#)

add_calendar, [3](#)
add_sa_item, [4](#)
add_variables, [6](#)

deprecated-rjd3workspace, [7](#)

get-results, [10](#)
get-specification, [11](#)
get_comment (set_comment), [29](#)
get_context, [12](#)
get_domain_specification
 (deprecated-rjd3workspace), [7](#)
get_estimation_specification
 (get-specification), [11](#)
get_metadata, [12](#)
get_point_specification
 (deprecated-rjd3workspace), [7](#)
get_priority (set_priority), [32](#)
get_raw_data (set_raw_data), [33](#)

get_reference_specification
 (get-specification), 11
 get_result_specification
 (get-specification), 11
 get_results (get-results), 10
 get_ts (set_ts), 35
 get_ts_metadata (get_metadata), 12

 jread_sap (read_sap), 22
 jread_workspace (read_sap), 22
 jsai_jresults (get-results), 10
 jsai_results (get-results), 10
 jsap_make_copy, 13
 jsap_refresh, 14
 jsap_sai, 17
 jws_add, 18
 jws_compute, 18
 jws_make_copy (jsap_make_copy), 13
 jws_new, 19
 jws_open, 20
 jws_refresh (jsap_refresh), 14
 jws_sap (jsap_sai), 17
 jws_sap_new (jws_new), 19

 make_copy (jsap_make_copy), 13

 put_metadata (set_ts_metadata), 36
 put_ts_metadata (set_ts_metadata), 36

 read_calendars, 21
 read_sai, 21
 read_sap, 22
 read_sap(), 14, 20
 read_variables, 23
 read_variables(), 7
 read_workspace (read_sap), 22
 read_workspace(), 14, 20
 refresh (jsap_refresh), 14
 regarima_read_spec, 24
 regarima_write_spec, 25
 remove_all_sa_item (replace_sa_item), 25
 remove_sa_item (replace_sa_item), 25
 replace_sa_item, 25
 rjd3toolkit::complete_modelling_context(),
 6
 rjd3toolkit::modelling_context(), 7, 19
 rjd3tramoseats::tramoseats(), 5
 rjd3tramoseats::tramoseats_dictionary(),
 10

 rjd3tramoseats::tramoseats_spec(), 34
 rjd3x13::x13(), 5
 rjd3x13::x13_dictionary(), 10
 rjd3x13::x13_spec(), 34

 sai_name, 26
 sai_name(), 31
 sap_name (sai_name), 26
 sap_sai_count, 27
 sap_sai_names (sai_name), 26
 save_workspace, 28
 set_comment, 29
 set_context, 30
 set_domain_specification
 (deprecated-rjd3workspace), 7
 set_metadata (set_ts_metadata), 36
 set_name, 31
 set_priority, 32
 set_raw_data, 33
 set_reference_specification
 (set_specification), 34
 set_specification, 34
 set_ts, 35
 set_ts_metadata, 36
 spreadsheet_update_path, 37

 tramo_read_spec, 39
 tramo_write_spec, 40
 tramoseats_read_spec, 38
 tramoseats_write_spec, 39
 transfer_sa_item, 41
 transfer_series
 (deprecated-rjd3workspace), 7
 txt_update_path, 42

 write_calendars, 43
 write_variables, 44
 write_variables(), 7
 ws_sap_count (sap_sai_count), 27

 x13_read_spec, 44
 x13_write_spec, 45